



tolerance	variable range	linear dimension (Tolerances Standard GB/T 14486-2008)
±0.1	6 to 10	≡
±0.14	6 to 10	≡
±0.19	10 to 18	≡
±0.25	18 to 30	≡
±0.32	30 to 50	≡
±0.43	50 to 80	≡
±0.57	80 to 120	≡
±0.72	120 to 160	≡
±0.88	160 to 200	≡
±1.05	200 to 250	≡
±1.25	250 to 500	≡
0.5	all	≡
0.025	5 to 5	≡
0.06	5 to 30	≡
0.12	30 to 120	≡
0.4	120 to 500	≡

电气性能/Electrical

参考标准/Standard

额定电压/Rated voltage

额定电流/Rated current

接触电阻/Contact resistance

绝缘电阻/Insulation resistance

使用线径/Wire range

耐电压/Wrth standing voltage

机械性能/Mechanical

扭矩/Torque

剥线长度/Steip Length

温度范围/Temp.Range

瞬时温度/MAX Soldering

尺寸/Dimensions

间距/Pitch

极数/Poles

材质及电镀/Material

塑件/Housing

螺丝/Screws

焊脚/Pin header

方块/Cage

UL IEC

300V 250V

16A 24A

20mΩ

500MΩ/DC500V

26~12AWG 2.5mm²

AC 2000V/1 Min

0.5Nm(4.5lb.in)

6-7mm

-40°C~+105°C

+250°C, for 5 Sec

5.0mm,5.08mm

2~24p

PA66, UL94V-0

M3.0, Steel Zn plated

Brass, Tin plated

Brass Ni plated

单位/UNITS mm 尺寸/ SIZE A4 比例/SCALE 5:2

第三视角/THIRD ANGLE PROJECTION

名称/ TITLE

DB129V-5.0/5.08-XXP

Cixi Dibo Electronics Co., LTD

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Terminal Blocks](#) category:

Click to view products by [DIBO](#) manufacturer:

Other Similar products are found below :

[00175550202](#) [MBE-1512](#) [MBE-1520](#) [MBE-154](#) [MBE-156](#) [MBES-1510](#) [MBES-153](#) [MBES-156](#) [MH-2512](#) [MHE-132](#) [MHE-133](#) [MHE-163](#)
[MI-254 \(35\)](#) [MI-272](#) [8739](#) [880507](#) [880508](#) [MPT-275](#) [1546551-6](#) [ELM023100](#) [ELM10110G](#) [ELVD12100](#) [BA311TU](#) [BA411SU](#) [MV-152](#)
[MV-253/NCNOC](#) [MV-254-D](#) [MV-255](#) [MV-462](#) [MV-472](#) [MV-493](#) [MVE-252](#) [MVE-253](#) [MVE-258](#) [MVE-273](#) [MVEB-153](#) [1700096](#)
[1702246](#) [1705142](#) [1712417](#) [1713020](#) [1713088](#) [1776118-2](#) [1790852](#) [1-796689-8](#) [1-796692-6](#) [1800001](#) [1800114](#) [1823215](#) [1838462](#)