

电气性能/Electrical

参考标准/Standard: UL IEC
 额定电压/Rated voltage: 300V 320V
 额定电流/Rated current: 15A 20A
 接触电阻/Contact resistance: 20mΩ

耐电压/Withstanding voltage: AC2000V/1Min

绝缘电阻/Insulation resistance: 500MΩ/DC500V

机械性能/Mechanical

温度范围/Temp Range: -40°C~+105°C

瞬间温度/MAX Soldering: +250°C, for 5 Sec

尺寸/Dimensions

间距/Pitch: 7.5mm, 7.62mm

极数/Poles: 2P-24P

材质及电镀/Material

塑件/Housing: PA66, UL94V-0


焊针/Pin header: Brass, Tin plated

螺母/Nut: M2.5 Brass

TOLERANCES EXCEPT AS NOTED

	linear dimension	fillet	chamfer	短角 short angle sid	≡	—	□	//	⊥
variable range	over 6 to 30	over 120 to 480	all	over 6 to 10	over 10 to 50	over 50 to 120	all	over 5 to 30	over 30 to 120
tolerance	±0.1	±0.2	±0.2	±0.5	±1	1°	30°	10°	0.5
	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30°
	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30°	10°
	±0.5	±0.9	±0.2	±0.5	±1	1°	30°	10°	0.5
	±0.9	±0.2	±0.5	±1	1°	30°	10°	0.5	0.025
	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	0.06
	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30°	0.12
	±0.5	±0.9	±0.2	±0.5	±1	1°	30°	10°	0.4

订购方式: HOW TO ORDER



Cixi Dibo Electronics Co., LTD

名称/NAME: DB2ERM-7.5/7.62-XXP

第一视角/FIRST ANGLE PROJECTION



单位/UNITS: mm 尺寸/SIZE: A4 比例/SCALE:

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [DIBO](#) manufacturer:

Other Similar products are found below :

[57.510.0053](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [860505](#) [860516](#) [860810](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP03-3,50](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [1377680000](#) [1531000000](#) [1546228-5](#) [ELFP03110](#) [ELFT07250](#) [ELVD12100](#) [ELVF09400](#) [ELVP03100](#) [ELXH071G0E](#) [1700410](#) [1702246](#) [1705229](#) [1714537](#) [1717806](#) [1719600](#) [1728941](#) [1734692](#) [1734795](#) [1740291](#) [1740628](#) [1746952](#) [1750207](#) [1752865](#) [1754115](#) [1754144](#) [1756913](#) [1760051](#) [1760336](#) [1765111](#) [1776388](#) [1777701](#) [1783410](#) [1800227](#) [1801080](#) [1809474](#)