

电气性能/Electrical

参考标准/Standard: UL IEC
 额定电压/Rated voltage: 300V 320V
 额定电流/Rated current: 15A 20A
 接触电阻/Contact resistance: 20mΩ

耐电压/Withstanding voltage: AC2000V/1Min

绝缘电阻/Insulation resistance: 500MΩ/DC500V

机械性能/Mechanical

温度范围/Temp Range: -40° C~+105° C

瞬间温度/MAX Soldering: +250° C, for 5 Sec

尺寸/Dimensions

间距/Pitch: 7.5mm, 7.62mm

极数/Poles: 2P-24P

材质及电镀/Material

塑件/Housing: PA66, UL94V-0


焊针/Pin header: Brass, Tin plated

螺母/Nut: M2.5 Brass

TOLERANCES EXCEPT AS NOTED

	linear dimension	fillet	chamfer	短角 short angle side	≡	—	□	//	⊥
variable range	over 6 to 30	over 120 to 480	all to 6	over 6 to 10	over 10 to 50	over 50 to 120	all to 5	over 5 to 30	over 30 to 120
tolerance	±0.1	±0.2	±0.2	±0.5	±1	1°	30'	10'	0.5
	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'
	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'
	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'
	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'	0.5
	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'
	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'
	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'
	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'	0.5
	±0.2	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'
	±0.3	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'
	±0.5	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'
	±0.9	±0.2	±0.5	±1	1°	30'	20'	10'	0.5

订购方式 : HOW TO ORDER



Cixi Dibo Electronics Co., LTD

名称/NAME DB2ERM-7.5/7.62-XXP

第一视角/FIRST ANGLE PROJECTION



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pluggable Terminal Blocks](#) category:

Click to view products by [DIBO](#) manufacturer:

Other Similar products are found below :

[57.404.7553](#) [57.504.0053.7](#) [57.510.0053](#) [57.910.6153](#) [01.112.1453](#) [CTB932VE/6](#) [MC 1.5/ 6-ST-3.5 GY AU](#) [ET02015000J0G](#) [734-104](#) [734-302](#) [734-304](#) [8-141-P](#) [FKCT 2.5/ 3-ST KMGY](#) [860505](#) [860508](#) [860516](#) [860810](#) [861908](#) [GBPACX-12](#) [93.731.4953.0](#) [PV05-5,08-K](#) [PVP02-5,00](#) [PVP04-3,50](#) [PVS02-5,00](#) [1-1986160-3](#) [H-10](#) [ELFH09150](#) [ELFH16150](#) [ELFP03110](#) [ELFT06250](#) [ELFT07250](#) [ELVF09400](#) [ELVP03100](#) [ELXH03100](#) [ELXH071G0E](#) [ELXP041G0](#) [ELXT046G0](#) [1700101](#) [1700410](#) [1700425](#) [1703176](#) [1703243](#) [1705229](#) [1710175](#) [1714537](#) [1717806](#) [1719600](#) [1729386](#) [1734692](#) [1734795](#)