



SIGN	DATE 10	DESCRIPTION
△	06 07	
△		
△		

Material

Housing: PA66 UL94V-0

Solder Pin: Brass With Tin plated

Screw: M3, steek, Zinc plated

Electrical

Rated Voltage:300V

Rated Current:30A

Contact Resistance:20mΩ,

Insulation Resistance:5000MΩ/1000V

Withstanding Voltage: 2000V/1Min

Wire range: 26-10AWG

Mechanical

Temp. Range: -40° C/+105° C

Tourqe: 0.5Nm

Strip length: 6-7mm

MAX soldering: +250° C5Sec

RoHS Version



Cixi Dibo Electronics Co.,LTD

PART NAME: TINAL BLOCK				TITLE:	
PART NO: DB910-7.62				DWG NAME: A1.DWG	
APPROVED BY	CHECKED BY	DESIGNED BY	DRAWN BY	CUSTOM NO:	Tolerance L ±0.10 L.S ±0.20 L.XX ±0.10 X° ±5°
陆少波				 FORM: 2/1 DWG/APP: A1	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Terminal Blocks](#) category:

Click to view products by [DIBO](#) manufacturer:

Other Similar products are found below :

[00175550202](#) [MBE-1512](#) [MBE-1520](#) [MBE-154](#) [MBE-156](#) [MBES-1510](#) [MBES-153](#) [MBES-156](#) [MH-2512](#) [MHE-132](#) [MHE-133](#) [MHE-163](#)
[MI-254 \(35\)](#) [MI-272](#) [8739](#) [880507](#) [880508](#) [MPT-275](#) [1546551-6](#) [ELM023100](#) [ELM10110G](#) [ELVD12100](#) [BA311TU](#) [BA411SU](#) [MV-152](#)
[MV-253/NCNOC](#) [MV-254-D](#) [MV-255](#) [MV-462](#) [MV-472](#) [MV-493](#) [MVE-252](#) [MVE-253](#) [MVE-258](#) [MVE-273](#) [MVEB-153](#) [1700096](#)
[1702246](#) [1705142](#) [1712417](#) [1713020](#) [1713088](#) [1776118-2](#) [1790852](#) [1-796689-8](#) [1-796692-6](#) [1800001](#) [1800114](#) [1823215](#) [1838462](#)