


订购方式：
HOW TO ORDER:



电气性能/Electrical
 参考标准/Standard: UL IEC
 额定电压/Rated voltage: 300V 250V
 额定电流/Rated current: 30A 35A
 接触电阻/Contact resistance: 20m Ω
 使用线径/Wire range: 26-10AWG 6.0mm²
 耐电压/Withstanding voltage: AC2000V/1Min
 绝缘电阻/Insulation resistance: 500M Ω /DC500V
 机械性能/Mechanical
 温度范围/Temp Range: -40 $^{\circ}$ C~+105 $^{\circ}$ C
 扭矩/Torque: 0.5Nm(4.5lb \cdot in)
 剥线长度/Strip length: 6-7mm
 尺寸/Dimensions
 间距/Pitch: 9.5mm
 极数/Poles: 2P-24P
 材质及电镀/Material
 塑件/Housing: PA66, UL94V-0
 螺丝/Screws: M3.0, steel Zinc plated
 方块/Cage: Brass, Ni plated
 焊脚/Pin header: Brass, SnIe plated

0 未定义/No definition	1 单间距/Sing pitch	2 双间距/Double pitch
灰色/Grey	蓝色/Blue	黑色/Black
10	20	30
绿色/Green	棕色/Orange	红色/Red
40	50	60
透明/Transparent	黄色/Yellow	白色/White
70	80	90

单位/UNITS	mm
尺寸/SIZE	A4
比例/SCALE	比例
名称/NAME	DB910-9.52-XXP

linear dimension(Tolerances Standard GB/T 14486-2008)	≡	—	□	//	L											
tolerance	±0.1	±0.14	±0.19	±0.25	±0.32	±0.43	±0.57	±0.72	±0.88	±1.05	±1.25	0.5	0.025	0.06	0.12	0.4
variable range	6 to 10	6 to 10	6 to 18	30 to 18	50 to 30	80 to 50	120 to 80	160 to 120	200 to 160	250 to 200	all to 250	5 to 5	5 to 30	5 to 120	30 to 120	120 to 120



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Terminal Blocks](#) category:

Click to view products by [DIBO](#) manufacturer:

Other Similar products are found below :

[00175550202](#) [MBE-1512](#) [MBE-1520](#) [MBE-154](#) [MBE-156](#) [MBES-1510](#) [MBES-153](#) [MBES-156](#) [MH-2512](#) [MHE-132](#) [MHE-133](#) [MHE-163](#)
[MI-254 \(35\)](#) [MI-272](#) [8739](#) [880507](#) [880508](#) [MPT-275](#) [1546551-6](#) [ELM023100](#) [ELM10110G](#) [ELVD12100](#) [BA311TU](#) [BA411SU](#) [MV-152](#)
[MV-253/NCNOC](#) [MV-254-D](#) [MV-255](#) [MV-462](#) [MV-472](#) [MV-493](#) [MVE-252](#) [MVE-253](#) [MVE-258](#) [MVE-273](#) [MVEB-153](#) [1700096](#)
[1702246](#) [1705142](#) [1712417](#) [1713020](#) [1713088](#) [1776118-2](#) [1790852](#) [1-796689-8](#) [1-796692-6](#) [1800001](#) [1800114](#) [1823215](#) [1838462](#)