

4G LTE CAT 1 CELLULAR **SMART MODEM**



DIGI XBEE³ **CELLULAR LTE CAT 1**

Digi XBee3[™] smart modems offer the easiest way to integrate cellular connectivity into an OEM device or IoT gateway.

Digi XBee3™ modules accelerate time to market for designers, OEMs and solution providers by quickly enabling wireless connectivity and easy-to-add functionality. Building on industry-leading technology, pre-certified Digi XBee3 modules offer the flexibility to switch between multiple frequencies and wireless protocols as needed.

Ideal for moderate bandwidth (typically <25 MB per month) and low-cost IoT applications, Digi XBee3 Cellular LTE CAT 1 modules are cost-competitive with legacy 2G/3G standard devices.

With Digi Remote Manager®, XBee3 modules can be easily configured and controlled from a simple, central platform. Built-in Digi TrustFence® security, identity and data privacy features use more than 175 controls to protect against new and evolving cyber threats. Standard XBee API frames and AT commands, MicroPython and XCTU software tools simplify adding functionality, set-up, configuration and testing. Digi XBee3 modules are the latest addition to the expanding Digi XBee Ecosystem of wireless modules, adapters and software all engineered to accelerate development and deployment.

BENEFITS

- Integrated MicroPython programmability enables custom scripting directly on the modem
- XBee Transparent and API modes simplify s/w design
- 90 days of free cellular service with development kits
- FCC certified and carrier end-device certified for Verizon and AT&T
- Smallest end-device certified cellular modem
- Direct USB provides easy PPP integration option
- OTA firmware updates
- Enhanced with Digi TrustFence® security framework
- Manage and configure with XCTU and Digi Remote Manager®

RELATED PRODUCTS





хсти






APPLICATION EXAMPLE





CELL TOWER



SPECIFICATIONS	Digi XBee3® Cellular Smart Modem, LTE CAT 1	
HARDWARE		
CELLULAR CHIPSET	Telit LE866A1-NA	
FORM FACTOR	Digi XBee 20-pin through-hole	
ANTENNA OPTIONS	1 U.FL: Cellular Primary,1 U.FL: Cellular Diversity Embedded Bluetooth Antenna	
DIMENSIONS	24.38 mm x 32.94 mm	
OPERATING TEMPERATURE	-40° C to +80° C	
SIM SIZE	4FF Nano	
INTERFACE AND I/O		
DATA INTERFACE	UART, SPI, USB	
OPERATING MODES	Transparent and API over serial, PPP over USB or Serial	
SECURITY	Digi Trustfence® security with Secure Boot and Protected JTAG	
CONFIGURATION TOOLS	Digi XCTU (Local), Digi Remote Manager (OTA)	
EMBEDDED PROGRAMMABILITY	MicroPython with 32 KB Flash / 32 KB RAM	
I/O	4 ADC lines (10-bit), 13 Digital I/O, I2C	
BLUETOOTH	Bluetooth LE Ready	
CELLULAR CHARACTERISTICS		
TRANSMIT POWER	Up to 23 dBm	
RECEIVE SENSITIVITY	-102dBm	
CARRIER APPROVALS	AT&T End Device Certified Verizon End Device Certification (Pending) Compatible with other LTE-CAT1 carriers, see band support	
SUPPORTED BANDS	Bands 2,4,12 Verizon Band 4, 13 (Coming Soon)	
DOWNLINK/UPLINK SPEEDS	10 Mbit/s Downlink, 5 Mbit/s Uplink (USB) 921 Kbit/s Downlink and Uplink (UART)	
DUPLEX MODE	Full-Duplex	
POWER REQUIREMENTS (AT 3.3VDC INPUT POWER)		
SUPPLY VOLTAGE	3.0 to 5.5V	
PEAK TRANSMIT CURRENT	1000mA Bluetooth Disabled 1060mA Bluetooth Enabled	
AVG TRANSMIT CURRENT	850mA	
AVG RECEIVE CURRENT	TBD	
POWER SAVE MODE	TBD	
REGULATORY AND CARRIER APPROVALS		
FCC (USA)	MCQ-XB3C1	
IC (CANADA)	1846A-XB3C1	
VERIZON END-DEVICE CERTIFIED	Pending	
AT&T END-DEVICE CERTIFIED	Complete	
PTCRB	Complete	

PART NUMBERS	DESCRIPTION
XK3-C-A1-UT-001	Digi XBee3 Cellular Smart Modem,LTE CAT 1, North America
XK3-C-A1-UT-U	Digi XBee3 Cellular Smart Modem,LTE CAT 1, Development Kit, AT&T

DIGI SERVICE AND SUPPORT / You can purchase with confidence knowing that Digi is always available to serve you with expert technical support and our industry leading warranty. For detailed information visit www.digi.com/support.

@ 1996-2018 Digi International Inc. All rights reserved. All trademarks are the property of their respective owners.

DIGI INTERNATIONAL WORLDWIDE HQ 877-912-3444 / 952-912-3444 / www.digi.com

DIGI INTERNATIONAL GERMANY +49-89-540-428-0

+49-89-540-428-0

DIGI INTERNATIONAL JAPAN +81-3-5428-0261 / www.digi-intl.co.jp **DIGI INTERNATIONAL SINGAPORE** +65-6213-5380

DIGI INTERNATIONAL CHINA +86-21-50492199 / www.digi.com.cn



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Multiprotocol Development Tools category:

Click to view products by Digi International manufacturer:

Other Similar products are found below:

CYW94343WWCD1_EVB MIKROE-2439 XKC-M5T-W ATWINC3400-XPRO 2636 Gpy STEVAL-FKI001V1 8265.NGWMG.DTX1

TEL0111 SiPy 22 dBm ATWINC3400-XSTK RE-WFKIT-9260NVP 2542 irpi01-868 irpi01-915 BCM94343WWCD1_EVB INP3010

INP3011 ISM43340-L77-EVB ISMART43362-E MIKROE-3542 nRF9160-DK QPQ1906EVB-01 102010129 102991023 102991025

107990093 113990254 SIMSA868C-Cloud-DKL SIMSA868-Cloud-DKL SIMSA915-Cloud-DKL SIMSA-DKL SKY66423-11EK2

SKY66423-11EK1 TEL0097 DFR0505 XKC-V1T-U FiPy 453-00010-K1 453-00011-K1 DVK-RM186-SM-01 XPC270300EK MTDOT-BOX-G-868-B MTDOT-BOX-G-915-B LBEH5DU1BW-TEMP-DS-SD 113030023 SKY66420-11EK1 SKY66420-11EK2 SKY66420
11EK3