


Twisted Pair Patch Cable, Raw - Category 5e Class D - SF/UTP



Abstract

CAT 5e Class D, SF/UTP, Twisted Pair Patch Cable, Raw, PVC, 100 MHz

Application areas

Primary (Campus), Secondary (Riser), Tertiary (Horizontally)

IEEE 802.3: 10Base-T; 100Base-T; 1000Base-T

IEEE 802.5: 16 MB; ISDN; FDDI; ATM; PoE

Norms

ANSI/TIA 568-C; ISO/IEC 11801 2nd Ed.; EN 50173; EN 50288-3-1

Physical Properties

Conductor	Bare annealed copper, stranded AWG 26/7
Insulation	HD-PE (High Density Polyethylene)
Total number of insulated conductors	8, twisted in 4 pairs
Color code	Blue-white, orange-white, green-white, brown-white
Individual pair shielding	None
Overall shielding	Foil- and braid shielding
Outer sheath	PVC
Outer sheath diameter	0.55 mm nominal
Outer sheath color	Grey (RAL 7035)

Mechanical Properties

Tensile loading	150 N max.
Dynamic bending radius	8x AD mm min.
Static bending radius	4x AD mm min.
Shipping- and storage temperature range	-10 °C up to +75 °C
Operating temperature range	-10 °C up to +60 °C
Installations temperature range	0 °C up to +50 °C
Overall diameter	5.6 mm nominal

Electrical Properties

DC loop resistance	≤ 280 Ω km
Resistance unbalance	≤ 2%
Insulation resistance	≥ 2000MΩ/km @500V
Capacitance	nom. 48 nF/km @ 800 Hz
Capacitance unbalance (pair-ground)	≤ 1500 nF/km
Characeristic Impedance	100 ± 15 Ohm @ 10-100 MHz
NVP	67%
Propagation delay	nom. ≤ 555 ns/100 m
Delay skew	nom. ≤ 50 ns/ 100 m
Test voltage (DC 1 min) core/core	1000V
Coupling attenuation	≥ 4 dB

Transmission Properties

FREQ.	ATT	NEXT	PS NEXT	RL	ACR	PS ACR
MHz	dB	dB	dB	dB	dB	dB
1	2.2	60.0	57.0	17.0	57.4	54.4
10	7.1	47.0	44.0	17.0	37.4	34.4
100	24.0	30.1	27.1	10.0	23.3	14.4

Product Number Information

Item code	Length	Packaging
DK-1531-P-1-1	100 m	Carton
DK-1531-P-305-1	305 m	Carton

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ethernet Cables / Networking Cables](#) category:

Click to view products by [Digitus](#) manufacturer:

Other Similar products are found below :

[73-6670-7](#) [73-6680-15](#) [73-7797-25](#) [MCJB2-10P6Q7-120](#) [84909-0204](#) [1200700174](#) [1200860368](#) [1410147](#) [E16A06002M030](#) [E200102-009-S1](#) [AX105346-EW](#) [MT14-187L](#) [17-103530](#) [ERWPAB3002M005](#) [190-038045-01](#) [NK5EPC18RDY](#) [NK5EPC18VLY](#) [NK5EPC18YLY](#) [NK5EPC1GRY](#) [NK5EPC4Y](#) [NK5EPC6YLY](#) [NK5EPC8BLY](#) [NK5EPC9YLY](#) [1969343-6](#) [C501100010](#) [C501106002](#) [C501106007](#) [C501106015](#) [C501106025](#) [C601102010](#) [C601104010](#) [C601106007](#) [C601106015](#) [2142758-2](#) [2168427-2](#) [CAT1106007](#) [21949-1](#) [2J1866A](#) [RJF SFTP 5E 0500](#) [AX100351](#) [MN14CEC/ST](#) [C501100015](#) [C501106004](#) [C501106010](#) [C5F1108007](#) [C601104004](#) [C601106004](#) [CA21106004](#) [CA21106010](#) [CA21109007](#)