

# PI3EQX2034

## USB 3.2 Gen 2x2 ReDriver with Integrated USB-C Detector

### Description

The DIODES PI3EQX2034 is a low power, high performance USB 3.2 Gen 2x2 ReDriver™ with Plug-in Detector for Type-C® connector.

The Device includes two main function blocks:

- 1) The USB3.2 Gen2x2 ReDriver
- 2) The Plug-in Detector for USB-C connector

#### The USB3.2 Gen2x2 ReDriver

The ReDriver provides programmable equalization, swing and flat gain to optimize performance over a variety of physical mediums by reducing Inter-Symbol Interference. The ReDriver supports four 100Ω Differential CML data I/O's between the Protocol ASIC to a switch fabric, over cable, or to extend the signals across other distant data pathways on the user's platform.

The integrated equalization circuitry provides flexibility with signal integrity of the signal before the ReDriver. A low-level input signal detection and output squelch function is provided for each channel. Each channel operates fully independently. The channels' input signal level determines whether the output is active.

The ReDriver also includes an adaptive power management feature to maximize battery life for power sensitive consumer devices.

#### The Plug-in Detector for USB-C Connector

The plug-in detector detects the plug-in orientation of the cable at a USB-C connector. It supports the port to configure as SOURCE (DFP) mode and DRP modes and automatically connects based on the voltage levels detected on CC pin. It is a fully-integrated solution with ultra-low power dissipation.

The plug-in detector supports both pin and I2C interfaces.

The PORT input pins determine the port setting in which the SOURCE or DRP port can be selected. In SOURCE and DRP modes, the SRC\_CUR input pin selects USB Type-C current advertisement at default USB, 1.5A, and 3A level. The system running in source mode can monitor ID pin to know the connector attached or not. Systems running in sink mode can monitor system's VBUS for connector status. DEBUG pin also indicate if a debug accessory is attached.

The plug-in detector provides VCONN function to power active cables and other accessories through VCONN pin. Low-resistance power switches are integrated in the chip-to-connect CC1/CC2 pins to VCONN pin.

I2C interface informs the processor the information of connection and plug orientation. An interrupt signal for indicating changes.

#### Notes:

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

### Features

#### ReDriver

- 10Gbps Serial Link with Linear Equalizer
- USB3.2 Gen 2x2
- Four 10Gbps Differential Signal Pairs
- Pin Mode Control for EQ/Flat Gain/Swing
- 100Ω Differential CML I/O's
- Automatic Receiver Detect
- Single Supply Voltage: 3.3V

#### Plug-In Detector

- USB Type-C Specification 2.0
- Supports SOURCE (DFP)/DRP Modes
- Auto-Configure Ports Orientation through CC Detection
- Supports VCONN to Power Active Cables and Other Accessories
- Supports Detecting Debug Accessory Mode (DAM) as Source (Rd /Rd Detection) if Configuring the Port as DFP
- Supports Detecting DAM as both Source & Sink (Rp/Rp detection) if Configuring the Port as DRP
- DEBUG Pin to Enable SBU Isolation for Compliance Requirement
- Supports Over-Current Protection and Over-Voltage Protection for VCONN
- Allow Both Pin Control and I2C Interface
- Integrated Power Switches, High-Precision Resistors and Current Sources for CC Pins
- Provides Support for Default USB Power, 1.5A and 3A SOURCE Modes with Pin Control
- Output Indicator for Plug-In Detection
- Power Saving Mode
- 24V Tolerance on CC1, CC2 and VBUSDET
- Power Supply Range : 3.0V to 5.0V
- Temperature Range: 0°C to 70°C
- Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)
- Halogen and Antimony Free. "Green" Device (Note 3)
- For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please [contact us](https://www.diodes.com/quality/product-definitions/) or your local Diodes representative.
- Packaging (Pb-free & Green):
  - 52-pin, 3.5mm x 9mm (ZL)

### Ordering Information

Part Number	Package	Description
PI3EQX2034ZLEX	ZL	52-Pin, 3.5mm x 9.0mm (TQFN)

#### Notes:

- E = Pb-free and Green
- X suffix = Tape/Reel

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for* [Interface - Signal Buffers, Repeaters](#) *category:*

*Click to view products by* [Diodes Incorporated](#) *manufacturer:*

Other Similar products are found below :

[PI3HDMI101ZHEX](#) [PI3EQX6741STZDEX](#) [PI6ULS5V9509UEX](#) [PI3HDMI101-BZHEX](#) [PI3EQX12904AZHEX](#) [PI3EQX6801AZDEX](#)  
[PI6ULS5V9515AUEx](#) [PI3DPX1203CZHEX](#) [PI3EQX1002E2ZREX](#) [DS100BR410SQX/NOPB](#) [PI2EQX632EXUBEX](#) [PI3HDX12211ZHEX](#)  
[PI3DPX8121AZLEX](#) [PI6ULS5V9617CUEx](#) [PCA9509PGM,125](#) [DS280BR820ZBLT](#) [PCA9617ADPJ](#) [PCA9617ATPZ](#) [PI3EQX1002BZLEX](#)  
[DS125BR820NJYR](#) [DS80PCI402SQ/NOPB](#) [89HP0604SZBNRG](#) [DS110DF1610FB/NOPB](#) [SN75LVCP601RTJR](#) [SN65DPHY440SSRHRR](#)  
[PI3EQX12902AZLEX](#) [PI3DPX1203BZLEX](#) [SN75DPHY440SSRHRR](#) [DS280DF810ABVT](#) [SN65DP159RSBR](#) [LTC4315IMS#TRPBF](#)  
[LTC4303IMS8#PBF](#) [LTC4300A-1IMS8#PBF](#) [LTC4300A-1CMS8#PBF](#) [PI3EQX1004EZTFEX](#) [PI2EQX4401DZFEX](#)  
[PI2MEQX2503XEAEX](#) [PI3DPX1203BZHIEX](#) [PI3DPX1205A1ZLBE](#) [PI3DPX1207Q3ZHEX](#) [PI3DPX1225Q3ZLBEX](#) [PI3EQX1001XUAEX](#)  
[PI3EQX1002B1ZLEX](#) [PI3EQX1004B1ZHEX](#) [PI3EQX1014ZTFEX](#) [PI3EQX10312ZHEX](#) [PI3EQX12902BZLEX](#) [PI3EQX12904EZHEX](#)  
[PI3EQX12908A2ZFEX](#) [PI3EQX16612ZLDEX](#)