
DIP SWITCH SERIES





FEATURES

※Low profile 1.6mm height *Top tape type for washing process

APPLICATION

※Industrial control


*Automatic machines control

HOW TO ORDER DHN - -Package: Pin Length: ==6.70mm F=8.10mm T/R=Tape & Reel V=RoHS & Lead Free Solderable Q=Halogen Free □=Regular T=Top Tape Sealed ="ON" Position F="OFF" Position

SPECIFICATION

Contact Rating	25mA, 24V DC
Contact Resistance	100m $Ω$ max.
Insulation Resistance	100M Ω min. 500V DC
Dielectric Strength	300V AC/1 minute
Operating Force	500gf max.
Travel	0.6mm
Operating Life	1,000 cycles
Operating Temp.	-40°C ~ +85°C
Storage Temp.	-40°C ~ +85°C

CIRCUIT





PACKAGE


<Tube>


DHN(F)-02: 125 pcs DHN(F)-04: 75 pcs DHN(F)-06: 54 pcs DHN(F)-08: 40 pcs DHN(F)-10: 33 pcs Tape & Reel>
DHN: 4000 pcs
DHNF: 2500 pcs

DHN











PART NO.	NO.OF POS	DIM A
DHN-02	2	3.77
DHN-04	4	6.31
DHN-06	6	8.85
DHN-08	8	11.39
DHN-10	10	13.93







DHNF





P.C.B. LAYOUT





PART NO.	NO.OF POS	DIM A
DHNF-02	2	3.77
DHNF-04	4	6.31
DHNF-06	6	8.85
DHNF-08	8	11.39
DHNF-10	10	13.93

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for DIP Switches/SIP Switches category:

Click to view products by Diptronics manufacturer:

Other Similar products are found below:

78M03S 79B10T 8136-475G4T G7G-1A2-CB-DC12 H7CZL8AC100240 A7SS-M A8CA-201 DRR60016 DRS4016 1825008-1 1825444-1 25.350.0653.0 SDA10H1BDA 97R06ST A2C-2A5 1825444-7 ADE08SA04 ADE12S04 192960010 2-1825058-8 25.330.0653.1 25.352.0353.0 CXDRIVEV2X IKN0600000 IKN0800000 LA2-002-DC24 DBS1003 438872000 DRD10CRAE04 DSR02T DSS 208 N E2FMX2D1M1TGJ03M NDI10H 219-9MSTP 204-6ES EPM02FV 701521596 NDS08V 76SB05 79A10 TD06H0SK1 Z7.255.9027.0 1-1825058-3 1825428-4 219-10LPSTF E3ZG6111D03M G4D212PUSTV2DC5 195-7MSTN NDI05H EPG301BT06