

Display Elektronik GmbH

DATA SHEET

**E-Paper Display**

**DEE 400300A2 – W**

4,2“

**E-PAPER DISPLAY**

Product Specification

Ver.: 0

16.03.2017

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	1 of 14

## **Specification For OED 4.2" E-Paper**

**Model NO.: DEE 400300A2-W**

<b>Prepared by</b>	<b>Checked by</b>	<b>Approved by</b>

### **Customer approval**

<b>Customer</b>	<b>Approved by</b>	<b>Date of approval</b>

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	2 of 14

<b>Version</b>	<b>Content</b>	<b>Date</b>	<b>Producer</b>
0	New Release	16.03.2017	MH

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	3 of 14

## CONTENTS

1	General Description.....	5
2	Features.....	5
3	Application .....	5
4	Mechanical Specification .....	5
	4.1 Dimension .....	5
	4.2 Mechanical Drawing of E-Paper Module .....	6
5	Input/Output Pin Assignment.....	7
6	Electrical Characteristics.....	8
	6.1 Absolute Maximum Rating .....	8
	6.2 Panel DC Characteristics.....	8
	6.3 Panel DC Characteristics(Driver IC Internal Regulators) .....	9
	6.4 MCU Interface.....	10
	6.4.1 MCU Interface Selection.....	10
	6.4.2 MCU Serial Interface (4-wire SPI) .....	10
	6.4.3 MCU Serial Interface (3-wire SPI) .....	11
7	Optical Specification .....	12
8	Handling, Safety, and Environment Requirements.....	12
9	Reliability Test .....	13
10	Block Diagram .....	14
11	Typical Application Circuit with SPI Interface .....	15

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	<b>4 of 14</b>

## 1 General Description

DEE 400300A2-W is an Active Matrix Electrophoretic Display(AM EPD), with interface and a reference system design. The 4.2" active area contains 400x300 pixels. The module is a TFT-array driving electrophoretic display, with integrated circuits including gate buffer, source buffer, MCU interface, timing control logic, oscillator, DC-DC, SRAM, LUT, VCOM. Module can be used in portable electronic devices, such as Electronic Shelf Label (ESL) System.

## 2 Features

- ◆ 400×300 Pixels Display
- ◆ White Reflectance above 30%
- ◆ Contrast Ratio above 8:1
- ◆ Ultra Wide Viewing Angle
- ◆ Ultra Low Power Consumption
- ◆ Pure Reflective Mode
- ◆ Bi-stable Display
- ◆ Commercial Temperature Range
- ◆ Landscape, Portrait Modes
- ◆ Hard-Coat Antiglare Display Surface
- ◆ Ultra Low Current Deep Sleep Mode
- ◆ On Chip Display RAM
- ◆ Waveform stored in On-Chip OTP
- ◆ Serial Peripheral Interface available
- ◆ On-Chip Oscillator
- ◆ On-Chip Booster and Regulator Control for generating VCOM, Gate and Source Driving Voltage
- ◆ I<sup>2</sup>C Signal Master Interface to read External Temperature Sensor

## 3 Application

Electronic Shelf Label System


## 4 Mechanical Specification

### 4.1 Dimension

<b>Parameter</b>	<b>Specifications</b>	<b>Unit</b>	<b>Remark</b>
Screen Size	4.2	Inch	
Display Resolution	400(H) × 300(V)	Pixel	120DPI
Active Area	84.80 × 63.60	mm	
Pixel Pitch	0.212 × 0.212	mm	
Pixel Configuration	Square		
Outline Dimension	91.00 × 77.00 × 1.15	mm	
Weight	16.4	g	

File Name	Specification for 4.2" E-Paper	Module Number	DEE400300A2-W
Version 0		Page Number	5 of 14

## 4.2 Mechanical Drawing of EPD Module



<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	6 of 14

## 5 Input/output Pin Assignment

No.	Name	I/O	Description	Remark
1	NC		Do not connect with other NC pins	
2	GDR	O	N-Channel MOSFET Gate Drive Control	
3	RESE	I	Current Sense Input for the Control Loop	
4	NC		Do not connect with other NC pins	
5	NC		Do not connect with other NC pins	
6	TSCL	O	I <sup>2</sup> C Interface to digital temperature sensor Clock pin	
7	TSDA	I/O	I <sup>2</sup> C Interface to digital temperature sensor Data pin	
8	BS1	I	Bus Interface selection pin	Note 5-4
9	BUSY	O	Busy state output pin	Note 5-3
10	RES#	I	Reset signal input. Active Low.	
11	D/C#	I	Data /Command control pin	Note 5-2
12	CS#	I	Chip select input pin	Note 5-1
13	D0	I	Serial Clock pin (SPI)	
14	D1	I	Serial Data pin (SPI)	
15	VDDIO	P	Power Supply for interface logic pins It should be connected with VCI	
16	VCI	P	Power Supply for the chip	
17	VSS	P	Ground	
18	VDD	C	Core logic power pin VDD can be regulated internally from VCI. A capacitor should be connected between VDD and VSS under all circumstances	
19	VPP	P	Power Supply for OTP Programming	
20	VSH	C	Positive Source driving voltage	
21	VGH	C	Positive Gate driving voltage	
22	VSL	C	Negative Source driving voltage	
23	VGL	C	Negative Gate driving voltage	
24	VCOM	C	VCOM driving voltage	

I = Input Pin, O =Output Pin, I/O = Bi-directional Pin (Input/Output), P = Power Pin, C = Capacitor Pin

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	7 of 14

Note 5-1: This pin is the chip select input connecting to the MCU. The chip is enabled for MCU communication only when CS# is pulled LOW.

Note 5-2: This pin is Data/Command control pin connecting to the MCU in 4-wire SPI mode. When the pin is pulled HIGH, the data at D1 will be interpreted as data. When the pin is pulled LOW, the data at D1 will be interpreted as command.

Note 5-3: This pin is Busy state output pin. When Busy is High, the operation of chip should not be interrupted, command should not be sent, e.g., The chip would put Busy pin High when

- Outputting display waveform
- Programming with OTP
- Communicating with digital temperature sensor

Note 5-4: Bus interface selection pin

<b>BS1 State</b>	<b>MCU Interface</b>
L	4-lines serial peripheral interface(SPI)
H	3- lines serial peripheral interface(SPI) - 9 bits SPI

## 6 Electrical Characteristics

### 6.1 Absolute Maximum Rating

<b>Parameter</b>	<b>Symbol</b>	<b>Rating</b>	<b>Unit</b>
Logic supply voltage	$V_{CI}$	-0.5 to +4.0	V
Logic Input voltage	$V_{IN}$	-0.5 to $V_{CI} + 0.5$	V
Logic Output voltage	$V_{OUT}$	-0.5 to $V_{CI} + 0.5$	V

Note: Maximum ratings are those values beyond which damages to the device may occur. Functional operation should be restricted to the limits in the Panel DC Characteristics tables.

### 6.2 Panel DC Characteristics

The following specifications apply for:  $V_{SS}=0V$ ,  $V_{CI}=3.0V$ ,  $T_{OPR}=25^{\circ}C$ .

<b>Parameter</b>	<b>Symbol</b>	<b>Condition</b>	<b>Applicable pin</b>	<b>Min.</b>	<b>Typ.</b>	<b>Max.</b>	<b>Unit</b>
Logic supply voltage	$V_{CI}$	-	$V_{CI}$	2.4	3.0	3.7	V
High level input voltage	$V_{IH}$	-	-	$0.8 V_{CI}$	-	-	V
Low level input voltage	$V_{IL}$	-	-	-	-	$0.2 V_{CI}$	V
High level output voltage	$V_{OH}$	$IOH = -100\mu A$	-	$0.9 V_{CI}$	-	-	V
Low level output voltage	$V_{OL}$	$IOL = 100\mu A$	-	-	-	$0.1 V_{CI}$	V
Typical power panel	$P_{TYP}$	-	-	-	45	240	mW
Deep sleep mode	$P_{STPY}$	-	-	-	0.006	-	mW
Typical operating current	$I_{opr\_VCI}$	$V_{CI}=3.0V$	-	-	15	80	mA

File Name	Specification for 4.2" E-Paper			Module Number	DEE400300A2-W		
Version 0				Page Number	8 of 14		
Sleep mode current	Islp_VCI	VCI=3.0V DC/DC OFF No clock No output load Ram data retain	VCI	-	35	50	uA
Deep sleep mode current	Idslp_VCI	VCI=3.0V DC/DC OFF No clock No output load Ram data not retain	VCI	-	2	5	uA
Operation temperature	T <sub>OPR</sub>	-	-	0	-	50	°C
Operating relative humidity	RHop	-	-	-	-	70	%RH
Storage temperature	TSTG	-	-	-20	-	70	°C
Storage relative humidity	RHst	-	-	30	-	60	%RH

- Notes: 1. The typical power is measured with following transition from horizontal 2 gray scale pattern to vertical 2 gray scale pattern. (Figure 6-1)
2. The deep sleep power is the consumed power when the panel controller is in deep sleep mode.
3. The listed electrical/optical characteristics are only guaranteed under the controller & waveform provided by OED.




Figure 6-2 The typical power consumption measure pattern

### 6.3 Panel DC Characteristics(Driver IC Internal Regulators)

The following specifications apply for: VSS=0V, VCI=3.0V, T<sub>OPR</sub> =25°C.

Parameter	Symbol	Condition	Applicable pin	Min.	Typ.	Max.	Unit
VCOM output voltage	VCOM	-	VCOM	-4.0	-	-0.2	V
Positive Source output voltage	V <sub>SH</sub>	-	S0-399	+14.5	+15	+15.5	V
Negative Source output voltage	V <sub>SL</sub>	-	S0-399	-15.5	-15	-14.5	V
Positive gate output voltage	V <sub>gh</sub>	-	G0-G299	+21	+22	+23	V
Negative gate output voltage	V <sub>gl</sub>	-	G0-G299	-21	-20	-19	V

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	9 of 14

## 6.4 MCU Interface

### 6.4.1 MCU Interface Selection

MCU interface consist of 2 data/command pins and 3 control pins. The pin assignment at different interface mode is summarized in Table 6-4-1. Different MCU mode can be set by hardware selection on BS1 pins. The display panel only supports 4-wire SPI or 3-wire SPI interface mode.

Pin Name	Data/Command Interface		Control Signal		
	D1	D0	CS#	D/C#	RES#
4-wire SPI	SDIN	SCLK	CS#	D/C#	RES#
3-wire SPI	SDIN	SCLK	CS#	L	RES#

**Table 6-4-1: MCU interface assignment under different bus interface mode**

### 6.4.2 MCU Serial Interface (4-wire SPI)

The serial interface consists of serial clock SCLK, serial data SDIN, D/C#, CS#. In 4-wire SPI mode, D0 acts as SCLK, D1 acts as SDIN.


Function	CS#	D/C#	SCLK
Write command	L	L	↑
Write data	L	H	↑

Note: ↑ stands for rising edge of signal

**Table 6-4-2: Control pins of 4-wire Serial interface**

SDIN is shifted into an 8-bit shift register on every rising edge of SCLK in the order of D7, D6, ... D0. D/C# is sampled on every eighth clock and the data byte in the shift register is written to the Graphic Display Data RAM (RAM) or command register in the same clock.

Under serial mode, only write operations are allowed.



**Figure 6-4-2: Write procedure in 4-wire SPI mode**

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	10 of 14

### 6.4.3 MCU Serial Interface (3-wire SPI)

The 3-wire serial interface consists of serial clock SCLK, serial data SDIN and CS#. In 3-wire SPI mode, D0 acts as SCLK, D1 acts as SDIN.


The operation is similar to 4-wire serial interface while D/C# pin is not used. There are altogether 9-bits will be shifted into the shift register on every ninth clock in sequence: D/C# bit, D7 to D0 bit. The D/C# bit (first bit of the sequential data) will determine the following data byte in the shift register is written to the Display Data RAM (D/C# bit = 1) or the command register (D/C# bit = 0).

Under serial mode, only write operations are allowed.

Function	CS#	D/C#	SCLK
Write command	L	Tie LOW	↑
Write data	L	Tie LOW	↑

Note: ↑ stands for rising edge of signal

**Table 6-4-3: Control pins of 3-wire Serial interface**



**Figure 6-4-3: Write procedure in 3-wire SPI mode**

<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	11 of 14

## 7 Optical Specification

Symbol	Parameter	Conditions	Values			Units	Notes
			Min.	Typ.	Max		
R	White Reflectivity	White	30	35	-	%	7-1
CR	Contrast Ratio		8:1	10:1	-	-	7-2
白 $\Delta$ L 24h	Reduce		-	$\leq 4$	-	-	-
T <sub>update</sub>	Image update time	at 25 °C	-	2100	-	ms	-

Notes: 7-1. Luminance meter: Eye-One Pro Spectrophotometer.

7-2. CR=Surface Reflectance with all white pixel/Surface Reflectance with all black pixels.

## 8 Handling, Safety, and Environment Requirements

<b>Warning</b>
The display glass may break when it is dropped or bumped on a hard surface. Handle with care. Should the display break, do not touch the electrophoretic material. In case of contact with electrophoretic material, wash with water and soap.

<b>Caution</b>
The display module should not be exposed to harmful gases, such as acid and alkali gases, which corrode electronic components. Disassembling the display module.
Disassembling the display module can cause permanent damage and invalidates the warranty agreements.

Observe general precautions that are common to handling delicate electronic components. The glass can break and front surfaces can easily be damaged. Moreover the display is sensitive to static electricality and other rough environmental conditions.


<b>File Name</b>	<b>Specification for 4.2" E-Paper</b>	<b>Module Number</b>	<b>DEE400300A2-W</b>
<b>Version 0</b>		<b>Page Number</b>	12 of 14

## 9 Reliability Test

No.	Test	Condition	Method	Remark
1	High-Temperature Operation	T = +50°C, RH = 30% for 168 hrs	IEC 60 068-2-2Bp	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
2	Low-Temperature Operation	T = 0°C for 168 hrs	IEC 60 068-2-2Ab	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
3	High-Temperature Storage	T = +70°C, RH=23% for 168 hrs	IEC 60 068-2-2Bp	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
4	Low-Temperature Storage	T = -25°C for 168 hrs	IEC 60 068-2-1Ab	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
5	High-Temperature, High-Humidity Operation	T = +40°C, RH = 90% for 168 hrs	IEC 60 068-2-3CA	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
6	High Temperature, High-Humidity Storage	T = +60°C, RH=80% for 168hrs	IEC 60 068-2-3CA	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
7	Thermal Shock	1 cycle:[-25°C 30min]→[+70°C 30 min] : 50 cycles	IEC 60 068-2-14	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
8	Package Vibration	1.04G, Frequency: 10~500Hz Direction: X,Y,Z Duration: 1 hours in each direction	Full packed for shipment	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
9	Package Drop Impact	Drop from height of 122 cm on concrete surface. Drop sequence: 1 corner, 3edges, 6 faces One drop for each	Full packed for shipment	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.
10	Electrostatic Effect (non-operating)	Machine model +/- 250V, 0Ω, 200pF	IEC 62179, IEC 62180	At the end of the test, electrical, mechanical, and optical specifications shall be satisfied.


File Name	Specification for 4.2" E-Paper	Module Number	DEE400300A2-W
Version 0		Page Number	13 of 14

## 10 Block Diagram



File Name	Specification for 4.2" E-Paper	Module Number	DEE400300A2-W
Version 0		Page Number	14 of 14

## 11 Typical Application Circuit with SPI Interface



Notes: 11-1. The electronic elements should be tested and verified for Max Power. We recommend the above electronic elements.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Embedded Processor Development Kits](#) category:*

*Click to view products by [Display Elektronik](#) manufacturer:*

Other Similar products are found below :

[ATLASEDGE.1](#) [QB-78K0RKG3-TB](#) [R0K578L1CD000BR](#) [100-437975](#) [EIC-Q410-210](#) [EZ-0012](#) [DEE 600800A-W](#) [P1010RDB-PB](#) [QB-V850ESJG2-TB](#) [R0K521237S001BE](#) [QB-78K0KC2L-TB](#) [QB-78K0SKB1-TB](#) [QB-R5F100SL-TB](#) [QB-V850ESJG3U-TB](#) [DEE 152152A-W](#)  
[12672](#) [12915](#) [12956](#) [RTK5RX2310P00000ZR](#) [955](#) [DEE 400300A2-W](#) [DEE 800480A-W](#) [TWR-KW24D512](#) [TWR-KV58F220M](#) [QB-78K0IB2-TB](#) [QB-78K0RIE3-TB](#)