

Mini Soft-Jaw Pliers

BT-SJ-509R BT-SJ-509A



The Mini Soft-Jaw Pliers are available in both straight (BT-SJ-509R) and 30° angled head (BT-SJ-509A) versions. These self-adjusting pliers allow for one-handed operation. The jaws adjust as quickly as your hand can squeeze the handles.



BT-SJ-509R
Straight Head



BT-SJ-509A
30° Angled Head

The narrow jaw design allows easy access to the tightest places. Non-marring jaws (BT-SJ-509A-1) are durable and easy to replace.

Jaw Replacement Instructions



Use a heat gun* to apply hot air to the back side of the jaw insert.



Pull the jaws out using sharp pliers or similar tool.



Apply a small amount of fuel resistant adhesive on the replacement jaw insert. Be sure to place the adhesive only on the portion that will be inserted into the pliers.



Push the replacement jaw insert into the opening in the pliers until it is fully seated in the tool.

*Wear safety glasses while operating heat gun. Heat guns produce flameless heat at very high temperatures. Therefore, it is necessary to keep hands, face, hair, as well as clothing and other heat sensitive material out of the air stream.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pliers & Tweezers](#) category:

Click to view products by [DMC](#) manufacturer:

Other Similar products are found below :

[0026](#) [T0058765801](#) [80](#) [76C](#) [378MN](#) [L4VN](#) [LN54VN](#) [NN7776VN](#) [54CGVN](#) [SN55VN](#) [DRP10N](#) [0036](#) [0020](#) [PN 5050/21D](#) [PNI 5015](#) [TR](#)
[20 VM](#) [PN 5025](#) [65516300](#) [1-84-199](#) [YT-2469](#) [181A.18CPE](#) [391A.16VE](#) [181EF.25CPEPB](#) [011640096](#) [CPE.A1PB](#) [SS406-160](#) [192A.18VE](#)
[011720102](#) [011850102](#) [011730101](#) [08 25 185](#) [STL 200](#) [T3773EF](#) [T2315](#) [PGT444](#) [PGT405](#) [160 300 5](#) [011620096](#) [T3773](#) [08 21 185](#) [T3907](#)
[8](#) [PGT423](#) [1302 015 2](#) [009990021](#) [RC 5](#) [34708](#) [011880102](#) [121 005 2](#) [6258](#) [1302 010 2](#)