# DMC1000-4R (NSN: 5180-01-586-3020) DANIELS MANUFACTURING Safe-T-Cable® Tool Kit

#### A Complete Tool And Parts Kit To Support Your .032" Applications.



Safe-T-Cable<sup>®</sup> Tool and Parts Kits are a travel-ready system whereby the user has Tools, Verification Equipment, Accessories, a supply of Cable/Ferrules, and the Instructions all in one package.

The packaging materials (polypropylene case, foam inserts, and laminated instructions) are manufactured to meet the most demanding handling conditions. FOD (Foreign Object Damage) is always a concern when workers are required to use tools and small components in or around an aircraft. The "shadowing" principal is a proven concept for Tool/parts control to minimize that concern.

DMC is well known throughout the aerospace industry for the quality and capability of the Tool Kits that we manufacture. If you have specific needs that cannot be covered by the Tool Kit described here, please call a DMC customer service representative for information on a Kit that will more appropriately meet your requirements.

DMC1000-4R .032" TOOL AND ACCESSORY LIST		
Part Number	Quantity	Description
SCTR323	1	ROTARY SAFE-T-CABLE TOOL WITH 3" NOSE ATTACHED (.032)
SCTN32-7	1	7" NOSE ASSEMBLY (.032)
C10-218	100	SAFE-T- CABLE .032 X 18"
SCT-TB1	1	TORQUE VERIFICATION BLOCK
45-6N	1	DIAGONAL CUTTER
689-412	1	FLAT BLADE SCREWDRIVER
4-1501	1	9/64" HEX WRENCH

Tool kit supplied in 1 polypropylene case and includes: Name Plate, Foam Pads/Inserts, Contents Charts and Instruction Sheets.

### DMC1000-4R

## NSN 5180-01-586-3020

DANIELS MANUFACTURING CORP., 526 THORPE ROAD, ORLANDO, FL 32824, USA PHONE (407) 855-6161 • FAX (407) 855-6884 • www.DMCTools.com • E-MAIL: DMC@DMCTools.com DMC1000-4R (NSN: 5180-01-586-3020) DANIELS MANUFACTURING Safe-T-Cable® Tool Kit



Safe-T-Cable was developed because the installation of hand twisted Lockwire is an expensive, time consuming, and awkward process. Safe-T-Cable is a simplified application method that relies on a precisely calibrated application tool for proper installation rather than operator skills. Operator training is simple, inspection is objective, and rework is virtually eliminated. This results in fewer demands on the Operators, Inspectors, and Maintenance Personnel. It will cut time and costs from your manufacturing or maintenance process.

Safe-T-Cable may be substituted for safety Lockwire to prevent loosening of threaded parts in accordance with the performance requirements of SAE specifications AS4536, AS3509, AS3510 and AS3511.

The Safe-T-Cable system involves three components: the calibrated tool, pre-assembled cables, and individual crimp ferrules. The cables have a square formed end cap securely attached to one end to provide a positive stop when threaded through a fastener. The other end is electrically fused so it will easily thread through the series of fasteners to be secured. The ferrules are preloaded into a disposable cartridge which allows convenient transportation, storage, and availability. The Safe-T-Cable tool tensions the cable, crimps the ferrule onto the cable, and cuts the cable flush with the ferrule. This system, when properly used, eliminates the possibility of Foreign Object Damage (FOD).

Safe-T-Cable is constructed of high tensile strength, stranded cable. It is more flexible than its Lockwire counterpart, although the working diameters are equivalent. This provides a stronger assembly



Step 1 - Thread

A cable assembly is threaded through the fasteners in a direction that exerts a positive pull on the fastener when tension is applied.



and lighter weight. Safe-T-Cable is available in four

For more detailed information, gualifications,

and specifications, contact DMC at (407) 855-6161 or

Eliminates injuries from sharp wire ends

nominal diameters: .022 inch diameter, .032 inch diameter, .040 inch diameter, and .062 inch diameter.

visit our web site at www.DMCTools.com.

Reduces installation time

Reduces operator error

Is stronger than wire

· Is quickly inspected

•

Improves FOD control

Reduces need to rework

Is quickly learned

· Allows access to tight areas

**Benefits of Safe-T-Cable** 

Simply thread the cable through the ferrule and the tool nose.

Step 2 - Insert



Correct tension is applied.





Step 4 - Crimp & Cut

The ferrule is firmly crimped and the cable is cut flush with the end of the ferrule.

#### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Tool Kits & Cases category:

Click to view products by DMC manufacturer:

Other Similar products are found below :

 217434-1
 4263
 1055420-1
 11-18-3023
 63860-8170
 856600-2
 690372163
 11-40-3247
 63883-2870
 63885-0270
 63866-1070
 63863-5070

 63892-7370
 11-18-3209
 63860-4070
 63881-0970
 A0403641
 11-18-3040
 63865-2070
 63910-1470
 63861-5070
 63850-7470
 11-18-3201

 63910-7570
 FM 0501
 146
 63883-0670
 63830-0070
 63902-9170
 11-18-3147
 11-18-3079
 63883-2670
 63900-1770
 11-18-3190
 63851-1070

 63912-4770
 63911-5270
 63895-1070
 63850-6070
 1-69411-3
 63852-9270
 63802-6270
 63902-4870
 11-18-3202
 63852-9170

 63850-1070
 63830-0170
 63910-2870
 11-18-3010
 63820-7070
 1-69411-3
 63852-9270
 63802-6270
 63902-4870
 11-18-3202
 63852-9170