

D A T A S H E E T

**PVC Ribbon cable –
FBK-Toy 3x0,25 mm² (AWG24-23)
according to VDE 0812**

TYPE	FBK-Toy
CROSSECTION	3 x 0,25 mm ²
WIRE CONSTRUCTION	3 x 14x0,15 mm
MATERIAL	Soft-annealed electrolytic copper Cu-ETP1 according to DIN EN 13602, bare
DIAMETER OF CONDUCTOR	each ca. 0,7 mm
ELECTRICAL RESISTANCE	each max. 79,9 Ω/km at 20°C acc. VDE 0812
INSULATION DIAMETER	nom. 1,3 mm ±0,1 mm / thickness of wall nom. 0,3 mm
OUTER DIMENSION	1,3 ±0,1 mm x 4,0 ±0,3 mm
INSULATION OF CONDUCTOR	Soft-PVC; YI2 (<u>PHTHALAT-FREE</u>) acc. 2005/84/EG (max. 0,1% Phthalat) Shore A 90 ±3
TEMPERATURE RANGE	moved from -5 to +85 °C unmoved from -40 to +85 °C
SERVICE VOLTAGE	max. 350 V
TESTING VOLTAGE	max. 1200 V
CURRENT RATING	max. 3 A at 35 °C room temperature and max. permitted conductor temperature of 80 °C
INSULATION RESISTANCE	> 20 MΩ x km at 20°C acc. VDE 0812
FLAME RETARDANT	PVC self-extinguishing and flame retardant acc. to VDE 0482-332-2-2 DIN EN 60332-2-2
COPPER WEIGHT	9,6 kg / 1.000 m
WEIGHT	ca. 1,6 kg / 100m
CONFORMITY	RoHS and REACH

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Ribbon Cables / IDC Cables](#) category:

Click to view products by [Donau](#) manufacturer:

Other Similar products are found below :

[AWG28-10G](#) [EHJ4C](#) [cab-LVDV-PWR-10-15](#) [Ribbon Cable, 4 Pin, 350mm](#) [Ribbon Cable, 4 Pin, 700mm](#) [cab-LVDV-DAT-34-15](#) [49635-C62-S2](#) [1-3636-600-5204](#) [ACL-eSSI-2](#) [IDD-04-G](#) [IDD-25-G](#) [3801/09 \(100FT\)](#) [0044716](#) [0044658](#) [0032805](#) [0012842](#) [0012801](#) [0012814](#) [21201](#) [22253](#) [22261](#) [22265](#) [22018](#) [22005](#) [22250](#) [22258](#) [XF-39603003P](#) [XF-20102003P3](#) [XF-10101502P2](#) [XF-12501502P2](#) [XF-25013004P](#) [XF-25013002P](#) [XF-10101504P](#) [XF-12501504P](#) [XF-39603004P4](#) [XF-20102002P2](#) [CL2542320190BC10E](#) [XF-2501L3003P3](#) [XF-39603003P3](#) [XF-12501503P](#) [XF-20162002P](#) [XF-12571503P](#) [XF-12571504P](#) [XF-12571503P3](#) [XF-20162003P3](#) [XF-12571502P2](#) [XF-12571502P](#) [XF-25013003P](#) [XF-25013003P3](#) [XF-20102004P4](#)