


CUT-OUT

	X	Y
0.75~1.25	13.6-0.1	8.7±0.1
1.25~2.00	13.7-0.1	8.7±0.1
2.00~3.00	13.8-0.1	8.7±0.1



MATERIAL:

Cover: Nylon66, UL rated: 94V-2 min
 Base: Nylon66, UL rated: 94V-2 min
 Terminal: Brass, silver or tin plated
 Rating: 6A 125V AC (UL CUL)
 3A 250V AC (UL CUL VDE CE CQC)
 Function: ON-OFF

Contact Resistance: 50mΩ Max
 Insulation Resistance: 100MΩ Min
 Dielectric Strength: 2000VAC 1 minute
 Dielectrical life: 10,000 cycles
 Mechanical life :50,000 cycles
 Operating Temperature: -20℃~80℃
 Safety Approval:



公差 TOLERANCES	.X±0.3	.XX±0.15	角度 ANGLE ±1°	单位	DIMENSION UNIT	mm.
版本 VERSION	A0	比例尺 SCALE	1:1	日期 DATE	品名 TITLE	图号 DRAWING NO
核准 APPROVED BY		核对 CHECKED BY		绘图 DRAWN BY	MR5-111-C5N-WW	MR5-111-C5N-WW_0
变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.				
版本 VER	变更说明 CHANGE DESCRIPTION	日期 DATE	ECN NO.			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rocker Switches](#) category:

Click to view products by [D-SWITCH](#) manufacturer:

Other Similar products are found below :

[LTILA6E-1S-WH-RC-FN12VXCR1](#) [6-1571986-9](#) [8055K23Z7V](#) [8055K52Z7V](#) [8138K20E6M50](#) [PREDD5-07F-BB0GW](#) [999-16716-002](#)
[999-16716-003](#) [999-16716-004](#) [A101J1V3Q004](#) [A101J2ZQ004](#) [A101J51CB0004](#) [A103J1ZQ004](#) [A201J1AQ004](#) [A201J50ZQ004](#)
[A203J51ZQ0004](#) [A435S1YZQ](#) [H8653VBBG2577W](#) [HB130CHNWWNAAC](#) [R13112ABB-602W](#) [1251.0303](#) [1352.0107](#) [1363.0201](#)
[1500G51E](#) [1571099-3](#) [1571987-4](#) [1571987-5](#) [1571988-5](#) [B123J77V7B2](#) [B226J50W4Q22P](#) [B433J37ZQ22M](#) [160212E](#) [1634200-7](#)
[1801.1164](#) [1831.1102](#) [1839.1502](#) [PANEL-PLUG-VHP-BLACK](#) [PANEL-PLUG-VHP-WT](#) [K1ABBSCADN](#) [K2ABAAAAAA](#)
[KG312A2DXD246X](#) [250011E714](#) [2600R21E](#) [260413E](#) [2637LH/2A7/122048L0](#) [2639LH/2A7/127000L0](#) [LL3AZXX-100-XGT1](#) [LL3AZXX-](#)
[100-XHS1](#) [LL3AZXX-100-XSD1](#) [30-695B](#)