



PCB LAYOUT

Function:(ON)-OFF
 Rating: 0.5A 30VDC
 0.25A 50VDC
 Contact Resistance: 50mΩ MAX.
 Insulation Resistance: 100MΩ min.at
 500VDC
 Dielectric Strength: 1000 VAC rms.
 Electrical life: 50,000 cycles
 Mechina life: 100,000 cycles
 Operating Temperature: -20°C~65°C
 Relative Air Humidity:45%~85%
 Operating Pressure:400±100gf
 Operating Stroke:1.4±0.3mm

MATERIAL:

Button:ABS,UL rated:94V-2 min
 Base:PBT,UL rated:94V-2 min
 Terminal:Brass,silver or tin plated



				公差 TOLERANCES				.X± 0.5 .XX± 0.3		角度 ANGLE ±1°		单位 DIMENSION UNIT mm.	
				版本 VERSION		A0		比例尺 SCALE		1:1		日期 DATE	
				核准				核对				品名 TITLE	
版本 VER				变更说明 CHANGE DESCRIPTION				日期 DATE		ECN NO.		图号 DRAWING NO	
				APPROVED BY				CHECKED BY				DRAWN BY 孙成	
										2021.09.08		PB16-ABN-S3	
												1080001	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [D-SWITCH](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW1L-M1C10V-A](#) [LW2L-M1C20M-A](#) [M22-D-R-GB0/K11](#) [67081K512X](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#)
[FLT 2U EE 01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K2](#) [8442K3](#) [8450K1](#)
[860K11911T01A](#) [861901](#) [861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [8646ABUL](#) [9001KXRK](#)
[9533CD4+U574+U4922](#) [95-414.000](#) [99-453.837](#) [PV3H2B0NN-341](#) [A22NZBGANGA](#) [A22NZBMMNGA](#) [A22NZBNANGA](#)
[A22NZMPATRA](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-7340](#) [A3U-TMW-A2C-5M](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [ABN400-R](#)
[121382](#) [1213C3](#) [HE3B-M2](#) [121194](#) [1212MRA](#) [1232A6NF](#) [1241.1183.7047](#) [121489](#)