



Nut Torque:5 ~ 14Nm

Operating Pressure:500gf ±150gf

Operating Stroke:2.2mm±0.5mm

Protection Grade:IP67,IK08

Function:ON-OFF

Contact:Silver Alloy

Base:PA66

Shell:SUS

Button:SUS

Lamp Type:LED

Forward current : 20mA

Lamp Life:50000H

Rating(Resistive load): 5A 250V AC

Contact Resistance: 50mΩ MAX

Insulation Resistance: 100MΩ MIN

Dielectric Strength: 1500VAC 1 minute

Electrical life: 50,000 cycles

Mechanical life :200,000 cycles

Operating Temperature: -20°C~80°C

Relative Air Humidity:45%~85%

Safety Approval:

公差 TOLERANCES .X±0.3 .XX±0.15 角度 ANGLE ±1°

单位 DIMENSION UNIT mm.



**D-SWITCH**  
东莞市德松电子有限公司  
D-SWITCH ELECTRONICS CO.,LTD.

版本 VERSION A0 比例尺 SCALE 1:1 日期 DATE 2021.04.27

品名 TITLE 图号 DRAWING NO

变更说明 CHANGE DESCRIPTION 日期 DATE ECN NO. APPROVED BY 核对 CHECKED BY 绘图 DRAWN BY 孙成 PBM-22232-FT-R1-Q24-S7S-A3 PBM-22232-FT-R1-Q24-S7S-A3\_A0

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Rocker Switches](#) category:*

*Click to view products by [D-SWITCH](#) manufacturer:*

Other Similar products are found below :

[LTILA6E-1S-WH-RC-FN12VXCR1](#) [6-1571986-9](#) [8055K23Z7V](#) [8055K52Z7V](#) [8138K20E6M50](#) [PREDD5-07F-BB0GW](#) [999-16716-002](#)  
[999-16716-003](#) [A101J1V3Q004](#) [A101J2ZQ004](#) [A101J51CB0004](#) [A103J1ZQ004](#) [A201J1AQ004](#) [A201J50ZQ004](#) [A203J51ZQ0004](#)  
[A435S1YZQ](#) [H8653VBBG2577W](#) [HB130CHNWWNAAC](#) [R13112ABB-602W](#) [1251.0303](#) [1352.0107](#) [1363.0201](#) [1500G51E](#) [1571099-3](#)  
[1571987-4](#) [1571987-5](#) [1571988-5](#) [B123J77V7B2](#) [B226J50W4Q22P](#) [B433J37ZQ22M](#) [160212E](#) [1634200-7](#) [1801.1164](#) [1831.1102](#) [1839.1502](#)  
[PANEL-PLUG-VHP-BLACK](#) [PANEL-PLUG-VHP-WT](#) [K1ABBSCADN](#) [K2ABAAAAAA](#) [KG312A2DXD246X](#) [250011E714](#) [2600R21E](#)  
[260413E](#) [2637LH/2A7/122048L0](#) [2639LH/2A7/127000L0](#) [LL3AZXX-100-XGT1](#) [LL3AZXX-100-XHS1](#) [LL3AZXX-100-XSD1](#) [30-695B](#)  
[160311E](#)