



Material	X	Y
0.75~1.25	30.0+0.1	22.0+0.1
1.25~2.00	30.2+0.1	22.0+0.1
2.00~3.00	30.4+0.1	22.0+0.1

MATERIAL:

Body:Nylon66, UL rated:94V-2 min

Actuator:Nylon66, UL rated:94V-2 min

Terminal:Brass,silver plated

Rating: 40A 125V AC

25A 250V AC

Function:ON-OFF

Protection Grade:IP65

Contact Resistance: 50mΩ Max

Insulation Resistance:100MΩ Min at DC 500V

Dielectric Strength: 2000VAC 1 minute

Dielectrical life: 10,000 cycles

Mechanical life :50,000 cycles

Operating Temperature: -20℃~80℃

Safety Approval:   



D-SWITCH
东莞市德致电子有限公司
D-SWITCH ELECTRONICS CO.,LTD.

公差 TOLERANCES

.X±0.5 .XX±0.3

角度 ANGLE ±1°

单位

DIMENSION UNIT mm.

版本 VERSION

A0

比例尺 SCALE

1:1

日期 DATE

2020.11.23

品名

TITLE

图号

DRAWING NO

核准 APPROVED BY

核对 CHECKED BY

绘图 DRAWN BY

孙成

R-6-210-WSN-BB

R-6-210-WSN-BB_0

版本 VER

变更说明 CHANGE DESCRIPTION

日期 DATE

ECN NO.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Rocker Switches](#) category:

Click to view products by [D-SWITCH](#) manufacturer:

Other Similar products are found below :

[LTILA6E-1S-WH-RC-FN12VXCR1](#) [6-1571986-9](#) [8007K26N324V52](#) [8055K23Z7V](#) [8055K32Z7V](#) [8055K52Z7V](#) [8138K20E6M50](#)
[PREDD4-07F-BB0FW](#) [PREDD5-07F-BB0GW](#) [999-16716-002](#) [A101J1V3Q004](#) [A103J1ZQ004](#) [A201J1AQ004](#) [A201J50ZQ004](#)
[H8653VBBG2577W](#) [HB130CHNWWNAAC](#) [R13112ABB-602W](#) [1251.0303](#) [1352.0107](#) [1500G51E](#) [1571099-3](#) [1571987-4](#) [1571987-5](#)
[1571988-5](#) [B123J77V7B2](#) [160212E](#) [1634200-7](#) [1801.1164](#) [PANEL-PLUG-VHP-BLACK](#) [PANEL-PLUG-VHP-WT](#) [K2ABAAAAAA](#)
[250011E714](#) [2600R21E](#) [260413E](#) [2639LH/2A7/127000L0](#) [LL3AZXX-100-XGT1](#) [LL3AZXX-100-XHS1](#) [LL3AZXX-100-XSD1](#) [30-695B](#)
[160311E](#) [A103J3ZQ004](#) [A201J61ZQ0004](#) [1852.1102](#) [1890.1104](#) [191.081.011](#) [AE107J1AQ004](#) [1935.3128](#) [1935.3133](#) [1MR7-B](#)
[SY236CD6U622](#)