

This Article Information Sheet (AIS) provides relevant battery information to retailers, consumers, OEMs and others users requesting a GHS-compliant SDS. Articles, such as batteries, are exempt from GHS SDS classification criteria. The GHS criteria is not designed or intended to be used to classify the physical, health and environmental hazards of an article. Branded consumer batteries are defined as electro-technical devices. The design, safety, manufacture, and qualification of branded consumer batteries follow ANSI and IEC battery standards. This document is based on principles set forth in the following hazard communication approaches: ANSI Z-400.1, GHS, JAMP AIS, and IEC 62474.

Duracell Silver Oxide Batteries (Specialty Cells) AIS-SO 10-Dec-15 2 Global Product Stewardship 1/7/2016
AIS-SO 10-Dec-15 2 Global Product Stewardship
10-Dec-15 2 Global Product Stewardship
2 Global Product Stewardship
Global Product Stewardship
1/7/2016
1///2010
moquet.l@duracell.com
Duracell Global Business Unit, 14 Research Drive, Bethel, CT USA 06801
(203) 796- 4430
www.duracell. com
North America: 1-800-551-2355 (9:00 AM - 5:00 PM EST)
Duracell branded consumer silver oxide button cell battery
Electro-technical device
Portable power source for electronic devices
Duracell
301/386; 303/357; 309/393; 319; 361/362; 364; 371; 376; 377; 379; 381/391; 384/392; 389/390; 394; 395/399; 396/397; MX76
(SR)
A battery powers a device by converting stored chemical energy into electrical energy.
DURACELL' 303/357

4. Article Construction

Applicable Battery Industry Standards ANSI C18.1M Part 1, ANSI C18.1M Part 2, ANSI C18.4, IEC 60086-1, IEC 60086-2, IEC 60086-5 Silver Oxide **Electro-technical System** Anode (Electrode - Negative) Zinc (CAS # 7440-66-6) Silver Oxide (CAS # 20667-12-3); Manganese Dioxide (CAS #1313-13-9) Cathode (Electrode - Positive) Electrolyte Alkali Metal Hydroxide (Aqueous Mixture: potassium hydroxide - CAS # 1310-58-3; sodium hydroxide - CAS # 1310-73-2) **Materials of Construction - Can** Nickel Plated Steel **Declarable Substances** None (IEC 62474 Criteria 1) **Mercury Free Battery** Yes (ANSI C18.4M <5ppm)

AIS-SO 1 of 4



Small Cell or Battery	All sizes of button cell batteries fit inside a specially designed test cylinder 2.25 inches
(ANSI C18.1M Part 2; IEC 60086-5)	(57.1mm) long by 1.25 inches (31.70 mm) wide.
5. Health & Safety	
Ingestion/Small Parts Warning	Required for sizes of button cell batteries: Keep away from children. If swallowed, consult a physician immediately.
Normal Conditions of Use	Exposure to contents inside the sealed battery will not occur unless the battery leaks, is exposed to high temperatures, or is mechanically abused.
Note to Physician	A damaged battery will release concentrated and caustic potassium hydroxide.
First Aid - If swallowed	Do not induce vomiting. Seek medical attention immediately. USA CALLS ONLY - CALL 24-
First Aid Free Contact	HOUR NATIONAL BATTERY INGESTION HOTLINE: (202) 625-3333 - COLLECT.
First Aid - Eye Contact First Aid - Skin Contact	Flush with water for at least 15 minutes. Seek medical care if irritation persists. Remove contaminated clothing. Wash skin with soap and water. Seek medical care if
That Aid - Skill Contact	irritation persists.
First Aid - Inhalation	Remove to fresh air.
Precautionary Statements	CAUTION: Keep batteries away from children. If swallowed, consult a physician at once. Batteries can explode or leak if heated, disassembled, shorted, recharged, exposed to fire or high temparure or inserted incorrectly. Do not carry batteries loose in your pocket or purse.
6. Fire Hazard & Firefighting	
Fire Hazard	Batteries may rupture or leak if involved in a fire.
Extinguishing Media	Use any extinguishing media appropriate for the surrounding area.
Fires Involving Large Quantities of Batteries	Large quantities of batteries involved in a fire will rupture and release caustic potassium hydroxide. Firefighters should wear self-contained breathing apparatus and protective clothing.
7. Handling & Storage	
Handling Precautions	Avoid mechanical and electrical abuse. Do not short circuit or install incorrectly. Batteries may rupture or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions.
Storage Precautions	Store batteries in a dry place at normal room temperature. Refrigeration does not make them last longer.
Spills of Large Quantities of Loose Batteries (unpackaged)	Notify spill personnel of large spills. Irritating and flammable vapors may be released from leaking or ruptured batteries. Spread batteries apart to stop shorting. Eliminate all ignition sources. Evacuate area and allow vapors to dissipate. Clean-up personnel should wear appropriate PPE to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in appropriate container for disposal. Remove any spilled liquid with absorbent material and contain for disposal.
8. Disposal Considerations (GHS Section	on 13)
Collection & Proper Disposal	Dispose of used (or excess) batteries in compliance with federal, state/provincial and local regulations. Do not accumulate large quantities of used batteries for disposal as accumulations could cause batteries to short-circuit. Do not incinerate. In countries, such as Canada and the EU, where there are regulations for the collection and recycling of batteries, consumers should dispose of their used batteries into the collection network at municipal depots and retailers. They should not dispose of batteries with household trash.
USA EPA RCRA (40 CFR 261)	Classified as non-hazardous waste (not ignitable, corrosive, reactive or toxic). Federal Universal Waste Regulations (40 CFR 273) do not apply. State requirements may be more stringent than Federal.
California Universal Waste Rule (Cal. Code Regs. Title 22, Div. 4.5, Ch. 23)	California prohibits disposal of batteries as trash (including household trash).

AIS-SO 2 of 4



Regulatory Status	Not regulated. Silver oxide batteries (sometimes referred to as "Dry Cell" or "household
Regulatory Status	
	batteries) are not listed or regulated as dangerous goods under IATA Dangerous Goods
	Regulations, ICAO Technical Instructions, IMDG Code, UN Model Regulations, U.S.
	Hazardous Materials Regulations (49 CFR), and UNECE ADR.
UN Identification Number/	None - Not Required
Shipping Name	
Special Provision (SP) Conformance	Special regulatory provisions require batteries to be packaged in a manner that prevents
	the generation of a dangerous quantity of heat and short circuits. Shippers can prepare
	batteries by taping the terminals, individually packaging batteries, or otherwise
	segregating the batteries to prevent risk of creating a short circuit. Batteries shipped in
	original unopened Duracell packaging is compliant.
US DOT SP	49 CFR 172.102 Special Provision 130
Air Transport (IATA/ICAO) SP	Special Provision A123 (IATA 57th Edition - 2016). NOTE: The words "NOT RESTRICTED"
	and "SPECIAL PROVISION A123" must be included on the description of the substance or
	the Air Waybill, when air way-bill is issued.
Passenger Air Travel	No restrictions
Emergency Transportation Hotline	CHEMTREC 24-Hour Emergency Response Hotline
	Within the United States call +703-527-3887
	Outside the United States, call +1 703-527-3887 (Collect)
10. Regulatory Information (GHS Secti	 on 15)
10a. Battery Requirements	5 25,
USA EPA Mercury Containing &	During the manufacturing process, no mercury is added.
Rechargeable Battery Management	a same
Act of 1996	
EU Battery Directive 2006/66/EC	Compliant with marking and substance restrictions for mercury (<0.0005%); cadmium
& amendment 2013/56/EU	(<0.0020%)I and lead (<0.0040%). Global labels are marked with the special collection
	symbol and the EU qualifier in accordance with EU Battery Directive 2006/66/EC, Article
	11. Paragraph 1 on batteries and accumulators and waste batteries and accumulators
10b. General Requirements	
USA CPSIA 2008 (PL. 11900314)	Exempt
USA CPSC FHSA (16 CFR 1500)	Consumer batteries are not listed as a hazardous product.
USA EPA TSCA Section 13 (40 CFR	For customs clearance purpose, batteries are defined as an "Article".
707.20)	
USA EPA RCRA (40 CFR 261)	Classified as non-hazardous waste (not ignitable, corrosive, reactive or toxic). Federal
	Universal Waste Regulations (40 CFR 273) do not apply. State requirements may be mor
	stringent than Federal.
California Prop 65	No warning required per 3rd party assessment.
CANADA Products Containing	Mercury free
Mercury Regulations SOR/20140254	
FILDEACH CAUSE /4.00	No listed substances are arresent to 0.0400 cm to 3
EU REACH SVHC's (168	No listed substances are present (>0.01% w/w)
Substances/Candidate List December	
EU REACH Article 31	SDS is not required consumer alkaline batteries.
10c. Regulatory Definitions - Articles	
USA OSHA	29 CFR 1910.1200(b)(6)(v)
USA TSCA	40 CFR 704.3; 710.2(3)(c); and [19 CFR 12.1209a)]
EU REACH	Title 1 - Chapter 2 - Article 3(3)
GHS	Section 1.3.2.1

AIS-SO 3 of 4



Globally Harmonized System (GHS)	GHS SDS requirements and classification criteria do not apply to articles or products (such as batteries) that have a fixed shape, which are not intended to release a chemical. The article exemption is found in Section 1.3.2.1.1 of the GHS and reads: <i>The GHS applies to pure substances and their dilute solutions and to mixtures. "Articles" as defined by the Hazard Communication Standard (29 CFR 1900.1200) of the OSHA of the USA, or by similar definition, are outside the scope of the system."</i>
Joint Article Management Promotion Consortium JAMP	JAMP is a Japanese Industry Association who developed the concept of an Article Information Sheet as a supply chain tool to share and communicate chemical information in articles. The AIS authoring process is based on "declarable" substances to meet global regulatory requirements as well as substances to be reported by GADSL, JIG, etc.
IEC 62474 Ed. 1.0 B:2012 Material Declaration for Products of and for the Electro-technical Industry	An international standard that came into effect in March 2012 concerning declaration for electrical and electronic products. IEC 6274 replaces the defunct Joint Industry Guide – Material Declaration for Electro-technical Products (JIG-101-Ed 4.1 (May 21, 2012)
Environmental Standardization for	The general principle for a substance to be included in the database as a declarable substance is: 1) existing national laws or regulations in an IEC member country that are relevant to Electro-technical products and that prohibit or restrict substances, or that have a labeling, communication, reporting or notification requirement, and 2) applying IEC 62474 criteria results in identification of declarable substance.
ANSI Z 400.1/Z19.1 (2010)	2.1 Scope: Applies to preparation of SDSs for hazardous chemicals used under occupational conditions. Does not address how the standard may be applied to articles. It presents basic information on how to develop and write a SDS. Additional information is provided to help comply with state and federal environmental and safety laws and regulations. Elements of the standard may be acceptable for International use.

DISCLAIMER: This AIS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Duracell to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations. This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Duracell assumes no responsibility for injury to the recipient or third persons or for any damage to any property resulting from misuse of the product.

AIS-SO 4 of 4

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for duracell manufacturer:

Other Similar products are found below:

LR20/D/MN1300(K2) MN2400 TURBO LR03/AAA/MN2400(K4) LR14-MN1400-C K2 MN2400B4 15035031 M3 C 2PK 10 ET 675 ET 13 ET 312 ET LR20/D (K2) PLUS POWER LR3/AAA/MN2400(K8) ECONOMY PACK LR6/AA/MN1500(K2) ECONOMY PACK LR6/AA/MN1500(K8) ECONOMY PACK MN11 E11A CEF27 2XAA 2XAAA MN1500 ULTRA POWER 75044300 PC1400 MN2400 CEF14 2XAA 2XAAA ACCU 9V1 5000394002883 MN1604 DRS5965 DRC5906 LR43 15035025 M3 PP3 PC1604 DRS5964 DRO5941 DRC5908 5000394019126 DRP6116 5000394105522 DRG5945 DRC5902 ACCU D2 5000394082991 DRP5953 DRN5924 5000394020092 DRO5940 DRC5904 DRC5907 DR5030A DRG5944 DRP5954 DRACUSB3-EU DRC5909