





WRIST STRAP:

- A. 4mm stud, to fit 4mm spring loaded medical snap socket.
- B. Easy to open plastic clasp secures elastic material in place, and allows the user to easily adjust the wrist band size. Maintains electrical continuity even when open.
- C. Non-allergenic stainless steel base plate, provides excellent skin contact, for superior grounding.
- D. Insulating cap, thermoplastic.
- E. Soft elastic band.

SPC-FO05.DWG

GROUND CORD:

- A. Barrel type banana plug. Fits industry standard banana jack .166 in. (4.22mm).
- B. Metallized, high flex tinsel, black jacket, 12 feet long
- C. One megohm, 1/4 watt, series resistor, molded within snap assembly, limits current for operator safety.
- D. Spring loaded 4mm snap socket.
- E. Alligator clip included.
- F. Date coded with date of manufacture.

BISSLADMEN! AL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION MOD/OR TESTS WE BELIEVE TO BE ADQUIRATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND DUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE NIENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.			SPC TECHNOLOGY						
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:						
	Jason Nash	04/07/08			WRIST STRAP KIT				
	CHECKED BY:	DATE:	SIZE	DWG. NO.			ELEC	TRONIC FILE	REV
	Jeff McVicker	04/07/08	Α		MC23780		14N9045.DWG		Α
	APPROVED BY:	DATE:							
	Jeff McVicker	04/07/08	SCALE: NTS			M.: INCHES [mm]	SHEET: 1 OF 1		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for PCB Holders & Vises category:

Click to view products by Duratool manufacturer:

Other Similar products are found below:

510-R 318-30 511-A 513-B 513-C 318-18 400 510 856-03 204 MC24588 513-A 510-A 301 303 304 305 308 311 312 797-14 845-246 327-12 324 727-04 333 727-12 335 592-12 337 670-A 343 344 346 352 353 354 358 366 371 376 380 385 MC23796 502 506 507 510 511 570