

| REVISIONS |   |                 |            |
|-----------|---|-----------------|------------|
| LTR       | DESCRIPTION   | DATE (YR-MO-DA) | APPROVED   |
| A         | Change CAGE code to 67268. Add cases B and I.<br>Change to 1.3, V1+ and V1-.<br>Changes to table I: $V_{CM}$ , $t_{PLH}$ , $t_{PHL}$ , and delay time between output A and B. | 89-03-09        | M. A. FRYE |
| B         | Add CAGE code 0C7V7. Make changes to paragraphs 3.1 and 3.5.1. - ro   | 00-02-15        | R. MONNIN  |
| C         | Drawing updated to reflect current requirements. - rrp  | 03-11-18        | R. MONNIN  |
| D         | Make correction under the conditions column for $I_{IH}$ and $I_{IL}$ tests as specified in table I. Make changes to figure 2 waveform limits.- ro                            | 05-08-15        | R. MONNIN  |

**CURRENT CAGE CODE 67268**

THE ORIGINAL FIRST SHEET OF THIS DRAWING HAS BEEN REPLACED.


|            |       |   |   |   |   |   |   |   |   |   |   |  |  |  |  |  |  |  |  |  |
|------------|-------|---|---|---|---|---|---|---|---|---|---|--|--|--|--|--|--|--|--|--|
| REV        |       |   |   |   |   |   |   |   |   |   |   |  |  |  |  |  |  |  |  |  |
| SHEET      |       |   |   |   |   |   |   |   |   |   |   |  |  |  |  |  |  |  |  |  |
| REV        |       |   |   |   |   |   |   |   |   |   |   |  |  |  |  |  |  |  |  |  |
| SHEET      |       |   |   |   |   |   |   |   |   |   |   |  |  |  |  |  |  |  |  |  |
| REV STATUS | REV   | D | D | D | D | D | D | D | D | D | D |  |  |  |  |  |  |  |  |  |
| OF SHEETS  | SHEET | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |   |  |  |  |  |  |  |  |  |  |

|  |                                   |  |                           |                   |
|--|-----------------------------------|--|---------------------------|-------------------|
| PMIC N/A   | PREPARED BY<br>DONALD R. OSBORNE  | <b>DEFENSE SUPPLY CENTER COLUMBUS</b><br><b>COLUMBUS, OHIO 43218-3990</b><br><a href="http://www.dsccl.dla.mil">http://www.dsccl.dla.mil</a> |                           |                   |
| <b>STANDARD<br/>MICROCIRCUIT<br/>DRAWING</b><br><br>THIS DRAWING IS AVAILABLE<br>FOR USE BY ALL<br>DEPARTMENTS<br>AND AGENCIES OF THE<br>DEPARTMENT OF DEFENSE<br><br>AMSC N/A | CHECKED BY<br>D. A. DICENZO       |  |                           |                   |
|  | APPROVED BY<br>N. A. HAUCK        | <b>MICROCIRCUIT, LINEAR, DIFFERENTIAL<br/>VOLTAGE COMPARATORS, MONOLITHIC<br/>SILICON</b>  |                           |                   |
|  | DRAWING APPROVAL DATE<br>87-05-04 |  |                           |                   |
|  | REVISION LEVEL<br>D               | SIZE<br>A  | CAGE CODE<br><b>14933</b> | <b>5962-87572</b> |
|  |                                   | SHEET 1 OF 9   |                           |                   |

1. SCOPE

1.1 Scope. This drawing describes device requirements for MIL-STD-883 compliant, non-JAN class level B microcircuits in accordance with MIL-PRF-38535, appendix A.

1.2 Part or Identifying Number (PIN). The complete PIN is as shown in the following example:



1.2.1 Device type(s). The device type(s) identify the circuit function as follows:

| <u>Device type</u> | <u>Generic number</u> | <u>Circuit function</u>                                   |
|--------------------|-----------------------|---|
| 01                 | 527                   | High speed voltage comparator with emitter-follower input |
| 02                 | 529                   | High speed voltage comparator                             |
| 03                 | LM161                 | High speed voltage comparator                             |

1.2.2 Case outline(s). The case outline(s) are as designated in MIL-STD-1835 and as follows:

| <u>Outline letter</u> | <u>Descriptive designator</u> | <u>Terminals</u> | <u>Package style</u> |
|-----------------------|-------------------------------|------------------|----------------------|
| B <u>1/</u>           | GDFP4-F14                     | 14               | Flat pack            |
| C                     | GDIP1-T14 or CDIP2-T14        | 14               | Dual-in-line         |
| D                     | GDFP1-F14 or CDFP2-F14        | 14               | Flat pack            |
| I                     | MACY1-X10                     | 10               | Can                  |

1.2.3 Lead finish. The lead finish is as specified in MIL-PRF-38535, appendix A.

1.3 Absolute maximum ratings.

|   |                  |
|---|------------------|
| Positive supply voltage (V1+):                                |                  |
| Device types 01 and 02.....                                   | +15 V dc         |
| Device type 03 .....  | +16 V dc         |
| Negative supply voltage (V1-):                                |                  |
| Device types 01 and 02.....                                   | -15 V dc         |
| Device type 03 .....  | -16 V dc         |
| Gate supply voltage (V2+) .....                               | +7 V dc          |
| Output voltage .....  | +7 V dc          |
| Differential input voltage (V <sub>IN</sub> ) .....           | ±5 V dc          |
| Input common mode voltage.....                                | ±6 V dc          |
| Lead temperature (soldering, 10 seconds) .....                | +300°C           |
| DC input current.....   | ±10 mA           |
| Power dissipation (P <sub>D</sub> ).....                      | 600 mW <u>2/</u> |
| Junction temperature (T <sub>J</sub> ).....                   | +175°C           |
| Storage temperature range.....                                | -65°C to +150°C  |
| Thermal resistance, junction-to-case (θ <sub>JC</sub> ) ..... | See MIL-STD-1835 |

1/ Inactive for new design. Acceptable only for use in equipment designed or redesigned on or before 29 November 1986.

2/ Must withstand the added P<sub>D</sub> due to short circuit test; e.g., I<sub>OS</sub>.

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>2</b> |

1.4 Recommended operating conditions.

Supply voltage:

- V1+ ..... +5 V dc to +10 V dc
- V1- ..... -6 V dc to -10 V dc
- V2+ ..... +4.5 V dc to +5.5 V dc
- Ambient operating temperature (T<sub>A</sub>)..... -55°C to +125°C

2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbooks. The following specification, standards, and handbooks form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATION

MIL-PRF-38535 - Integrated Circuits, Manufacturing, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

- MIL-STD-883 - Test Method Standard Microcircuits.
- MIL-STD-1835 - Interface Standard Electronic Component Case Outlines.

DEPARTMENT OF DEFENSE HANDBOOKS

- MIL-HDBK-103 - List of Standard Microcircuit Drawings.
- MIL-HDBK-780 - Standard Microcircuit Drawings.

(Copies of these documents are available online at <http://assist.daps.dla.mil/quicksearch/> or <http://assist.daps.dla.mil> or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with MIL-PRF-38535, appendix A for non-JAN class level B devices and as specified herein. Product built to this drawing that is produced by a Qualified Manufacturer Listing (QML) certified and qualified manufacturer or a manufacturer who has been granted transitional certification to MIL-PRF-38535 may be processed as QML product in accordance with the manufacturers approved program plan and qualifying activity approval in accordance with MIL-PRF-38535. This QML flow as documented in the Quality Management (QM) plan may make modifications to the requirements herein. These modifications shall not affect form, fit, or function of the device. These modifications shall not affect the PIN as described herein. A "Q" or "QML" certification mark in accordance with MIL-PRF-38535 is required to identify when the QML flow option is used.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38535, appendix A and herein.

3.2.1 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 1.

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full ambient operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are described in table I.

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>3</b> |

TABLE I. Electrical performance characteristics.

| Test                              | Symbol              | Conditions <u>1</u> /<br>-55°C ≤ T <sub>A</sub> ≤ +125°C<br>unless otherwise specified | Group A<br>subgroups | Device<br>type | Limits |     | Unit |
|-----------------------------------|---------------------|--|----------------------|----------------|--------|-----|------|
|                                   |                     |  |                      |                | Min    | Max |      |
| Input offset voltage              | V <sub>IO</sub>     |  | 1                    | 01,02          |        | 4   | mV   |
|                                   |                     |  | 2,3                  |                |        | 6   |      |
|                                   |                     |  | 1                    | 03             |        | 3   |      |
|                                   |                     |  | 2,3                  |                |        | 5   |      |
| Input bias current                | I <sub>B</sub>      | V <sub>IN</sub> = 0 V  | 1                    | 01             |        | 2   | μA   |
|                                   |                     |  | 2,3                  |                |        | 4   |      |
|                                   |                     |  | 1                    | 02             |        | 12  |      |
|                                   |                     |  | 2,3                  |                |        | 36  |      |
|                                   |                     |  | 1,2,3                | 03             |        | 20  |      |
| Input offset current              | I <sub>OFFSET</sub> | V <sub>IN</sub> = 0 V  | 1                    | 01             |        | 0.5 | μA   |
|                                   |                     |  | 2,3                  |                |        | 1   |      |
|                                   |                     |  | 1                    | 02             |        | 3   |      |
|                                   |                     |  | 2,3                  |                |        | 9   |      |
|                                   |                     |  | 1                    | 03             |        | 4   |      |
|                                   |                     |  | 2,3                  |                |        | 8   |      |
| Common mode voltage range         | V <sub>CM</sub>     |  | 1,2,3                | 01,02          | ±5     |     | V    |
| High level output voltage (LOGIC) | V <sub>OH</sub>     | V <sub>2+</sub> = 4.5 V,<br>I <sub>SOURCE</sub> = -1 mA                                | 1,2,3                | All            | 2.4    |     | V    |
| Low level output voltage (LOGIC)  | V <sub>OL</sub>     | V <sub>2+</sub> = 4.5 V,<br>I <sub>SINK</sub> = 10 mA                                  | 1,2,3                | All            |        | 0.5 | V    |
| High level input voltage (STROBE) | V <sub>IH</sub>     | V <sub>2+</sub> = 4.5 V  | 1                    | All            | 2      |     | V    |
|                                   |                     |  | 2,3                  |                | 2.4    |     |      |
| Low level input voltage (STROBE)  | V <sub>IL</sub>     | V <sub>2+</sub> = 4.5 V  | 1,2,3                | All            |        | 0.8 | V    |

See footnotes at end of table.

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>4</b> |

TABLE I. Electrical performance characteristics – Continued.

| Test                                 | Symbol           | Conditions <sup>1/</sup><br>-55°C ≤ T <sub>A</sub> ≤ +125°C<br>unless otherwise specified                        | Group A<br>subgroups | Device<br>type | Limits |      | Unit |
|--------------------------------------|------------------|--|----------------------|----------------|--------|------|------|
|                                      |                  |  |                      |                | Min    | Max  |      |
| High level input current<br>(STROBE) | I <sub>IH</sub>  | V <sub>2+</sub> = 5.5 V,<br>V <sub>STROBE</sub> = 2.7 V  | 1,2,3                | All            |        | 200  | μA   |
| Low level input current<br>(STROBE)  | I <sub>IL</sub>  | V <sub>2+</sub> = 5.5 V,<br>V <sub>STROBE</sub> = 0.4 V  | 1,2,3                | All            |        | -2   | mA   |
| Output short circuit<br>current      | I <sub>OS</sub>  | V <sub>2+</sub> = 5.5 V,<br>V <sub>OUT</sub> = 0 V   | 1,2,3                | All            |        | -70  | mA   |
| Supply current                       | I <sub>1+</sub>  | V <sub>1+</sub> = 10 V, V <sub>1-</sub> = -10 V,<br>V <sub>2+</sub> = 5.5 V                                      | 1,2,3                | All            |        | 5    | mA   |
|                                      | I <sub>1-</sub>  |  |                      |                |        | -10  |      |
|                                      | I <sub>2+</sub>  |  |                      |                |        | 20   |      |
| Input clamp voltage<br>(STROBE)      | V <sub>IC</sub>  | V <sub>2+</sub> = 5.5 V,<br>I <sub>IN</sub> = -18 mA   | 1,2,3                | All            |        | -1.5 | V    |
| Propagation delay<br>time            | t <sub>PLH</sub> | V <sub>IN</sub> = ±100 mV step, <sup>2/</sup><br>C <sub>L</sub> = 15 pF, T <sub>A</sub> = +25°C,<br>see figure 2 | 9                    | 01             |        | 26   | ns   |
|                                      |                  |  |                      | 02             |        | 22   |      |
|                                      |                  |  |                      | 03             |        | 20   |      |
|                                      | t <sub>PHL</sub> |  |                      | 01             |        | 24   |      |
|                                      |                  |  |                      | 02             |        | 20   |      |
|                                      |                  |  |                      | 03             |        | 20   |      |
| Delay time between<br>output A and B |                  | V <sub>IN</sub> = ±100 mV step, <sup>2/</sup><br>C <sub>L</sub> = 15 pF, T <sub>A</sub> = +25°C,<br>see figure 2 | 9                    | All            |        | 5    | ns   |

<sup>1/</sup> V<sub>1+</sub> = +10 V, V<sub>1-</sub> = 10 V, V<sub>2+</sub> = +5 V, unless otherwise specified.

<sup>2/</sup> For device types 01 and 02, R<sub>4</sub> = 390 Ω. For device type 03, R<sub>4</sub> = 2.43 kΩ.

3.5 Marking. Marking shall be in accordance with MIL-PRF-38535, appendix A. The part shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's PIN may also be marked. For packages where marking of the entire SMD PIN number is not feasible due to space limitations, the manufacturer has the option of not marking the "5962-" on the device.

3.5.1 Certification/compliance mark. A compliance indicator "C" shall be marked on all non-JAN devices built in compliance to MIL-PRF-38535, appendix A. The compliance indicator "C" shall be replaced with a "Q" or "QML" certification mark in accordance with MIL-PRF-38535 to identify when the QML flow option is used.


|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>5</b> |

| Device types    | 01 and 02       |          | 03       |   |
|-----------------|-----------------|----------|----------|---|
| Case outlines   | C and D         |          | B and C  | I |
| Terminal number | Terminal symbol |          |          |   |
| 1               | V1+             | V1+      | INPUT A  |   |
| 2               | NC              | NC       | INPUT B  |   |
| 3               | INPUT A         | INPUT A  | V1-      |   |
| 4               | INPUT B         | INPUT B  | STROBE B |   |
| 5               | NC              | NC       | OUTPUT B |   |
| 6               | V1-             | V1-      | GND      |   |
| 7               | NC              | NC       | OUTPUT A |   |
| 8               | STROBE B        | STROBE B | STROBE A |   |
| 9               | OUTPUT B        | OUTPUT B | V2+      |   |
| 10              | GND             | GND      | V1+      |   |
| 11              | OUTPUT A        | OUTPUT A | ---      |   |
| 12              | NC              | NC       | ---      |   |
| 13              | STROBE A        | STROBE A | ---      |   |
| 14              | V2+             | V2+      | ---      |   |

NC = No connection

FIGURE 1. Terminal connections.

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>6</b> |



PIN NUMBERS REFER TO CASES B, C, AND D  
 CR1-CR4 = 1N94  
 R<sub>1</sub> SELECTED FOR 15: 1 DIVIDER  
 R<sub>2</sub> AND R<sub>3</sub> SELECTED FOR 100 mV AT PIN 4

INPUT  
 PRR = 1 MHz  
 P<sub>w</sub> = 50 ns  
 t<sub>r</sub> = t<sub>f</sub> = 2 ns  
 INPUT = 3.00 V




FIGURE 2. Switching time test circuit and waveforms.

**STANDARD  
 MICROCIRCUIT DRAWING**  
 DEFENSE SUPPLY CENTER COLUMBUS  
 COLUMBUS, OHIO 43218-3990

SIZE  
**A**

**5962-87572**

REVISION LEVEL  
**D**

SHEET  
**7**

3.6 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in MIL-HDBK-103 (see 6.6 herein). The certificate of compliance submitted to DSCC-VA prior to listing as an approved source of supply shall affirm that the manufacturer's product meets the requirements of MIL-PRF-38535, appendix A and the requirements herein.

3.7 Certificate of conformance. A certificate of conformance as required in MIL-PRF-38535, appendix A shall be provided with each lot of microcircuits delivered to this drawing.

3.8 Notification of change. Notification of change to DSCC-VA shall be required for any change that affects this drawing.

3.9 Verification and review. DSCC, DSCC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

#### 4. VERIFICATION

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-38535, appendix A.

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1015 of MIL-STD-883.

(2)  $T_A = +125^{\circ}\text{C}$ , minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

##### 4.3.1 Group A inspection.

a. Tests shall be as specified in table II herein.

b. Subgroups 4, 5, 6, 7, 8, 10, and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

##### 4.3.2 Groups C and D inspections.

a. End-point electrical parameters shall be as specified in table II herein.

b. Steady-state life test conditions, method 1005 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to the preparing or acquiring activity upon request. The test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in method 1005 of MIL-STD-883.

(2)  $T_A = +125^{\circ}\text{C}$ , minimum.

(3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>8</b> |



TABLE II. Electrical test requirements.

| MIL-STD-883 test requirements                                      | Subgroups<br>(in accordance with<br>MIL-STD-883, method 5005,<br>table I) |
|--|---|
| Interim electrical parameters<br>(method 5004)                     | ---   |
| Final electrical test parameters<br>(method 5004)                  | 1*,2,3,9  |
| Group A test requirements<br>(method 5005)                         | 1,2,3,9   |
| Groups C and D end-point<br>electrical parameters<br>(method 5005) | 1   |

\* PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38535, appendix A.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished using DD Form 1692, Engineering Change Proposal.

6.4 Record of users. Military and industrial users shall inform Defense Supply Center Columbus (DSCC) when a system application requires configuration control and the applicable SMD. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronics devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0544.

6.5 Comments. Comments on this drawing should be directed to DSCC-VA, Columbus, Ohio 43218-3990, or telephone (614) 692-0547.

6.6 Approved sources of supply. Approved sources of supply are listed in MIL-HDBK-103. The vendors listed in MIL-HDBK-103 have agreed to this drawing and a certificate of compliance (see 3.6 herein) has been submitted to and accepted by DSCC-VA.

|   |                  |                            |                   |
|---|------------------|----------------------------|-------------------|
| <b>STANDARD<br/>MICROCIRCUIT DRAWING</b><br>DEFENSE SUPPLY CENTER COLUMBUS<br>COLUMBUS, OHIO 43218-3990 | SIZE<br><b>A</b> |                            | <b>5962-87572</b> |
|   |                  | REVISION LEVEL<br><b>D</b> | SHEET<br><b>9</b> |

STANDARD MICROCIRCUIT DRAWING BULLETIN

DATE: 05-08-15

Approved sources of supply for SMD 5962-87572 are listed below for immediate acquisition information only and shall be added to MIL-HDBK-103 and QML-38535 during the next revision. MIL-HDBK-103 and QML-38535 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This information bulletin is superseded by the next dated revision of MIL-HDBK-103 and QML-38535. DSCC maintains an online database of all current sources of supply at <http://www.dscclia.mil/Programs/Smcr/>.

| Standard microcircuit drawing PIN <u>1/</u> | Vendor CAGE number | Vendor similar PIN <u>2/</u> |
|---|--------------------|------------------------------|
| 5962-8757201CA                              | <u>3/</u>          | 527/BCA                      |
| 5962-8757201DA                              | <u>3/</u>          | 527/BDA                      |
| 5962-8757202CA                              | 0C7V7              | 529/BCA                      |
| 5962-8757202DA                              | 0C7V7              | 529/BDA                      |
| 5962-8757203BA                              | 0C7V7              | LM161/BA                     |
| 5962-8757203CA                              | 0C7V7              | LM161/CA                     |
|   | 3V146              | LM161J/883                   |
| 5962-8757203IA                              | 0C7V7              | LM161/IA                     |
|   | 3V146              | LM161H/883B                  |

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ **Caution.** Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.
- 3/ Not available from an approved source of supply.

| <u>Vendor CAGE number</u> | <u>Vendor name and address</u>  |
|---------------------------|---|
| 0C7V7                     | QP Semiconductor<br>2945 Oakmead Village Court<br>Santa Clara, CA 95051 |
| 3V146                     | Rochester Electronics<br>10 Malcolm Hoyt Drive<br>Newburyport, MA 01950 |

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in the information bulletin.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Analog Comparators](#) category:*

*Click to view products by [E2v](#) manufacturer:*

Other Similar products are found below :

[633740E](#) [ADCMP396ARZ-RL7](#) [NCV2200SN2T1G](#) [NCV2200SQ2T2G](#) [SC339DR2G](#) [LM2901SNG](#) [LM339SNG](#) [AP393AM8G-13](#)  
[418524AB](#) [TS393CD C3](#) [LM393SNG](#) [55122](#) [5962-8757203IA](#) [MAX971ESA+T](#) [MAX961ESAT](#) [MAX944ESD+T](#) [MAX931ESAT](#)  
[MAX984CPE](#) [MAX9062EBSTG45](#) [MAX9041AEUTT](#) [MAX9022ASAT](#) [RT2902YDT](#) [M38510/11201B2A](#) [NTE911](#) [5962-8751601DA](#)  
[5962-8751601CA](#) [MAX961EUA+T](#) [MAX9065EBS+TG45](#) [NCV2202SN2T1G](#) [MAX919ESA+T](#) [LT6700HS6-2#TRMPBF](#) [MAX19005CCS+](#)  
[LM339EDR2G](#) [LT6700HS6-2#TRM](#) [NTE919](#) [NTE922](#) [TS883IQ2T](#) [LT6700HVCS6-3#TRMPBF](#) [LT6700HVHS6-3#TRMPBF](#)  
[MAX978EEE+T](#) [MAX975ESA+T](#) [MAX9602EUG+T](#) [MAX997EUA+T](#) [MIC841NYC5-T5](#) [LM393WDT](#) [MCP6564T-E/STVAO](#)  
[MAX983ESA+T](#) [NCX2200GMAZ](#) [LTC1540CMS8#PBF](#) [MC10E1651FNG](#)