# EAO – Your Expert Partner for **Human Machine Interfaces**

## 10-2113.1066 - Single-LED

### 10-2113.1066 - Single-LED



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### **Other Attributes**

Weight 0,001 kg Operation current 7 / 14 mA  $\pm$ 15 % Operating voltage 28 V AC/DC +10 %

### Illumination

Socket T5.5 LED colour blue

### **Optics**

Lumi. intensity 650 mcd Dom. wavelength 470 nm


eao 🔳

Stand: 12.09.2019

# EAO – Your Expert Partner for **Human Machine Interfaces**

### 10-2113.1066 - Single-LED

### **Dimensions**



#### **Additional information**

When using AC/DC types with AC operation, slight flickering can occure

Luminous intensity data of the LEDs on direct voltage Electrical and optical data are measured at 25 °C

The specified versions are built with a protection diode (halve wave rectifier) in series and the LED

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination

For supply voltages above 48 V, it is necessary to use a voltage reduction element (external series resistor or transformer)

eao 🔳

Stand: 12.09.2019

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by EAO manufacturer:

Other Similar products are found below:

LW1A-P1-GD LW1A-P1-W 01-931.3 01-152.025 73.362.4028.0 750-1520 9001OA120 A0142N5 A3DT-500Y AL6M-LK3-R AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-G APD106LN-S APN1126-G APS122DN-W ASLWLD-G ASLWLD-R ATN2100 AYLW4L-A 18-237.035 18-945 HW1A-L1-GD HW1A-P2-GL HW1X-BM411-R HW2A-L1-GL HWAZ1N-OB PA2100/2 PA2200/1 PA2SHIELD PAMR25 LA3P-1C03V-Y 96-923.5 A0244J2 LSPD-120A LSPD-1Y LSPD-6A LSPD-6DA LSPD-6DW LSPD-6DY LSPD-6R LSPD-6W 18-946 AL6H-LK3-A AL6H-P4-JW AL6M-LK1-MG AP8M155-G APD106LN-W APN106L-O