

EAO – Your Expert Partner for Human Machine Interfaces

10-2513.1144 - Single-LED

10-2513.1144 - Single-LED



Attention: The preview is based on a sample product. This can differ from your current configuration.

Other Attributes

| | |
|-------------------|------------------|
| Weight | 0,002 kg |
| Operation current | 13 mA \pm 15 % |
| Operating voltage | 28 V AC/DC +10 % |


Illumination

| | |
|------------|--------|
| Socket | BA9s |
| LED colour | yellow |

Optics

| | |
|-----------------|---------|
| Lumi. intensity | 270 mcd |
| Dom. wavelength | 587 nm |

Dimensions



Additional information

The max. overall length of the lamp may not exceed 25mm

Electrical and optical data are measured at 25 °C

The specified 12, 24, 28, 48 VAC/DC versions are built with a bridge rectifier

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Industrial Panel Mount Indicators / Switch Indicators](#) category:

Click to view products by [EAO](#) manufacturer:

Other Similar products are found below :

[LW1A-P1-GD](#) [LW1A-P1-W](#) [01-931.3](#) [01-152.025](#) [73.362.4028.0](#) [750-1520](#) [9001OA120](#) [A0142N5](#) [A3DT-500Y](#) [AL6M-LK3-R](#) [AL6M-P7P-A](#) [AOLQW-2B0600](#) [AP1M255-A](#) [APD106LN-G](#) [APD106LN-S](#) [APN1126-G](#) [APS122DN-W](#) [ASLWLD-G](#) [ASLWLD-R](#) [ATN2100](#) [AYLW4L-A](#) [18-237.035](#) [18-945](#) [HW1A-L1-GD](#) [HW1A-P2-GL](#) [HW1X-BM411-R](#) [HW2A-L1-GL](#) [HWAZ1N-OB](#) [PA2100/2](#) [PA2200/1](#) [PA2SHIELD](#) [PAMR25](#) [LA3P-1C03V-Y](#) [96-923.5](#) [A0244J2](#) [LSPD-120A](#) [LSPD-1Y](#) [LSPD-6A](#) [LSPD-6DA](#) [LSPD-6DW](#) [LSPD-6DY](#) [LSPD-6R](#) [LSPD-6W](#) [18-946](#) [AL6H-LK3-A](#) [AL6H-P4-JW](#) [AL6M-LK1-MG](#) [AP8M155-G](#) [APD106LN-W](#) [APN106L-O](#)