## EAO – Your Expert Partner for Human Machine Interfaces

### 10-2H24.2055 - Single-LED

### 10-2H24.2055 - Single-LED



Attention: The preview is based on a sample product. This can differ from your current configuration.

### **Other Attributes**

Weight Operation current Operating voltage

### Illumination

Socket LED colour

**Optics** Lumi. intensity Dom. wavelength 0,002 kg 3 mA ±15 % 130 V AC +10 %

BA9s green


450 mcd 525 nm



# EAO – Your Expert Partner for Human Machine Interfaces

### 10-2H24.2055 - Single-LED

### Dimensions



#### Additional information

The max. overall length of the lamp may not exceed 25mm Electrical and optical data are measured at 25 °C The specified 6 VDC, 24 VDC Bi-colour; 130 VAC, 130 DC und 230 VAC versions are built with a protection diode The specified 130 VAC types are developed to run on a supply voltage of 130 VAC only. An operation at a higher supply voltage using commercial lampholders with integrated resistors, is not approved Luminosity and wave length variations caused by LED

manufacturing processes may cause slight differences regarding the illumination



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Industrial Panel Mount Indicators / Switch Indicators category:

Click to view products by EAO manufacturer:

Other Similar products are found below :

LW1A-P1-GD LW1A-P1-W 01-931.3 01-152.025 73.362.4028.0 750-1520 9001OA120 A0142N5 A3DT-500Y AL6M-LK3-R AL6M-P7P-A AOLQW-2B0600 AP1M255-A APD106LN-G APD106LN-S APN1126-G APS122DN-W ASLWLD-G ASLWLD-R ATN2100 AYLW4L-A 18-237.035 18-945 HW1A-L1-GD HW1A-P2-GL HW1X-BM411-R HW2A-L1-GL HWAZ1N-OB PA2100/2 PA2200/1 PA2SHIELD PAMR25 LA3P-1C03V-Y 96-923.5 A0244J2 LSPD-120A LSPD-1Y LSPD-6A LSPD-6DA LSPD-6DW LSPD-6DY LSPD-6R LSPD-6W 18-946 AL6H-LK3-A AL6H-P4-JW AL6M-LK1-MG AP8M155-G APD106LN-W APN106L-O