

General Purpose Pushbutton Switches and Indicators

Series 11/21

Rear Mounted Pushbuttons and Indicators

FEATURES

- 250 VAC/5 A, 220 VDC/0.1 A, 24 VDC/2 A snap action
42 VAC/0.1 A, 42 VDC/0.1 A low-level
- Minimum depth:
Series 11: 1.08"
Series 21: 0.944"
- Mounts in panels to 0.157 inch thick
- Choice of front panel mounting nut
- 5-million operations, low level
- Front panel replaceable lens and lamp



Series 11
pushbutton
low level



Series 21
pushbutton
snap action



Series 21
pushbutton
low level



Series 11
pushbutton
snap action

Reference

International Approvals	page 35
Oil & watertight versions	page 52
Accessories	page 166
Lamps	page 152
Technical Information	page 161

To order: first select switch or indicator desired, indicating contact and terminal type when applicable. Then order lens and illumination separately.

Series 11

Lighted Pushbuttons & Indicators

(Order lens, lamp, and front mounting nut separately)

Switch Element	Momentary	Maintained
	Round	Round
Snap Action		
1-pole Form Z	11-131.8 □ □	11-271.8 □ □
2-pole Form Z	11-132.8 □ 5	11-272.8 □ 5
3-pole Form Z	11-133.8 □ 5	11-273.8 □ 5
4-pole Form z	11-134.8 □ 5	11-274.8 □ 5
Low Level		
1 N.O. contact	11-435.836	11-475.836
1 N.C. contact	11-436.836	11-476.836
2 N.O. contacts	11-431.836	11-471.836
2 N.C. contacts	11-432.836	11-472.836
1 N.O., 1 N.C. contact	11-433.836	11-473.836
Indicator		
Solder connection	11-030.805	
Length to match low level. Universal terminations	11-031.806	

Select contact and terminal type where applicable

8 □ □

1st digit is always 8 (Case color is gray)

Contact material (2nd digit): 1 = Silver, 2 = Gold over silver

Terminal type (3rd digit): 2 = 0.110" Q.C., 5 = Solder

Lenses

□ Add color digit

Description	Round	0	1	2	3	4	5	6	7	8	9
Lens, with diffuser (lamp)	11-931. □	✓		✓		✓	✓	✓			✓
Lens, no diffuser (LED)	11-932. □			✓		✓	✓	✓	✓		

□ 0 = Black, 1 = Solar Black, 2 = Red, 3 = Orange, 4 = Yellow, 5 = Green, 6 = Blue
7 = Clear, 8 = Gray, 9 = White. Black and Gray are opaque.



Mounting Nuts

Description	Part Number
Rear mounting nut (included with switch)	11-934
Front mounting nut required (not included)	
A. Knurled, open face, bright chrome, ø 14 mm	11-935
B. Knurled, flat face, bright chrome, ø 14 mm	11-936
C. Knurled, conical face, bright chrome, ø 16 mm	11-937

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [EAO](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW1L-M1C10V-A](#) [LW2L-M1C20M-A](#) [M22-D-R-GB0/K11](#) [67081K512X](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#)
[FLT 2U EE 01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KA3AC05K-001](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#)
[860K11911T01A](#) [861901](#) [861K11911T01A07](#) [861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [8646ABUL](#) [9533CD4+U574+U4922](#) [95-414.000](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#)
[121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#) [1241.1183.7047](#) [121489](#) [1223A2ULCSA](#) [1241.1183.8000](#) [1241.1183.8029](#)
[D5P-MT4](#) [1301940184](#) [13435AG](#) [13445AD29GX768](#)