EAO – Your Expert Partner for **Human Machine Interfaces**

61-2101.0/D - Keylock switch actuator 2 positions square

61-2101.0/D - Keylock switch actuator 2 positions square



Attention: The preview is based on a sample product. This can differ from your current configuration.

Mounting

Mounting cut-out Ø 16 mm

Other Attributes

Weight 0.065 kg

Operating-/Indication part

Switching angle $B = 42^{\circ}$

IP-Rating

Front protection IP 65

Actuator

Key remove

Switching action Rest - Momentary

Switching element

Rotary positions 2

Function

Keylock switch


eao 🔳

Stand: 15.03.2016

EAO – Your Expert Partner for **Human Machine Interfaces**


61-2101.0/D - Keylock switch actuator 2 positions square

Dimensions



L1 = Solder/Plug-in terminal 2.8 x 0.5 mm

Mounting cut-outs




L1 = Solder/Plug-in terminal 2.8 x 0.5 mm

Wiring diagram



Switching positions



Additional information

Standard lock: DOM 311
Two keys are supplied with each key lock switch
Optional lock numbers on request
If mounted with anti-twist device, the lug is on the left side
Anti-twist ring not needed by using anti-twist device

Legend

Switching action: A = Rest, B = Momentary

eao 🔳

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Actuators category:

Click to view products by EAO manufacturer:

Other Similar products are found below:

LW1B-A0L LW1B-M0 680-4000-00 704.012.618 704.096.0 704.411.018I 704.412.0 704.633.1 704.730.1 704.733.0 862.8102 G6083

9PA24 A0107X A019307 ADC-418G 12MA7 ASDHHY-B HW1F-3G HW1M-L2222 HW4S-31L 200-.704-00 JS-10008 JS-10083 JS
10118 JS-10133 JS-10277 JS-10389 JS-150 JS-552 JS-555 JS-68 JS-6-B JS-91 JS-94 22-211.011 9001KXSDC 92-458.500 SAPT654133

2PA3 SW53AA2 302561 LW2L-A0 3E-10.4 468-10243-001 51-030.005 JM-13 JS-10120 JS-138-B JS-143-B