

Slow-make switching element PIT

When using the switching element, the application guidelines must be observed.

Switching system

The double-break, slow-make switching element is equipped with one or two independent contact systems, acting as normally open or normally closed contact. The normally closed contact has forced opening.

Slow-make contacts with forced action are ideal for high switch ratings.

Up to three switching elements can be snapped to each actuator.

For the emergency-stop pushbutton use the slow-make switching element (max. 2).

Special requirements for positive-opening auxiliary current switches

Positive opening travel	Emergency stop 12.5 mm
Minimum force	Emergency stop 50 N (actuating force at which is safely switched)
Max. travel	Emergency stop 12.5 mm

Material

Housing

The indicator lights/switches may be installed in enclosures with protection class 2 according to DIN EN 61140.

The enclosure must at least have enclosure class 2 according to UL50E.

Material of contact

Hard silver and gold-silver

Switch housing

Plastic

Mechanical characteristics

Terminals

PIT push-in terminal	
- max. wire cross section	1.0 mm ²
- stripping length wire	8 mm
- max. number of wire	2
- max. strand cross section	0.75 mm ²
- stripping strands	use stranded wires only with wire end ferrules of 8 mm length
- max. number of strands	2

Only one polarity is allowed on each side when wiring.

Tightening torque

Screws at the plastic mounting flange max. 0.4–0.5 Nm

Screws at the metal mounting flange max. 0.25–0.3 Nm

Actuating force

1 Normally closed 2 N

1 Normally open 3 N

Actuating travel

approx. 5.8 mm ± 0.2 mm

Mechanical lifetime

(with 1 switching element)

Pushbutton maintained action 1.5 million cycles of operation

Pushbutton momentary action 3 million cycles of operation

Selector switch maintained action 1.25 million cycles of operation

Selector switch momentary action 2.5 million cycles of operation

Emergency-stop switch 50 000 cycles of operation

Keylock switch maintained action 25 000 cycles of operation

Keylock switch momentary action 50 000 cycles of operation

Electrical characteristics

Standards

The switches comply with DIN EN 60947-1/EN IEC 60947-5-1

Rated Insulation Voltage U_i

500 V, as per DIN EN 60947-5-1

Rated impulse withstand voltage U_{imp}

4 kV, according to EN/IEC 60947-5-1

Electrical life

50 000 cycles of operation

Thermal current I_{th}

Max. current at continuous operation and limit temperatures which do not exceed the specified max. values.

6 A

Switching voltage and switching current

as per EN IEC 60947-5-1

voltage	DC13	AC15
24 V	4,0 A	6,0 A
48 V		6,0 A
60 V	1,5 A	
110 V	1,0 A	
120 V		6,0 A
230 V		7,0 A

Recommended minimum operational data

Gold-silver contacts:

Voltage 24 VDC

Current 5 mA

Hard silver contacts:

Voltage 24VDC

Current 50mA

Protection class

Indicators and switches, fit for mounting into devices with protection class II

Ambient conditions

Storage temperature

-40 °C ... +85 °C

Operating temperature

-40 °C ... +55 °C

(other temperatures on request)

Protection degree

IP20

Shock resistance

(single impacts, semi-sinusoidal)

300m/s² pulse width 11 ms, as per DIN EN 60068-2-27

Pollution degree

3

Climatic resistance

Relative humidity

10 ... 95% non-condensing

Approvals

Approbations

CB (IEC 60947-5-1)

DNV

EAC

NFF

cULus

VDE

Conformities

CE

CCC

UKCA

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Switch Contact Blocks](#) / [Switch Kits](#) category:

Click to view products by [EAO](#) manufacturer:

Other Similar products are found below :

[84-8512.2320](#) [A01RTC8](#) [A02512](#) [190-17505-001](#) [190-17508-001](#) [A02506](#) [190-17501-001](#) [190-17506-001](#) [190-17509-003](#) [190-17509-005](#)
[GLZ304](#) [51401](#) [190-17507-002](#) [190-17510-001](#) [WCH-01-CONNECTOR-BLACK](#) [GLZ346](#) [XESD1281](#) [ZB5AW065](#) [09-0A72.3142](#)
[A0150B-D](#) [1.20.119.002/0000](#) [1.20.125.022/0000](#) [5.05510.6440000](#) [71-671.026](#) [92-800.042](#) [LSZ3A](#) [LSZ3C](#) [LSZ3K](#) [1MK1](#)
[5.00100.1420000](#) [5.00100.1410000](#) [2MN6](#) [ZALVB5](#) [1.20126.7040000](#) [1.20126.0020000](#) [1.20122.0610000](#) [1.20122.0420000](#)
[1.20122.0220000](#) [1.20122.0620000](#) [1.20126.3050000](#) [1.20.126.514/0000](#) [1.20126.7010000](#) [3SU1501-1AG00-1BA0](#) [3SU1501-1AG00-1CA0](#)
[3SU1501-1AG20-1CA0](#) [3SU1501-1AG50-1BA0](#) [1.20126.0050000](#) [1.20126.0010000](#) [1.20124.0190000](#) [1.20123.0030000](#)