
EAO – Your Expert Partner for **Human Machine Interfaces**

95-313.000 - Switching element

95-313.000 - Switching element



Attention: The preview is based on a sample product. This can differ from your current configuration.

Front

Front dimension 13 mm x 13 mm

Front shape square

Other Attributes

Weight 0,002 kg

Operating-/Indication part

Lens illumination illuminative

IP-Rating

Front protection IP40

Connection Method

Terminal PCB

Actuator

Switching action Momentary

Switching element

Switching system Slow-make switching element


Contacts 1 NO Switching voltage 48 V DC Switching current 0.05 A

Contact material

EAO – Your Expert Partner for **Human Machine Interfaces**

95-313.000 - Switching element

Component layout



Additional information

for combining with lens and diffuser Suitable for PCB thickness 1.5 to 2.5 mm Special spring clip contacts position and hold the pushbutton in place during the soldering process. The soldering provides the contacting and the mechanical strength. The pushbutton is designed for panel mounting only

Legend

Contacts: NO = Normally open Switching action: B = Momentary

eao 🔳

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Pushbutton Switches category:

Click to view products by EAO manufacturer:

Other Similar products are found below:

8940K2012 LW1L-M1C10V-A LW1L-M1C70-A LW2L-A1C20M-GD LW2L-M1C20M-A 60324L M22-D-R-GB0/K11 M7E-HRN2
67021K512 67081K512X 701PB580 7199K101 810K12910 810KSV30B MML21EA2ADK MML21KA3ABK MML23KA3AC05K-001
MML23KW3AA01W 8418K2 8442K3 8450K1 860K11911T01A 861901 861K11911T01A07 861K13810T00A14 861K13911
8646AB6X718UL 8646ABUL 9001KXRK 907AYY100 PMHD155A1 9533CD4+U574+U4922 95-414.000 99-450.837 99-453.837
PV3H2B0NN-341 1203MRA A22NZBGANGA A22NZBNANGA A22NZMPATRA A2PMA1X03EC56 A3A-5123-02 A3A-7140 A3A-7310 A3A-7340 A3U-TMW-A2C-5M A595 12037A2ULCSA ABD122N-B 1211390004