Printed Circuit Board


Fuseholders and Fuseblocks For 5mm x 20mm Fuses











HTC-45M **PCB Vertical Mount Fuseholder**

250V AC, 6.3A, 2.5W Bayonet Cap/Carrier See Specifications below.

PCB Horizontal Mount Fuseholder

250V AC, 6.3A, 2.5W **Bayonet Cap/Carrier** See Specifications below.

HTC-60M, HTC-65M **PC Board Mount Fuseholder**


Valox 420 SEO; Bronze See Specifications below.


HTC-15M & HTC-140M PCB Fuseblock & Snap-On Cover


250V, 6.3A, 1.6W See Specifications below.


HTC-200M PC Board Mount Fuseclip


For 5mm diameter fuses Tape and Fan Fold packed Tin plated bronze











All tolerances (± 0.005 ", ± 0.13 mm)

SPECIFICATION DATA

Terminals — Brass, tin plated.

Molded Materials — High temperature thermoplastic that meets the flammability ratings of UL 94-VO (HTC-15M material meets UL94-V1); Glow Wire Test: 960°C per IEC 695-2-1.

Solderability — In accordance with IEC 68-2-20.

Electrical — Contact Resistance: ≤ 10mΩ; Insulation Resistance: ≥ 10MΩ; Dielectric Strength ≥ 2000 VAC.

Shock Safety — PC2 (fuseholders).

Agency Approvals — HTC-45M, HTC-50M U.L. Recognized (Guide IZLT2, File # E14853; 6.3A, 250V; CSA Certified (Class 6225-01, File # 47235; 10A, (9226032; 6.3A, 250V) . No Agengy Listings on HTC-15M, HTC-200M,HTC-60M and HTC-65M. HTC-140M. 250V) Semko:

- Standard Qty 10 (No Prefix), Bulk Qty 100 (Prefix Catalog Number with **BK/**). Ammo Pack (HTC-200M) 1000 pieces per box Packaginging -(Prefix Catalog Number TR).

Panel Mount Fuseholders

HTC

For 5mm x 20mm Fuses









HTC-35M **Panel Mount Fuseholder**

250V, 6.3A, 2.5W Threaded Cap/Carrier See Specifications Below

HTC-40M **Panel Mount Fuseholder**

250V, 6.3A, 2.5W Screwdriver slot


HTC-55M **Panel Mount Fuseholder**


250V, 6.3A, 2.5W Bayonet Cap/Carrier See Specifications Below


HTC-70M **Panel Mount Fuseholder**

250V, 10A, 2.5W Bayonet Cap/Carrier See Specifications Below

All tolerances (± 0.005 ", ± 0.13 mm) Mounting Hole Mounting Panel -**.472**" ± .002" (12.0 ± .05mm) .500" ± .002" .217" (5.5mm) .**591**' (12.70 ± .05mm) -1.476"-(37.5mm)







SPECIFICATION DATA

Terminals — Brass, tin plated, with 3mm HTC-35M, -55M, (4.8mm HTC-70M).

Molded Materials — High temperature thermoplastic that meets the flammability ratings of UL 94-VO; Glow Wire Test: 960°C per IEC 695-2-1.

Solderability — In accordance with IEC 68-2-20.

Agency Approvals— UL Recognized Guide 1ZLT2, File E14852; CSA Certified Class 6225-01, File 47235; SEMKO 9005230

Electrical — Contact Resistance: ≤ 10mΩ; Insulation Resistance: ≥ 10MΩ; Dielectric Strength ≥ 2000 VAC.

Shock Safety — PC2 (fuseholders)

Packaging — Standard Qty 10 (No Prefix), Bulk Qty 100 (Prefix Catalog Number with BK/). Ammo Pack (HTC-200M) 1000 pieces per box (Prefix Catalog Number TR).

The only controlled copy of this BIF document is the electronic read-only version located on the Bussmann Network Drive. All other copies of this BIF document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Clips category:

Click to view products by Eaton manufacturer:

Other Similar products are found below:

5960-64 659524 707190 124472H BK/4222 BK/4861-01 1A5600 JN1 1A1310-05 1A5940 4121 4207 4861-01 BK/1A5778 BK/1A5779 BK1A5780 BK/5682-02 4180 3561TR 1A5780 9483 1A3400-12-R 3519 KEYSTONE 01230001Z 3-124-245 3-111-507 01000057H 01020071Z 01250001Z 05200001N 0LCC6 5960-09 BK-1A5601-01 8040.0001 01000058Z 01220087Z 01020079Z 01050002Z 01070002Z 01210002Z BK/1A1119-05 FC -102 bright tin FC -211 bright tin 3511 3515 3517 3520 3522 3529 3532