BUSSMANN

HTC

PCB Fuse accessories for 5 mm fuses



PCB Fuse blocks



HTC-15M

- UL 4248 rating: 250 V, 20 A
- IEC 60217-6 rating: 250 V, 6.3 A, 1.6 W
- · Self-certified voltage rating: 500 V, 20 A
- Tin plated brass terminals
- cURus: Guide IZLT2 & IZLT8, File # 14853
- · Cover available:
 - HTC-150M (Transparent) Flammability rating: UL94-V2
 - HTC-140M (Beige/Natural) Flammability rating: UL94-V0



HTC-78M

- UL 4248 rating: 250 V, 20 A
- IEC 60127-6 rating: 250 V, 6.3 A, 1.6 W
- Self-certified voltage rating: 500 V, 20 A
- cURus: Guide IZLT2 & IZLT8, File # 14853
- · Cover available:
 - HTC-100M Flammability rating: UL94-V0



HTC-60M

- UL 4248 rating: 250 V, 20 A
- IEC 60127-6 rating: 250 V, 6.3 A, 1.6 W
- · Tin plated bronze terminals



BK4-HTC-518M



- 250 V, 15 A
- · Bakelite, UL 94V-0, black
- · Clip: copper alloy, nickel plated
- · Terminals: brass, nickel plated





BK4-HTC-528M


- 250 V, 15 A
- · Bakelite, UL 94V-0, black
- · Clip: copper alloy, nickel plated
- · Terminals: brass, nickel plated




Dimensions- inches (mm)









PCB Fuse clips

HTC-200M


- · Tin plated bronze
- · Tape and fan fold packed




HTC-210M

· Tin plated brass

Dimensions- inches (mm)






PCB Fuse holders



HTC-45M

- 250 V, 10 A, 2.5 W
- Bayonet cap/parrierT TECOMM
- Operating temperature range: -30 °C to + 85 °C
- · cURus: Guida ELT2 & IZLTE File #11853



* Maximum dimension with fuse is installed




HTC-50M

· 250 V, 10 Ke commended repalcement

Bayonet cap/carrier

- Operating emperature range: -30 °C to + 85 °C
- cURus: Guide IZLI2 & IZLI8 File # 14853



* Maximum dimension with fuse is installed

Common HTC specifications

• Solerability: In accordance with IEC 68-2-20

• Molded materials: UL94 V-0

Packaging codes

Packaging code prefix	Description
Blank	10 pieces packed into a carton (HTC-15M and HTC-60M only))
BK-	100 pieces packed into a cardboard shelf package (HTC-15M and HTC-60M only)
BK1-	1000 pieces packed into a poly bag
BK4	4000 pieces packed into a carton (HTC-518M and HTC-528M only)
AP	1000 pieces per box in Ammo pack (HTC-200M only)

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.


Eaton

Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com/electronics

© 2021 Eaton All Rights Reserved Printed in USA Publication No. 2110 February 2021

Eaton is a registered trademark.

All other trademarks are property of their respective owners.















X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Clips category:

Click to view products by Eaton manufacturer:

Other Similar products are found below:

5960-64 659524 707190 124472H BK/4222 BK/4861-01 1A5600 JN1 1A1310-05 1A5940 4121 4207 4861-01 BK/1A5778 BK/1A5779 BK1A5780 BK/5682-02 4180 3561TR 1A5780 9483 1A3400-12-R 3519 KEYSTONE 01230001Z 01000057H 01020071Z 01250001Z 05200001N 0LCC6 5960-09 BK-1A5601-01 8040.0001 01000058Z 01220087Z 01020079Z 01050002Z 01070002Z 01210002Z BK/1A1119-05 FC -102 bright tin FC -211 bright tin 3511 3515 3517 3520 3522 3529 3532 3533 3534