BUSSMANN

HTC

PCB Fuse accessories for 5 mm fuses



PCB Fuse blocks



HTC-15M

- UL 4248 rating: 250 V, 20 A
- IEC 60217-6 rating: 250 V, 6.3 A, 1.6 W
- · Self-certified voltage rating: 500 V, 20 A
- Tin plated brass terminals
- cURus: Guide IZLT2 & IZLT8, File # 14853
- · Cover available:
 - HTC-150M (Transparent) Flammability rating: UL94-V2
 - HTC-140M (Beige/Natural) Flammability rating: UL94-V0



HTC-78M

- UL 4248 rating: 250 V, 20 A
- IEC 60127-6 rating: 250 V, 6.3 A, 1.6 W
- Self-certified voltage rating: 500 V, 20 A
- cURus: Guide IZLT2 & IZLT8, File # 14853
- · Cover available:
 - HTC-100M Flammability rating: UL94-V0



HTC-60M

- UL 4248 rating: 250 V, 20 A
- IEC 60127-6 rating: 250 V, 6.3 A, 1.6 W
- · Tin plated bronze terminals



BK4-HTC-518M



- 250 V, 15 A
- · Bakelite, UL 94V-0, black
- · Clip: copper alloy, nickel plated
- · Terminals: brass, nickel plated





BK4-HTC-528M


- 250 V, 15 A
- · Bakelite, UL 94V-0, black
- · Clip: copper alloy, nickel plated
- · Terminals: brass, nickel plated




Dimensions- inches (mm)









PCB Fuse clips

HTC-200M


- · Tin plated bronze
- · Tape and fan fold packed




HTC-210M

· Tin plated brass

Dimensions- inches (mm)






PCB Fuse holders



HTC-45M

- 250 V, 10 A, 2.5 W
- Bayonet cap/parrierT TECOMM
- Operating temperature range: -30 °C to + 85 °C
- · cURus: Guida ELT2 & IZLTE File #11853



* Maximum dimension with fuse is installed




HTC-50M

· 250 V, 10 Ke commended repalcement

Bayonet cap/carrier

- Operating emperature range: -30 °C to + 85 °C
- cURus: Guide IZLI2 & IZLI8 File # 14853



* Maximum dimension with fuse is installed

Common HTC specifications

• Solerability: In accordance with IEC 68-2-20

• Molded materials: UL94 V-0

Packaging codes

| Packaging code prefix | Description |
|-----------------------|---|
| Blank | 10 pieces packed into a carton (HTC-15M and HTC-60M only)) |
| BK- | 100 pieces packed into a cardboard shelf package (HTC-15M and HTC-60M only) |
| BK1- | 1000 pieces packed into a poly bag |
| BK4 | 4000 pieces packed into a carton (HTC-518M and HTC-528M only) |
| AP | 1000 pieces per box in Ammo pack (HTC-200M only) |

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.


Eaton

Electronics Division 1000 Eaton Boulevard Cleveland, OH 44122 United States Eaton.com/electronics

© 2021 Eaton All Rights Reserved Printed in USA Publication No. 2110 February 2021

Eaton is a registered trademark.

All other trademarks are property of their respective owners.















X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Fuse Holder Accessories category:

Click to view products by Eaton manufacturer:

Other Similar products are found below:

BK/1A1337 1A1853 1A4421 1A5220 903-048 1A1337 1A4544 1A5220-01 CO2-10 CO3-03 348897 B072-7007 BK/1A4421 X30110 09030012H 09050023H 00970021HXNVDL 00BS0232P CO2-04 BK1A1853 BK9834 00970053XP 3566C 00970053H 04450718ZX900 CH10CL BP/FP-3 58600000005 33-012C 880140 00970023S 880150 PDM71009ZXM B109-7091-4 B109-7091-6 B109-7091-5 CFBAR2-M8XSP 901-524 CVR-RH-25100 LFH60030FBC 03540514Z 03540526Z 03540531Z 03540541Z 03540525Z 03540537Z 03540539Z 03540540Z FEH CC2/J