


# ECMT1V24

## Common mode choke, through-hole



### Product features

- Closed magnetic path reduces conductive EMI emission
- High impedance and inductance values
- Robust construction
- High voltage isolation
- Independent winding sections
- Rated voltage: 250 Vac

### Applications

- Industrial IoT equipment
- Motion controls
- Power supplies
- Battery backup
- Renewable energy products
- Smart meters
- Solar/wind generators, inverters, charger controllers
- Medical equipment
- High tech consumer products
- Appliances

### Environmental compliance and general specifications

- Storage temperature range (Component): -40 °C to +85 °C
- Operating temperature range: -40 °C to +125 °C (ambient plus self-temperature rise)
- Wave solder temperature: +260 °C maximum



**Product specifications**


Part number <sup>7</sup>	OCL <sup>1</sup> (mH) minimum (1-2), (4-3)	DCR <sup>2</sup> (Ω) maximum (1-2), (4-3) @ +25 °C	I <sub>rms</sub> <sup>3</sup> (A) short 2,3	SRF (kHz) minimum	Hi-pot <sup>4</sup> (Vac)	Hi-pot <sup>5</sup> (Vac)	Insulation resistance <sup>6</sup> (MΩ) minimum
ECMT1V2429S-5R0-R	5.0	0.3	1.4	712	1500	1000	100
ECMT1V2429S-100-R	10	0.6	1.2	423	1500	1000	100
ECMT1V2429S-150-R	15	0.6	1.0	408	1500	1000	100
ECMT1V2429S-300-R	30	1.6	0.6	276	1500	1000	100

1. Open circuit inductance (OCL) Test parameters: 1 kHz, 0.25 Vrms, 0.0 Adc, +25 °C
2. DCR Test parameters: 4-wire method measured from the root of base, +25 °C
3. I<sub>rms</sub><sup>3</sup>: Maximum DC current for an approximate temperature rise of 40 °C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed +125 °C under worst case operating conditions verified in the end application.


4. Hi-pot: Coil-Coil, 2 seconds, 5 mA
5. Hi-pot: Coil-Core, 2 seconds, 5 mA
6. Insulation Resistance: Coil-Coil and Coil-Core, at 500 Vdc
7. Part Number Definition: ECMT1Vxxxx-yyy-R  
ECMT1V = Product code  
xxxx= Size indicator  
y= Orientation H= horizontal, S= vertical  
zzz=Inductance value in mH, R= decimal point, If no R is present last digit indicates number of zeros  
-R= RoHS compliant

**Mechanical parameters, schematic, pad layout (mm)**


**ECMT1V2429S-xxx-R**



**Recommended PCB layout**



**Schematic**



Part number	A	B	C	D	E	F	G
ECMT1V2429S-xxx-R	20.0 max.	29.0 max.	24.0 max.	3.5 ± 0.5	10.0 ± 0.5	13.0 ± 0.5	0.7 ± 0.1


Part marking: xxx-yyy, xxx =inductance value in mH, yyy= lot code  
Traces or vias underneath the inductor not recommended

**Packaging information (mm)**





ECMT1V2429S-xxx-R

Supplied in tray, 8 trays per carton. (56 parts per tray x 8 trays per box = 448 parts per carton)


(Tray height 25 mm)




**Impedance vs frequency**



**Measurement method**






Common Mode




Differential Mode

Inductance vs frequency



## Wave solder profile



## Reference EN 61760-1:2006

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat		
• Temperature min. ( $T_{smin}$ )	100 °C	100 °C
• Temperature typ. ( $T_{styp}$ )	120 °C	120 °C
• Temperature max. ( $T_{smax}$ )	130 °C	130 °C
• Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )	70 seconds	70 seconds
$\Delta$ preheat to max Temperature	150 °C max.	150 °C max.
Peak temperature ( $T_p$ )*	235 °C – 260 °C	250 °C – 260 °C
Time at peak temperature ( $t_p$ )	10 seconds max 5 seconds max each wave	10 seconds max 5 seconds max each wave
Ramp-down rate	~ 2 K/s min ~3.5 K/s typ ~5 K/s max	~ 2 K/s min ~3.5 K/s typ ~5 K/s max
Time 25 °C to 25 °C	4 minutes	4 minutes

## Manual solder

+350 °C, 4-5 seconds. (by soldering iron), generally manual, hand soldering is not recommended.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

**Eaton**  
**Electronics Division**  
1000 Eaton Boulevard  
Cleveland, OH 44122  
United States  
[www.eaton.com/electronics](http://www.eaton.com/electronics)

© 2021 Eaton  
All Rights Reserved  
Printed in USA  
Publication No. ELX1094 BU-ELX21104  
September 2021

Eaton is a registered trademark.  
All other trademarks are property  
of their respective owners.

Follow us on social media to get the  
latest product and support information.



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Common Mode Chokes / Filters](#) category:*

*Click to view products by [Eaton](#) manufacturer:*

Other Similar products are found below :

[74279408](#) [PE-62911NL](#) [PE-64683](#) [ST6118T-R](#) [T8114NLT](#) [RD5122-10-6M0](#) [TCM0806G-350-2P-T](#) [TCM0806G-650-2P-T](#) [IND-0110](#)  
[UAL21V07012500](#) [UAL21VR0802000](#) [UAL24VR06500CH](#) [UALSC023000000](#) [UALSC1020JH000](#) [UALSC1520JH000](#)  
[UALSU16VD30030](#) [UALSU16VD40010](#) [UALSU9H0305000](#) [UALSU9HF060300](#) [UALSU9VD070100](#) [36-00037](#) [5701610000](#)  
[UALW21HS072450](#) [UALSU9VD070400](#) [UALSU9HF050500](#) [UALSU9H0208000](#) [UALSCF25081300](#) [UAL24VK06450CH](#)  
[PLT10HH501100PNB](#) [PLT10HH401100PNB](#) [PLT10HH1026R0PNB](#) [PE-67531](#) [EXC-X4CH120X](#) [TLH10UB 113 0R5](#) [2752041447](#)  
[2752045447](#) [CMS3-11-R](#) [7351V](#) [CMF16-153131](#) [744252510](#) [T8116NLT](#) [FE2X10-4-2NL](#) [744253200](#) [744253101](#) [744252220](#) [TX8111NLT](#)  
[UAL30VR3500470](#) [CTX01-19077-R](#) [T8003NLT](#) [CTX01-13663](#)