



Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series military fuse

F03A250V1A

UPC:051712157018

Dimensions:

- **Height:** .001 IN
- **Length:** .001 IN
- **Width:** .001 IN

Weight:.1 LB

Warranties:

- Not Applicable

Specifications:

- **Type:** Electronic, Fast-acting
- **Amperage Rating:** 1A
- **Voltage Rating:** 250 Vac, 125 Vdc
- **Interrupt Rating:** 35 AIC at 250 Vac, 10 kAIC at 125 Vac/dc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Diameter:** .25 IN
- **Connection:** Ferrule end X ferrule end
- **Service Response Time:** 4 hour minimum at 100%, 60 minute maximum at 135%, 120 second maximum at 200%

Supporting documents:

- [Product Catalog](#)

Certifications: No Data

Product compliance:

- Contact factory



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Cartridge Fuses](#) category:

Click to view products by [Eaton](#) manufacturer:

Other Similar products are found below :

[5TT3A-R](#) [MBO-20](#) [MDM-4/10](#) [MDQ-V-15/100](#) [MDX-1-6/10](#) [MDX-2](#) [MDX-3-2/10](#) [MDX-6-1/4](#) [FLSR-15](#) [FLSR-30](#) [FRS-1-1/4](#) [FRS-1-6/10](#) [FRS-4/10](#) [H362003](#) [ABC-2](#) [1/2A](#) [AGC-1-1/2RX](#) [AGC-15EX](#) [AGC-V-3-12-R](#) [AGY-50](#) [15019-G](#) [MSL-1-1/2](#) [MSL-1-1/4](#) [MSL-1/2](#) [MSL-1/4](#) [MSL-3](#) [MSL-3/4](#) [MSL-4](#) [MSL-5](#) [BK1/C436-2A](#) [BK1-GMA-1-6-R](#) [BK1-S505-1-R](#) [BK1-S506-3-15-R](#) [BK/MDM-15](#) [BK/MDM-3/4](#) [S501-V-10A](#) [S505-V-500MA](#) [SEF-1697-1-002](#) [301030](#) [303030](#) [FLA10](#) [FLA-4/10](#) [FLNR-5](#) [20.0M6.3X32F](#) [GGB-17-1/2](#) [301001](#)
[301020](#) [311008](#) [313.25](#) [313.75](#)