



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Eaton Bussmann series high speed cylindrical fuse

**FWC-30A10F**

**UPC:**051712370851

### Dimensions:

- **Height:** .46 IN
- **Length:** 20.866 IN
- **Width:** 15.354 IN

**Weight:**.0207 LB

### Warranties:

- Not Applicable

### Specifications:

- **Type:** FWC, Ferrule style
- **Application:** DC common bus, DC drives, power converters/rectifiers, reduced voltage starters
- **Voltage Rating:** 500 Vac/dc (35-800A only)
- **Interrupt Rating:** 200 kAIC Vac, 50 kAIC at 700 Vdc
- **Fuse Indicator:** Non Indicating
- **Packaging Type:** Standard
- **Current Rating:** 30A RMS
- **Pre Arc (I<sub>2</sub>T):** 95
- **Clearing (I<sub>2</sub>T):** Clearing at 600V: 600
- **Connection:** Ferrule end X ferrule end
- **Watt Losses:** 7.5W

### Supporting documents:

- [Product Catalog](#)

### Certifications:

- CSA Certified
- UL Recognized

### Product compliance:

- CE Marked





## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Specialty Fuses](#) category:*

*Click to view products by [Eaton](#) manufacturer:*

Other Similar products are found below :

[63NZ02GL](#) [714125](#) [722134](#) [F02A-4AS](#) [F02B-1A](#) [80NH00GR-6](#) [FWH-200A](#) [FWP-32A14F](#) [12LCT](#) [12TDLSJ63](#) [REN-3](#) [15.5CAVH2E](#)  
[ECF-1](#) [ECF-2](#) [ECF-3](#) [ECF-4](#) [170M0213](#) [170M1369-D](#) [170M3809D](#) [BK/F02B-1A](#) [N-2-1/2](#) [N-3-2/10](#) [NITD2](#) [20D16](#) [KAA-3](#) [KAB-30](#)  
[KAW-3](#) [2D16](#) [LKN-125B](#) [16D27SB](#) [16FC](#) [170M1564D](#) [170M2616](#) [170M2668](#) [170M4161](#) [170M4241](#) [170M4699](#) [ESD63](#) [ABS-30](#) [ABS-8](#)  
[ACF-15](#) [ACF-30](#) [ACO-30](#) [F02A-10A](#) [SSD10](#) [200NH1M](#) [FWP-25A14FI](#) [FWP-40A14FI](#) [FWP-500A](#) [FWP-63A22FI](#)