

1/4" x 1 1/4" Glass Tube Fuses

TDC10 Series (Fast-Acting) & TDC11 Series (Time-Delay)






Description

- TDC10 Series fast-acting
- TDC11 Series time-delay
- Lead free and RoHS compliant
- 1/4" x 1 1/4" physical size
- Glass tube, electroplated brass endcap construction
- Interrupting rating equals 10 times rated current
- TDC10 Series designed to British Standard BS2950A


Ordering

Specify part number and product code prefix,

e.g.: BK/TDC10-20-R



Dimensions - mm Drawing Not to Scale



FAST-ACTING TDC10 SERIES SPECIFICATIONS										
Part		Voltage Rating	Interrupting Rating (amps @ rated voltage) *							
Number	Amps	(Vac)	1000V	750V	500V	350V	250V	150V	100V	32V
TDC10-50-R	50mA	1000	500mA	_	_	_	_	_	_	_
TDC10-60-R	60mA	1000	600mA	_	_	_	_	_	_	_
TDC10-100-R	100mA	1000	1	_	_	_	_	_	_	_
TDC10-150-R	150mA	1000	1.5	_	_	_	_	_	_	_
TDC10-250-R	250mA	1000	2.5	_	_	_	_	_	_	_
TDC10-500-R	500mA	750	_	5	_	_	_	_	_	_
TDC10-750-R	750mA	500	_	_	7.5	_	_	_	_	_
TDC10-1-R	1	350	_	_	_	10	_	_	_	_
TDC10-1.5-R	1.5	250	_	_	_	_	15	_	_	_
TDC10-2-R	2	250	_	_	_	_	20	_	_	_
TDC10-3-R	3	250	_	_	_	_	30	_	_	_
TDC10-5-R	5	250	_	_	_	_	50	_	_	_
TDC10-7-R	7	150	_	_	_	_	_	70	_	_
TDC10-10-R	10	100	_	_	_	_	_	_	100	_
TDC10-12-R	12	32	_	_	_	_	_	_	_	120
TDC10-15-R	15	32	_	_	_	_	_	_	_	150
TDC10-20-R	20	32	_	_	_	_	_	_	_	200
TDC10-25-R	25	32	_	_	-	_	_	_	_	250


TIME-DELAY TDC11 SERIES SPECIFICATIONS									
Part		Voltage Rating	Interrupting Rating (amps @ rated voltage) *						
Number	Amps	(Vac)	1000V	750V	500V	350V	250V	150V	100V
TDC11-50-R	50mA	1000	500mA	_	_	_	_	_	_
TDC11-60-R	60mA	1000	600mA	_	_	_	_	_	_
TDC11-100-R	100mA	1000	1	_	_	_	_	_	_
TDC11-150-R	150mA	1000	1.5	_	_	_	_	_	_
TDC11-250-R	250mA	1000	2.5	_	_	_	_	_	_
TDC11-500-R	500mA	750	_	5	_	_	_	_	_
TDC11-750-R	750mA	500	_	_	7.5	_	_	_	_
TDC11-1-R	1	350	_	_	_	10	_	_	_
TDC11-1.5-R	1.5	250	_	_	_	_	15	_	_
TDC11-2-R	2	250	_	_	_	_	20	_	_
TDC11-3-R	3	250	_	_	_	_	30	_	_
TDC11-5-R	5	250	_	_	_	_	50	_	_
TDC11-7-R	7	150	_	_	_	_	_	70	_
TDC11-10-R	10	100	_	_	_	_	_	_	100


 ^{*} Interrupting Rating: Interrupting rating is 10 times the rated current.
** DC Cold Resistance (Measured at <10% of rated current)



BU?SB13328 Page 1 of 2 Data Sheet OC?2602


Time-Current Curves





Packaging Code				
Packaging Prefix	refix Description			
BK	100 fuses packed into a cardboard carton			
BK1	1000 fuses packed into a cardboard carton			

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.











X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Eaton manufacturer:

Other Similar products are found below:

BK1-S506-6-3-R BK-MDL-3-R BK/ABC-1 BK/MDA-15 GMA-5A GMA250MA 89096-015 8946K153 8961K155 M22-D-R-GB0/K11 M22-L-R/R 6422 6580 CTX20-16-52LP-R CWL530FI CXM/CO/GP/R/BB 6HD36 714125 MBO-2 7314K36 7321K2 F02A-1-1/2A F02A-1-1/2AS F02A-1AS F02A-2AS F02A-3/4A F03A250V12A F03B125V4A MCR-4 MDA-2-8/10-R MDA-30A MDA-V-1/16 F60C500V10AS F60C500V15AS 7563K84 7634K36 MDQ-3/16 MDQ-7/10 MDQ-V-1/10 MDQ-V-1/14 MDQ-V-1/16 MDQ-V-1/2 MDQ-V-1/4 MDQ-V-3/16 MDQ-V-3/8 MDQ-V-6/10 MDQ-V-6-1/4 MDV-1-1/2 MDV-3/8 MDV-4