

RG125DC Series

Flatpak

180x180x40mm



- DC radial blower with electronically commutated external rotor motor. Fully integrated commutation electronics.
- With electronic protection against reverse polarity, blocking and overloading by PTC-resistor; partially impedance protected.
- Spiral housing and blower of fiber-glass reinforced plastic. Housing base of galvanised steel plate.
- Radial air exhaust through housing port.
- Electrical connection via 2 leads AWG 22, TR 64. Stripped and tinned ends.
- UL, CSA, VDE approvals on some models, please contact application engineering.

| Part Number | Curve | CFM @ 0 | VDC | Volt. Range | Power (W) | dBa | Max Amb. Temp C | Bearing Type | Features | Wgt. (lbs) |
|---------------|-------|---------|-----|-------------|-----------|-----|-----------------|--------------|----------|------------|
| RG125-19/12NM | 1 | 35.3 | 12 | 7 to 15 | 2 | 48 | 75 | Ball | Leads | 1.61 |
| RG125-19/12N | 2 | 51.5 | 12 | 7 to 15 | 5 | 58 | 75 | Ball | Leads | 1.61 |
| RG125-19/14NM | 1 | 35.3 | 24 | 12 to 28 | 2 | 48 | 75 | Ball | Leads | 1.61 |
| RG125-19/14N | 2 | 51.5 | 24 | 12 to 28 | 5 | 58 | 75 | Ball | Leads | 1.61 |
| RG125-19/18N | 2 | 51.5 | 48 | 36 to 56 | 5 | 58 | 75 | Ball | Leads | 1.61 |

