



The ECS-2100 Series clock oscillator offers low current drain and is compatible with HCMOS/TTL logic. The metal package with pin #4 case ground acts as a shielding to minimize radiation.

FEATURES

- HCMOS/TTL logic compatible
- Wide frequency range
- Low power consumption
- Resistance weld package
- 3.3V operation (optional)

PART NUMBERING GUIDE

| PART NUMBER * | FREQUENCY STABILITY |
|---------------|---------------------|
| ECS-2100A | ±100 PPM |
| ECS-2100B | ±50 PPM |
| ECS-2100C | ±25 PPM |

* Complete part number to include frequency. i.e. ECS-2100A-100 (100 = 10.000MHz)

OPERATING CONDITIONS/ELECTRICAL CHARACTERISTICS

| PARAMETERS | FREQUENCY RANGE | CONDITIONS | MINIMUM | TYPICAL | MAXIMUM | UNITS |
|---|------------------|--------------------------|---------|---------|---------|-----------------|
| FREQUENCY RANGE (f_0) | 1.000 ~ 150.000 | | 1.000 | | 150.000 | MHz |
| OPERATING TEMP. RANGE (T_{OPR}) | 1.000 ~ 150.000 | | 0 | | +70 | °C |
| STORAGE TEMP. RANGE (T_{STG}) | 1.000 ~ 150.000 | | -55 | | +125 | °C |
| FREQUENCY STABILITY | 1.000 ~ 150.000 | All conditions* | -100 | | +100 | PPM |
| INPUT CURRENT (I_{DD}) | 1.000 ~ 25.000 | | | 17 | 25 | mA |
| | 25.000 ~ 50.000 | | | 33 | 46 | mA |
| | 50.000 ~ 80.000 | | | 45 | 77 | mA |
| | 80.000 ~ 150.000 | | | 67 | 82 | mA |
| OUTPUT SYMMETRY | 1.000 ~ 80.000 | 50% V_{DD} level | 45 | 50 ±3 | 55 | % |
| | 80.000 ~ 150.000 | 50% V_{DD} level | 40 | 50 ±3 | 60 | % |
| RISE TIME (T_R) | 1.000 ~ 150.000 | 10% ~ 90% V_{DD} level | | | 5 | nS |
| FALL TIME (T_F) | 1.000 ~ 150.000 | 90% ~ 10% V_{DD} level | | | 5 | nS |
| OUTPUT VOLTAGE (V_{OL}) (V_{OH}) | 1.000 ~ 150.000 | $I_{OL} = 16$ mA | | | 0.5 | V |
| | 1.000 ~ 150.000 | $I_{OH} = -16$ mA | 4.5 | | | V |
| OUTPUT CURRENT (I_{OL}) (I_{OH}) | 1.000 ~ 100.000 | $V_{OL} = 0.5$ V | | | 16 | mA |
| | 1.000 ~ 150.000 | $V_{OH} = 4.5$ V | | | -16 | mA |
| OUTPUT LOAD | 1.000 ~ 150.000 | TTL | | | 10 | TTL |
| | 1.000 ~ 80.000 | HCMOS | | | 50 | pF |
| | 80.000 ~ 150.000 | HCMOS | | | 30 | pF |
| START-UP TIME (T_s) | 1.000 ~ 150.000 | 0.0V TO 5.0V | | | 10 | mS |
| SUPPLY VOLTAGE (V_{DC}) | | +5.0 ±0.25 | | | | V _{DC} |

* Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, aging, shock and vibration.

PACKAGE DIMENSIONS (mm)



Figure 1) ECS-2100 Series – Side, Bottom and Top views



Figure 2) TTL Output Wave Form




Figure 3) HCMOS Output Wave Form

| PIN CONNECTIONS | |
|-----------------|--------|
| #1 | NC |
| #4 | GROUND |
| #5 | OUTPUT |
| #8 | +5V DC |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Standard Clock Oscillators](#) category:

Click to view products by [ECS Inc](#) manufacturer:

Other Similar products are found below :

[601252](#) [F335-25](#) [F535L-33.333](#) [F535L-50](#) [ASV-20.000MHZ-LR-T](#) [ECS-2018-160-BN-TR](#) [MXO45HS-2C-66.6666MHZ](#) [SiT1602BI-22-33E-50.000000E](#) [SiT8209AI-32-33E-125.000000](#) [SIT8918AA-11-33S-50.000000G](#) [SM4420TEV-40.0M-T1K](#) [F335-24](#) [F335-40](#) [F535L-10](#) [F535L-12](#) [F535L-16](#) [F535L-24](#) [F535L-27](#) [F535L-48](#) [PE7744DW-100.0M](#) [CSX-750FCC14745600T](#) [ASF1-3.686MHZ-N-K-S](#) [XO57CTECNA3M6864](#) [ECS-2100A-147.4](#) [601251](#) [EP16E7E2H26.000MTR](#) [SIT8918AA-11-33S-16.000000G](#) [XO3003](#) [9120AC-2D2-33E212.500000](#) [9102AI-243N25E100.00000](#) [8208AC-82-18E-25.00000](#) [ASDK2-32.768KHZ-LR-T3](#) [8008AI-72-XXE-24.545454E](#) [8004AC-13-33E-133.33000X](#) [AS-4.9152-16-SMD-TR](#) [ASFL1-48.000MHZ-LC-T](#) [SIT8920AM-31-33E-25.0000](#) [DSC1028DI2-019.2000](#) [9121AC-2C3-25E100.00000](#) [9102AI-233N33E100.00000X](#) [9102AI-233N25E200.00000](#) [9102AI-232H25S125.00000](#) [9102AI-133N25E200.00000](#) [9102AC-283N25E200.00000](#) [9001AC-33-33E1-30.000](#) [3921AI-2CF-33NZ125.000000](#) [5730-1SF](#) [PXA000010](#) [8003AI-12-33S-40.00000Y](#) [1602BI-13-33S-19.200000E](#)