



TH97/2478





TH09/2479 IATF 0113686 SGS TH07/1033

G105 ~ G270

 $I_{T(RSM)} = 1.0$ Amperes $V_{BO} = 95$ thru 280 Volts

MECHANICAL DATA:

* Case: DO-41 Molded plastic

* Epoxy: UL94V-O rate flame retardant

* Lead : Axial lead solderable per MIL-STD-202,


Method 208 guaranteed

* Polarity : Color band denotes cathode end

* Mounting position : Any
* Weight : 0.339 gram

* Pb / RoHS Free

SIDACs



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25 °C ambient temperature unless otherwise specified.

RATING	SYMBOL	G105	G120	G130	G220	G240	G260	G270	UNIT
Maximum Repetitive Peak Off-State Voltage	V_{DRM}	±90	±90	±90	±180	±180	±180	±180	V
Minimum Breakover Voltage	V _{BO(Min.)}	95	110	120	205	220	240	250	V
Maximum Breakover Voltage	V _{BO(Max.)}	113	125	135	230	250	270	280	V
Maximum On-State RMS Current	I _{T(RMS)}	1.0							Α
Maximum Peak Surge (Non-Repetitive)	I _{TSM} 20						Α		
On-State RMS Current one-cycle @ 60Hz	TSM	I _{TSM}					20		
Maximum Repetitive Peak Off-State Current	1			10					
(60 Hz Sine Wave , $V_D = Rated V_{DRM}$)	I _{DRM}	10							μΑ
Maximum Dynamic Holding Current	I _{HO}	100							mA
Maximum Breakover Current	I _{BO}	200							μΑ
Operating Junction Temperature Range	TJ	- 40 to + 125							°C
Storage Temperature Range	Тѕтс	- 40 to + 150							°C

Page 1 of 1 Rev. 02 : March 25, 2005

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Diodes - General Purpose, Power, Switching category:

Click to view products by EIC Semiconductor manufacturer:

Other Similar products are found below:

MCL4151-TR3 MMBD3004S-13-F RD0306T-H BAV17-TR BAV19-TR 1N3611 NTE156A NTE574 NTE6244 1SS181-TP

1SS400CST2RA SDAA13 SHN2D02FUTW1T1G LS4151GS08 1N4449 1N456A 1N4934-E3/73 1N914B 1N914BTR 1SS226-TP

RFUH20TB3S D291S45T BAV300-TR BAW56DWQ-7-F BAW75-TAP MM230L-CAA IDW40E65D1 JAN1N3600 JAN1N4153-1

JAN1N4454-1 JAN1N4454UR-1 LL4151-GS18 053684A SMMSD4148T3G 707803H NSVDAN222T1G CDSZC01100-HF LL4150-M-08

1N4454-TR BAV199E6433HTMA1 BAV70HDW-7 BAS28-7 JANTX1N6640 BAW56HDW-13 BAS28 TR VS-HFA04SD60STR-M3

NSVM1MA152WKT1G 1SS388-TP RGP30D-E3/73 VS-8EWF02S-M3