

3.8-30V V_{DD} Hall Effect Sensor

1. Description

The SS43F is small, versatile digital Hall-effect devices that are operated by the magnetic field from a permanent magnet or an electromagnet.

These unipolar sensors are designed to meet the requirements of a wide range of potential applications. These economical unipolar sensors are well suited for simple, high-volume, cost-sensitive position and motion sensing applications.

The 3.8Vdc to 30Vdc supply voltage range allows this device to be used in very wide voltage applications.

2. Features

- Wide operating voltage range: 3.8V to 30V
- Built-in reverse voltage protecting capability
- RoHS-compliant material meets directive 2011/65/EU
- Robust design: will operate up to 150°C
- Package: TO-92S package
- Unipolar respond to a single pole: North (AT) or South (A,BT and ET),making these products well-suited for shift selectors,wiper end/home position, door ajar/open, and vane-interrupt systems etc.

3. Applications

- Speed and RPM sensing
- Door or lid closure detection
- Flow-rate sensing
- Printer head position sensing
- Robotics control
- Medication bin monitor on portable drug carts

4. Package Information

Part Number	Marking	Description
SS43F	43F	Flat, TO-92S package, bulk packing (1000 units per bag)

Table-1 Package Information

5. Pin Configuration and Functions


Name	Number	Description	Outline
VDD	1	Supply Voltage pin	
GND	2	Ground pin	
OUT	3	Collector Output pin	

Table-2 Pin configuration

6. Specification

6.1 Absolute Maximum rating

Over operating free-air temperature range (unless otherwise noted)

Parameter	Symbol	Min	Max	Units
Supply Voltage	V_{DD}	-30	40	V
VDD Reverse Voltage V_{DD}	V_{RDD}		-30	V
Output Voltage	V_{OUT}		40	V
Output Current	I_{OUT}		50	mA
Operating Ambient Temperature	T_A	-40	150	°C
Storage Temperature	T_s	-65	170	°C
Magnetic Flux	B	No Limit		Gauss

Table-3 Absolute Maximum rating

6.2 ESD Protection

Parameter	Value	Unit
HBM (human body mode, C=100pF, R=1.5 kohm)	+/-8000	V

Table-4 ESD Protection


6.3 Electric Characteristics

(At 12V supply, 20mA load, TA= 25°C)

Symbol	Parameter	Test Condition	Min	Typ	Max	Units
V _{DD}	Supply voltage	regular work	3.8		30	V
I _{DD}	Supply Current	V _{DD} = 12V		4.0	10	mA
V _{DSon}	Output saturation voltage	at 20mA, Gauss >Bop			0.4	V
I _{OFF}	Output Leakage Current	B<Brp			10	uA
T _R	Output rise time	V _{DD} =12V at 25°C C _L = 20pF			1.5	us
T _F	Output fall time	V _{DD} =12V at 25°C C _L = 20pF			1.5	us
B _{OP}	Magnetic operating point	TA=25°C	70		180	Gauss
B _{RP}	Magnetic release point	TA=25°C	50		150	Gauss
B _{HYST}	Magnetic hysteresis window	TA=25°C B _{OP} -B _{RP}	30	50	80	Gauss
T	Operating temperature		-40		150	°C
T _s	Storage temperature:		-65		170	°C

Table-5 Electric Characteristics

7. Typical Application




8. Function Description

The SS43F exhibits unipolar magnetic switching characteristics. Therefore, it requires south or north poles to operate properly.


The device behaves as a unipolar with asymmetric operating and release switching points. This means While the magnetic flux density(B) is larger than operate point (Bop), the output will be turned on (Low), while the magnetic flux density(B) is lower than release point (Brp), then turn off (High).

9. Magnetic Activation



Unipolar switch characteristic

10. Dimension (TO-92S)



Dimension; mm

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.420	1.620	0.056	0.064
A1	0.660	0.860	0.026	0.034
b	0.350	0.480	0.014	0.019
b1	0.400	0.550	0.016	0.022
c	0.360	0.510	0.014	0.020
D	3.900	4.100	0.154	0.161
D1	2.280	2.680	0.090	0.106
E	3.050	3.250	0.120	0.128
e	1.270 TYP.		0.050 TYP.	
e1	2.440	2.640	0.096	0.104
L	15.100	15.500	0.594	0.610
θ	45° TYP.		45° TYP	

DISCLAIMER

ELECSUPER PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with ElecSuper products. You are solely responsible for

- (1) selecting the appropriate ElecSuper products for your application;
- (2) designing, validating and testing your application;
- (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements.

These resources are subject to change without notice. ElecSuper grants you permission to use these resources only for development of an application that uses the ElecSuper products described in the resource. Other reproduction and display of these resources are prohibited. No license is granted to any other ElecSuper intellectual property right or to any third party intellectual property right. ElecSuper disclaims responsibility for, and you will fully indemnify ElecSuper and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources. ElecSuper's products are provided subject to ElecSuper's Terms of Sale or other applicable terms available either on www.elecsuper.com or provided in conjunction with such ElecSuper products. ElecSuper's provision of these resources does not expand or otherwise alter ElecSuper's applicable warranties or warranty disclaimers for ElecSuper products.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Board Mount Hall Effect/Magnetic Sensors](#) category:

Click to view products by [ElecSuper](#) manufacturer:

Other Similar products are found below :

[HGPRDT005A](#) [AH1894-FA-7](#) [AH277AZ4-AG1](#) [AV-10448](#) [SS41C](#) [AH1894-Z-7](#) [TLE4946-1L](#) [TLE4976L](#) [SS85CA](#) [BU52003GUL-E2](#)
[AH277AZ4-BG1](#) [AH3376-P-B](#) [TLE4941](#) [TLE4945-2L](#) [AH3360-FT4-7](#) [TLE4941-1](#) [AH374-P-A](#) [SS41-JL](#) [AH1913-W-7](#) [AH3373-P-B](#)
[MA732GQ-Z](#) [MA330GQ-Z](#) [S-57K1NBL2A-M3T2U](#) [S-57P1NBL9S-M3T4U](#) [S-576ZNL2B-L3T2U](#) [S-576ZNL2B-A6T8U](#) [S-57P1NBL0S-](#)
[M3T4U](#) [S-57A1NSL1A-M3T2U](#) [S-57K1RBL1A-M3T2U](#) [S-57P1NBH9S-M3T4U](#) [S-57P1NBH0S-M3T4U](#) [S-57A1NSH1A-M3T2U](#) [S-](#)
[57A1NSH2A-M3T2U](#) [S-57K1NBH1A-M3T2U](#) [S-57A1NNL1A-M3T2U](#) [S-5701BC11B-L3T2U5](#) [S-57GNNL3S-A6T8U](#) [S-57TZ1L1S-](#)
[A6T8U](#) [S-57GSNL3S-A6T8U](#) [S-5716ANDH0-I4T1U](#) [S-57GSNL5S-L3T2U](#) [S-57GDNL3S-L3T2U](#) [S-57GNNL3S-L3T2U](#) [S-57RBNL8S-](#)
[L3T2U](#) [S-57RBNL9S-A6T8U](#) [S-57RB1L8S-L3T2U](#) [S-57GDNL5S-L3T2U](#) [S-57RBNL9S-L3T2U](#) [S-57TZ1L1S-L3T2U](#) [S-57TZNL1S-](#)
[A6T8U](#)