

SAFETY DATA SHEET

Non-Silicone Heat Transfer Compound – Xtra

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

1. Identification

Product identifier

Product name Non-Silicone Heat Transfer Compound – Xtra

Product number HTCX, EHTCX35SL, EHTCX100T, EHTCX700G, EHTCX01K, EHTCX12.5K, ZE

Recommended use of the chemical and restrictions on use

Application Heat Dissipation

Uses advised againstNo specific uses advised against are identified.

Details of the supplier of the safety data sheet

Supplier

ELECTROLUBE. A division of HK WENTWORTH LTD

HK WENTWORTH-AMERICA

PO Box 126257

Benbrook, Texas 76126

USA

info@hkw.us.com +1 888-501-9203

Emergency telephone number

Emergency telephone +1 202 464 2554 (USA only)

+44 1235 239670

2. Hazard(s) identification

Classification of the substance or mixture

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Label elements

Pictogram



Signal word Warning

Hazard statements H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/ container in accordance with national regulations.

Other hazards

Non-Silicone Heat Transfer Compound - Xtra

This product does not contain any substances classified as PBT or vPvB.

3. Composition/information on ingredients

Mixtures

zinc oxide 60-100%

CAS number: 1314-13-2

M factor (Acute) = 1 M factor (Chronic) = 1

Classification

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

Maleic Anhydride <1%

CAS number: 108-31-6

Classification

Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Resp. Sens. 1 - H334 Skin Sens. 1 - H317

The full text for all hazard statements is displayed in Section 16.

4. First-aid measures

Description of first aid measures

General information Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.

Inhalation Remove affected person from source of contamination. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on

their side in the recovery position and ensure breathing can take place.

Ingestion Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water

or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing

such as collar, tie or belt.

Skin Contact Rinse with water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 10 minutes.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards. The severity of the symptoms

described will vary dependent on the concentration and the length of exposure.

Non-Silicone Heat Transfer Compound – Xtra

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

Skin contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

Indication of immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry

powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances:

Harmful gases or vapors.

Advice for firefighters

Protective actions during firefighting

Avoid breathing fire gases or vapors. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Avoid discharge to the aquatic environment. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions No action shall be taken without appropriate training or involving any personal risk. Keep

unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not

touch or walk into spilled material.

Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Avoid discharge to the

aquatic environment. Large Spillages: Inform the relevant authorities if environmental pollution

occurs (sewers, waterways, soil or air).

Methods and material for containment and cleaning up

Non-Silicone Heat Transfer Compound – Xtra

Methods for cleaning up

Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Small Spillages: If the product is soluble in water, dilute the spillage with water and mop it up. Alternatively, or if it is not water-soluble, absorb the spillage with an inert, dry material and place it in a suitable waste disposal container. Large Spillages: If leakage cannot be stopped, evacuate area. Flush spilled material into an effluent treatment plant, or proceed as follows. Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dangerous for the environment. Do not empty into drains. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Reference to other sections

For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

7. Handling and storage

Precautions for safe handling

Usage precautions

Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Handle all packages and containers carefully to minimize spills. Keep container tightly sealed when not in use. Avoid the formation of mists. Avoid discharge to the aquatic environment. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment. Do not reuse empty containers.

Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

Conditions for safe storage, including any incompatibilities

Storage precautions

Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Utilize retaining walls to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

Storage class

Miscellaneous hazardous material storage.

Specific end uses(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

zinc oxide

Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ fume Long-term exposure limit (8-hour TWA): OSHA 15 mg/m³ total dust

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ respirable fraction Short-term exposure limit (15-minute): ACGIH 10 mg/m³ respirable fraction Long-term exposure limit (8-hour TWA): OSHA 5 mg/m³ respirable fraction

Maleic Anhydride

Non-Silicone Heat Transfer Compound - Xtra

Long-term exposure limit (8-hour TWA): OSHA 0.25 ppm 1 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 0.0025 ppm 0.01 mg/m³ inhalable fraction and vapor

A4, RSens, DSens

OSHA = Occupational Safety and Health Administration.

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

RSens = Respiratory sensitizer. DSens = Dermal sensitizer.

zinc oxide (CAS: 1314-13-2)

Immediate danger to life and health

500 mg/m³

Maleic Anhydride (CAS: 108-31-6)

Immediate danger to life and health

10 mg/m³

Exposure controls

Protective equipment







Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimize worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimize exposure.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with OSHA 1910.133. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

Non-Silicone Heat Transfer Compound – Xtra

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

Environmental exposure controls

Keep container tightly sealed when not in use. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance Paste.

Color White.

Odor No characteristic odor.

pH Not available.

Melting point Not available.

Initial boiling point and range Not available.

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or

explosive limits

Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density 2.61 @ 20°C/68°F

Solubility(ies) Insoluble in water.

Partition coefficientNot available.Auto-ignition temperatureNot available.Decomposition TemperatureNot available.

Viscosity 127-141 Pa s @ 20°C/68°F

Explosive properties Not considered to be explosive.

Oxidizing properties Does not meet the criteria for classification as oxidizing.

10. Stability and reactivity

Reactivity There are no known reactivity hazards associated with this product.

Stability Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

Non-Silicone Heat Transfer Compound – Xtra

Possibility of hazardous

reactions

No potentially hazardous reactions known.

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors.

11. Toxicological information

Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitization

Respiratory sensitization Based on available data the classification criteria are not met.

Skin sensitization

Skin sensitization Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitroBased on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity

None of the ingredients are listed or exempt.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

Based on available data the classification criteria are not met.

development

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

.

Non-Silicone Heat Transfer Compound – Xtra

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Prolonged inhalation of high concentrations may damage respiratory system.

Ingestion Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may

be inhaled, resulting in the same symptoms as inhalation.

Skin Contact Prolonged contact may cause dryness of the skin.

Eye contact May cause temporary eye irritation.

Route of entry Ingestion Inhalation Skin and/or eye contact

Target Organs No specific target organs known.

Maleic Anhydride

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,000.0

mg/kg)

Species Rat

ATE oral (mg/kg) 2,000.0

12. Ecological Information

Toxicity Aquatic Acute 1 - H400 Very toxic to aquatic life. Aquatic Chronic 1 - H410 Very toxic to

aquatic life with long lasting effects.

zinc oxide

Acute aquatic toxicity

LE(C)₅₀ $0.1 < L(E)C50 \le 1$

M factor (Acute) 1

Chronic aquatic toxicity

M factor (Chronic) 1

Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility No data available.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

Non-Silicone Heat Transfer Compound – Xtra

General information

The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods

Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

General For limited quantity packaging/limited load information, consult the relevant modal

documentation using the data shown in this section.

UN Number

UN No. (TDG) 3082
UN No. (IMDG) 3082
UN No. (ICAO) 3082
UN No. (DOT) ID8000

UN proper shipping name

Proper shipping name (TDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS zinc oxide)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS zinc oxide)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS zinc oxide)

Proper shipping name (DOT) CONSUMER COMMODITY

Transport hazard class(es)

DOT hazard class 9

DOT hazard label 9

TDG class 9

TDG label(s) 9

IMDG Class 9

ICAO class/division 9

Transport labels



DOT transport labels



Packing group

Non-Silicone Heat Transfer Compound – Xtra

TDG Packing Group III

IMDG packing group III

ICAO packing group

Environmental hazards

Environmentally Hazardous Substance



Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-A, S-F

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

15. Regulatory information

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

Maleic Anhydride

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

The following ingredients are listed or exempt:

zinc oxide

1.0 %

Maleic Anhydride

1.0 %

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

Non-Silicone Heat Transfer Compound - Xtra

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

Non-Silicone Heat Transfer Compound – Xtra

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

zinc oxide

Present.

Maleic Anhydride

Present.

Inventories

US - TSCA

The following ingredients are listed or exempt:

zinc oxide

Present.

Reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate

Present.

Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene

Present.

Maleic Anhydride

Present.

US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

16. Other information

Training advice Read and follow manufacturer's recommendations. Only trained personnel should use this

material.

Issued by Bethan Massey

Revision date 3/5/2017

Revision 1

SDS No. 514

Hazard statements in full H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for electrolube manufacturer:

Other Similar products are found below:

TCRGUNB ER2220RP250G GP300S GP500S HTCX35SL EAD200D TPM350 SCP26G 2K300KIT DCT01L SWAJ05L ARW300 DCE0.75L SSS500ML SYR20ML PRS400D GP500SL ER2218RP250G ER2224 UR5638 CCRG01L SPG900G DEI05L ER221935SL GP300SL HTS100T ASA250ML HTC700G ULL200D EADI200D AFAG35SL ECW025 EADPI200 HTSP100T CMO200D FSC05L HTC100T OSL400 SYR02ML URC200D ER2223 RST250 SOB200D UR5118RP250G UR5528RP250G DDF400 ML NSCP400H AFC400D/12 SYR10ML DCA01L