

PWB/PBB/PJB/PNB/PRB/PVB Paints

A range of quick drying, high quality, universal spray paints based on alkyd resins. They exhibit excellent coverage and hardness characteristics and are ideally suited for use in manufacturing, repair and for home and workshop use. These paints use the International RAL classification system. Colours available are white, blue, yellow, black, red and green.

- Excellent coverage & flow; easy to apply
- Fast drying with high opacity; various colours available
- Excellent hardness and very good adhesion to bare metal
- Very good resistance to water and other and chemicals; ideal for a variety of applications

Typical Properties:	Gloss	Gloss 90 angle of 60°
	Satin	25 angle of 60°
	Coverage @ ~20µm	1.0-1.5 m ² (depends on colour)
	Drying time @ 20°C	15 minutes (surface)
		3 hours (touch dry)
		24 hours (full cure)
	Maximum Temperature (°C)	110

Description	Packaging	Order Code	Shelf Life
White Gloss RAL 9010	400ml Aerosol	PWB400	24 Months
Blue Gloss RAL 5010	400ml Aerosol	PBB400	24 Months
Yellow Gloss RAL1021	400ml Aerosol	PJB400	24 Months
Black Gloss RAL 9005	400ml Aerosol	PNB400	24 Months
Red Gloss RAL 3000	400ml Aerosol	PRB400	24 Months
Green Gloss RAL 6002	400ml Aerosol	PVB400	24 Months

Directions for Use

- Ensure that surface is dry, smooth and free from dust and grease.
- To test, paint a sample panel in advance. Check synthetic and plastic substrates for adhesion and compatibility. For plastics such as PP and EPDM, a primer coat should be applied first.
- Shake the spray-can well for at least 2 minutes and at intervals during use.
- Spray, (holding the aerosol vertically), at a distance of 25-30 cm from the object to be painted. Best results are obtained by applying several thin coats rather than one single thick coat. Wait a few minutes, with a maximum of 30 minutes, between the applications of each layer.
- After use, clear the valve by spraying with the can inverted
- If repainting is necessary, this should be after 24 hours. Drying of the synthetic paint depends on the thickness of the layer and the ambient temperature.

Revision 1: Jan 2014

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Electrolube](#) manufacturer:

Other Similar products are found below :

[UR5635RP250G](#) [CCRG01L](#) [ARW300](#) [CTG35SL](#) [ULC400D](#) [ULS200D](#) [SWA400H](#) [AFC400D](#) [GP300SL](#) [SGB200D](#) [GP300S](#) [APL400H](#)
[TCRGUNB](#) [APL15ML](#) [SPG35SL](#) [RRR250](#) [HTSX35SL](#) [ETSB000](#) [ER221935SL](#) [HPA200H](#) [BLR10SL](#) [SCP03B](#) [HTCX_ZF10SL](#) [ER2188](#)
[100G](#) [SWAJ05L](#) [ASA250ML](#) [BLV-15ML](#) [DEI05L](#) [IPA100](#) [DCA200H](#) [LRM200D](#) [ASC250ML](#) [SGB35SL](#) [PCM250](#) [CCS020](#)
[UR5041RP250G](#) [HTC35SL](#) [EML200F](#) [ER2074RP250G](#) [CG6035SL](#) [ULS400DB](#) [ER2188 50G](#) [CPL200H](#) [BLR-15ML](#) [IPA01L](#)
[UR5048RP250G](#) [ER2188 250G](#) [MPG50T](#) [HTS35SL](#) [UR5097RP250G](#)