


PIS2D15H(P) Series

Low Profile SMD Inductors for Power Line (High current)

FEATURES

- The PIS2D15H(P) series emphasizes higher current for customers' choice
- Magnetically shielded structure that ensures the high-density mounting configurations.
- Flat bottom surface ensures secure, reliable mounting.
- Provided in embossed carrier tape packaging for use with automatic mounting machines.



APPLICATIONS

Low profile/ large current specifically suitable for Portable telephones, hard disk drives, PDA, DSC and other electronic equipments.


PRODUCT IDENTIFICATION

PIS 2D15H(P) - 3R3 M - T


- | | | | | |
|----------------------------------|-----|-----|-----|--------------------------|
| (1) | (2) | (3) | (4) | (5) |
| (1) Product name | | | | (5) Packaging style |
| (2) Shapes and Dimensions(LxWxT) | | | | T : taping ; None : Bulk |
| (3) Inductance | | | | |
| 3R3 : 3.3uH ; 100 : 10uH | | | | |
| (4) Tolerance | | | | |
| M : ± 20%, N : ± 30% | | | | |

SHAPES AND DIMENSIONS(mm)

(1)PIS2D15H




(2)PIS2D15HP




RECOMMENDED FOOTPRINT(mm)

(1)PIS2D15H



(2)PIS2D15HP



PIS2D15H(P) Series

Low Profile SMD Inductors for Power Line (High current)

ELECTRICAL CHARACTERISTICS

Part Number	Inductance (uH)	Tolerance (±%)	Rdc Typ. (Ω)	Idc Typ.(mA)		Irms Typ. (mA) T ↑ 25°C	Color Coding
				L ↓ 10%	L ↓ 35%		
PIS2D15H(P)-R47□-T	0.47 / 1KHz	30	0.04	3000	3400	2200	Black
PIS2D15H(P)-1R0□-T	1 / 1KHz	20,30	0.049	2600	3000	2000	Black
PIS2D15H(P)-1R2□-T	1.2 / 1KHz	30	0.083	2300	2500	1900	Brown
PIS2D15H(P)-1R5□-T	1.5 / 1KHz	20,30	0.09	2100	2500	1500	Brown
PIS2D15H(P)-2R2□-T	2.2 / 1KHz	20,30	0.09	1800	2100	1280	Red
PIS2D15H(P)-3R3□-T	3.3 / 1KHz	20,30	0.149	1500	1720	1100	Orange
PIS2D15H(P)-3R9□-T	3.9 / 1KHz	20,30	0.158	1400	1560	1020	Yellow
PIS2D15H(P)-4R7□-T	4.7 / 1KHz	20,30	0.197	1300	1500	960	Black
PIS2D15H(P)-5R6□-T	5.6 / 1KHz	20,30	0.232	1200	1300	940	Black
PIS2D15H(P)-6R8□-T	6.8 / 1KHz	20,30	0.266	1100	1300	840	Brown
PIS2D15H(P)-100□-T	10 / 1KHz	20	0.403	940	1100	740	Red
PIS2D15H(P)-150□-T	15 / 1KHz	20	0.567	760	860	600	Orange
PIS2D15H(P)-220□-T	22 / 1KHz	20	0.905	600	680	460	Yellow
PIS2D15H(P)-330□-T	33 / 1KHz	20	1.486	440	480	400	Black
PIS2D15H(P)-470□-T	47 / 1KHz	20	1.814	400	440	260	Brown
PIS2D15H(P)-680□-T	68 / 1KHz	20	3.520	290	330	260	Orange
PIS2D15H(P)-101□-T	100 / 1KHz	20	3.840	240	280	240	Black

1. When ordering, please specify tolerance and packaging codes. Ex: PIS2D15H-3R3M-T

Tolerance : M = ± 20% , N = ± 30%

Packaging : Clear tape and reel { standard }.

2. L , Idc : Agilent/HP 4284A, 1KHz with 1V

3. Rdc : DIGITAL MILLIOHM METER Chroma 16502, or equivalent.

4. Idc for Inductance drop 10% or 35% from its value without current.

5. Irms for a 25°C rise above 25°C ambient.

6. Operating temperature range from -25°C to 105°C.

7. Packaging quantity: 1000 pcs/reel

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Fixed Inductors](#) category:

Click to view products by [EMTEK](#) manufacturer:

Other Similar products are found below :

[CR32NP-100KC](#) [CR32NP-151KC](#) [CR32NP-180KC](#) [CR32NP-181KC](#) [CR32NP-1R5MC](#) [CR32NP-390KC](#) [CR32NP-3R9MC](#) [CR32NP-680KC](#) [CR32NP-820KC](#) [CR32NP-8R2MC](#) [CR43NP-390KC](#) [CR43NP-560KC](#) [CR43NP-680KC](#) [CR54NP-181KC](#) [CR54NP-470LC](#) [CR54NP-820KC](#) [CR54NP-8R5MC](#) [70F224AI](#) [MGDQ4-00004-P](#) [MHL1ECTTP18NJ](#) [MHQ1005P10NJ](#) [MHQ1005P1N0S](#) [MHQ1005P2N4S](#) [MHQ1005P3N6S](#) [MHQ1005P5N1S](#) [MHQ1005P8N2J](#) [PE-51506NL](#) [PE-53601NL](#) [PE-53602NL](#) [PE-53630NL](#) [PE-53824SNLT](#) [PE-92100NL](#) [PG0434.801NLT](#) [PG0936.113NLT](#) [9220-20](#) [9310-16](#) [PM06-2N7](#) [PM06-39NJ](#) [A01TK](#) [1206CS-471XJ](#) [HC2LP-R47-R](#) [HC2-R47-R](#) [HC3-2R2-R](#) [HCF1305-3R3-R](#) [1206CS-151XG](#) [RCH664NP-140L](#) [RCH664NP-4R7M](#) [RCH8011NP-221L](#) [RCP1317NP-332L](#) [RCP1317NP-391L](#)