




Rechargeable AA-2000 (HR6)



Industry Standard Dimensions



Typical Discharge Characteristics



Specifications

- Classification:** ACCU Rechargeable
- Chemical System:** Nickel-Metal Hydride (NiMH)
- Designation:** IEC-HR6
- Nominal Voltage:** 1.2 Volts
- Rated Capacity:** 2000 mAh (to 1.0 volts)
Based on 400 mA (0.2C) discharge rate
- Typical Weight:** 28.0 grams
- Typical Volume:** 8.3 cubic centimeters
- Jacket:** Plastic Label

Internal Resistance:

The internal resistance of the cell varies with state of charge, as follows:

| Cell Charged | Cell 1/2 Discharged |
|---|---------------------|
| 30 milliohms | 40 milliohms |
| (tolerance of ±20% applies to above values) | |

AC Impedance (No Load):

The impedance of the charged cell varies with frequency, as follows:

| Frequency (Hz) | Impedance (milliohms) (Charged Cell) |
|----------------|---|
| 1000 | 12 |

Above values based on AC current set at 1.0 ampere.
Value tolerances are ±20%.

Operating and Storage Temperatures:

To maintain maximum performance, observe the following general guidelines regarding environmental conditions.

- Charge: 0°C to 40°C
- Discharge: 0°C to 50°C
- Storage: -20°C to 30°C
- Humidity: 65±20%

Operating at extreme temperatures, will significantly impact battery cycle life.

Important Notice

This datasheet contains information specific to battery chargers manufactured at the time of its publication.

©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Control Switches](#) category:

Click to view products by [Energizer](#) manufacturer:

Other Similar products are found below :

[80887-99](#) [80932-99](#) [86855-00](#) [88814-30](#) [1424293-1](#) [HW4S-2TC10](#) [89721-12](#) [89804-08](#) [SSN](#) [RL01801](#) [ASD2L20N-LVO](#) [50051857-17](#)
[50099156-001-05](#) [51.155R-15200](#) [50058920-26](#) [CP-FA51](#) [CP-FA49](#) [ACCU-SC/L-3000](#) [PP9M](#) [PP87G](#) [PP86GA](#) [PP71G](#) [PP70G](#) [PP6G](#)
[PP62G](#) [PP58BL](#) [PP56G](#) [PP86GB](#) [PP77GA](#) [PP76G](#) [PP4M](#) [PP47G](#) [PP46G](#) [PP41M](#) [PP40G](#) [PP32G](#) [RD-20](#) [PP23M](#) [PP12G](#) [PORTAPRO](#)
[POM-2708](#) [PNB-2005](#) [3057.0012](#) [CV-075](#) [CV-140SB](#) [CV-150](#) [CV-150S](#) [214X20XK](#) [CV-180](#) [CV-200MB](#)