


1-800-383-7323 USA/CAN www.energizer.com

ENERGIZER EN22





Industry Standard Dimensions



Specifications
NOT INTENDED FOR RETAIL TRADE

Classification: Alkaline

Chemical System: Zinc-Manganese Dioxide (Zn/MnO 2)

No added mercury or cadmium

Designation: ANSI-1604A, IEC-6LR61

Nominal Voltage: 9.0 volts

Jacket:

Operating Temp: -18°C to 55°C (0°F to 130°F)

Typical Weight: 45.6 grams (1.6 oz.)


21.1 cubic centimeters (1.3 cubic inch) **Typical Volume:**

Shelf Life: 5 years at 21°C (80% of initial capacity)

Terminal: Miniature Snap


Milliamp-Hours Capacity

Continuous discharge to 4.8 volts at 21°C




Constant Resistance Performance

Typical Characteristics (21°C)



Constant Current Performance

Typical Characteristics (21°C)



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication. © Energizer Holdings, Inc. - Contents herein do not constitute a warranty.


Form No. EBC - 1206I Page 1 of 2





ENERGIZER EN22



Industry Standard Tests (21°C)







Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication.

© Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

Form No. EBC - 12061 Page 2 of 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Energizer manufacturer:

Other Similar products are found below:

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 50058920-26 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP71G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP12G PORTAPRO POM-2708 PNB-2005 3057.0012 CV-075 CV-140SB CV-150 CV-150S 214X20XK CV-180 CV-200MB