


1-800-383-7323 USA/CAN www.energizer.com

ENERGIZER E93



Industry Standard Dimensions




Classification: Chemical System:

Designation: Nominal Voltage: Nominal IR: Operating Temp: Typical Weight: Typical Volume: Jacket: Shelf Life: Terminal: Alkaline Zinc-Manganese Dioxide (Zn/MnO₂) No added mercury or cadmium ANSI-14A, IEC-LR14 1.5 volts 150 to 300 milliohms (fresh) -18°C to 55°C (0°F to 130°F) 66.2 grams (2.3 oz.) 26.9 cubic centimeters (1.6 cubic inch) Plastic Label 10 years at 21°C Flat Contact


Milliamp-Hours Capacity Continuous discharge to 0.8 volts at 21°C

Specifications



Battery Selection Indicator

Device Selection Guide:



This data sheet contains typical information specific to products manufactured at the time of its publication. ©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.


Form No. EBC - 11040




ENERGIZER E93



1000







Important Notice This data sheet contains typical information specific to products manufactured at the time of its publication. ©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Control Switches category:

Click to view products by Energizer manufacturer:

Other Similar products are found below :

80887-99 80932-99 86855-00 88814-30 1424293-1 HW4S-2TC10 89721-12 89804-08 SSN RL01801 ASD2L20N-LVO 50051857-17 50099156-001-05 51.155R-15200 50058920-26 CP-FA51 CP-FA49 ACCU-SC/L-3000 PP9M PP87G PP86GA PP71G PP70G PP6G PP62G PP58BL PP56G PP86GB PP77GA PP76G PP4M PP47G PP46G PP41M PP40G PP32G RD-20 PP23M PP12G PORTAPRO POM-2708 PNB-2005 3057.0012 CV-075 CV-140SB CV-150 CV-150S 214X20XK CV-180 CV-200MB