



Multilayer ceramic capacitors

Chip, HQF

Series/Type: Chip

Date: February 2009

The following products presented in this data sheet are being withdrawn.

Substitute Products: See www.epcos.com/withdrawal_mlcc

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B37923K5100J070		2009-06-26	2010-06-30	2010-12-31
B37923K5120J060		2009-06-26	2010-06-30	2010-12-31
B37923K5120J070		2009-06-26	2010-06-30	2010-12-31

© EPCOS AG 2009. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B37933K5000B460		2009-06-26	2010-06-30	2010-12-31
B37923K5150J060		2009-06-26	2010-06-30	2010-12-31
B37933K5000B470		2009-06-26	2010-06-30	2010-12-31
B37923K5150J070		2009-06-26	2010-06-30	2010-12-31
B37933K5000B560		2009-06-26	2010-06-30	2010-12-31
B37923K5180J060		2009-06-26	2010-06-30	2010-12-31
B37933K5000B570		2009-06-26	2010-06-30	2010-12-31
B37923K5180J070		2009-06-26	2010-06-30	2010-12-31
B37933K5000B660		2009-06-26	2010-06-30	2010-12-31
B37923K5220J060		2009-06-26	2010-06-30	2010-12-31
B37933K5000B670		2009-06-26	2010-06-30	2010-12-31
B37923K5220J070		2009-06-26	2010-06-30	2010-12-31
B37933K5000B760		2009-06-26	2010-06-30	2010-12-31
B37933K5000B770		2009-06-26	2010-06-30	2010-12-31
B37933K5000B860		2009-06-26	2010-06-30	2010-12-31
B37933K5000B870		2009-06-26	2010-06-30	2010-12-31
B37933K5000B960		2009-06-26	2010-06-30	2010-12-31
B37933K5000B970		2009-06-26	2010-06-30	2010-12-31
B37933K5010B060		2009-06-26	2010-06-30	2010-12-31
B37933K5010B070		2009-06-26	2010-06-30	2010-12-31
B37933K5010B260		2009-06-26	2010-06-30	2010-12-31
B37933K5010B270		2009-06-26	2010-06-30	2010-12-31
B37933K5010B560		2009-06-26	2010-06-30	2010-12-31
B37933K5010B570		2009-06-26	2010-06-30	2010-12-31
B37933K5010B860		2009-06-26	2010-06-30	2010-12-31
B37933K5010B870		2009-06-26	2010-06-30	2010-12-31
B37933K5020B260		2009-06-26	2010-06-30	2010-12-31
B37933K5020B270		2009-06-26	2010-06-30	2010-12-31
B37933K5020B760		2009-06-26	2010-06-30	2010-12-31
B37933K5020B770		2009-06-26	2010-06-30	2010-12-31
B37933K5030B360		2009-06-26	2010-06-30	2010-12-31
B37933K5030B370		2009-06-26	2010-06-30	2010-12-31
B37933K5030B960		2009-06-26	2010-06-30	2010-12-31
B37933K5030B970		2009-06-26	2010-06-30	2010-12-31
B37933K5040C760		2009-06-26	2010-06-30	2010-12-31
B37933K5040C770		2009-06-26	2010-06-30	2010-12-31
B37933K5050C660		2009-06-26	2010-06-30	2010-12-31
B37933K5050C670		2009-06-26	2010-06-30	2010-12-31



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B37933K5060C860		2009-06-26	2010-06-30	2010-12-31
B37933K5060C870		2009-06-26	2010-06-30	2010-12-31
B37933K5080C260		2009-06-26	2010-06-30	2010-12-31
B37933K5080C270		2009-06-26	2010-06-30	2010-12-31
B37933K5100J060		2009-06-26	2010-06-30	2010-12-31
B37933K5100J070		2009-06-26	2010-06-30	2010-12-31
B37933K5120J060		2009-06-26	2010-06-30	2010-12-31
B37933K5120J070		2009-06-26	2010-06-30	2010-12-31
B37933K5150J060		2009-06-26	2010-06-30	2010-12-31
B37933K5150J070		2009-06-26	2010-06-30	2010-12-31
B37933K5180J060		2009-06-26	2010-06-30	2010-12-31
B37933K5180J070		2009-06-26	2010-06-30	2010-12-31
B37933K5220J060		2009-06-26	2010-06-30	2010-12-31
B37933K5220J070		2009-06-26	2010-06-30	2010-12-31
B37933K5270J060		2009-06-26	2010-06-30	2010-12-31
B37933K5270J070		2009-06-26	2010-06-30	2010-12-31
B37933K5820J060		2009-06-26	2010-06-30	2010-12-31
B37933K5820J070		2009-06-26	2010-06-30	2010-12-31
B37923K5000B360		2009-06-26	2010-06-30	2010-12-31
B37923K5000B370		2009-06-26	2010-06-30	2010-12-31
B37923K5000B460		2009-06-26	2010-06-30	2010-12-31
B37923K5000B470		2009-06-26	2010-06-30	2010-12-31
B37923K5000B560		2009-06-26	2010-06-30	2010-12-31
B37923K5000B570		2009-06-26	2010-06-30	2010-12-31
B37923K5000B660		2009-06-26	2010-06-30	2010-12-31
B37923K5000B670		2009-06-26	2010-06-30	2010-12-31
B37923K5000B760		2009-06-26	2010-06-30	2010-12-31
B37923K5000B770		2009-06-26	2010-06-30	2010-12-31
B37923K5000B860		2009-06-26	2010-06-30	2010-12-31
B37923K5000B870		2009-06-26	2010-06-30	2010-12-31
B37923K5000B960		2009-06-26	2010-06-30	2010-12-31
B37923K5000B970		2009-06-26	2010-06-30	2010-12-31
B37923K5010B060		2009-06-26	2010-06-30	2010-12-31
B37923K5010B070		2009-06-26	2010-06-30	2010-12-31
B37923K5010B260		2009-06-26	2010-06-30	2010-12-31
B37923K5010B270		2009-06-26	2010-06-30	2010-12-31
B37923K5010B560		2009-06-26	2010-06-30	2010-12-31
B37923K5010B570		2009-06-26	2010-06-30	2010-12-31



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B37923K5010B860		2009-06-26	2010-06-30	2010-12-31
B37923K5010B870		2009-06-26	2010-06-30	2010-12-31
B37923K5020B260		2009-06-26	2010-06-30	2010-12-31
B37923K5020B270		2009-06-26	2010-06-30	2010-12-31
B37923K5020B760		2009-06-26	2010-06-30	2010-12-31
B37923K5020B770		2009-06-26	2010-06-30	2010-12-31
B37923K5030B360		2009-06-26	2010-06-30	2010-12-31
B37923K5030B370		2009-06-26	2010-06-30	2010-12-31
B37923K5030B960		2009-06-26	2010-06-30	2010-12-31
B37923K5030B970		2009-06-26	2010-06-30	2010-12-31
B37923K5040C760		2009-06-26	2010-06-30	2010-12-31
B37923K5040C770		2009-06-26	2010-06-30	2010-12-31
B37923K5050C660		2009-06-26	2010-06-30	2010-12-31
B37923K5050C670		2009-06-26	2010-06-30	2010-12-31
B37923K5060C860		2009-06-26	2010-06-30	2010-12-31
B37923K5060C870		2009-06-26	2010-06-30	2010-12-31
B37923K5080C260		2009-06-26	2010-06-30	2010-12-31
B37923K5080C270		2009-06-26	2010-06-30	2010-12-31
B37923K5100J060		2009-06-26	2010-06-30	2010-12-31

For further information please contact your nearest EPCOS sales office, which will also support you in selecting a suitable substitute. The addresses of our worldwide sales network are presented at www.epcos.com/sales.

SMD

HQF

Ordering code system




B37923	K	5	100	J	0	60
<p>Type and size Chip size (inch/mm) = Temperature characteristic HQF 0402/1005 \triangle B37923 0603/1608 \triangle B37933</p>						
<p>Termination Standard: K \triangle nickel barrier for all case sizes</p>						
<p>Rated voltage 5 (Code) \triangle 50 VDC</p>						
<p>Capacitance, coded (example) 100 \triangle 10 · 10⁰ pF = 10 pF</p>						
<p>Capacitance tolerance C_R < 10 pF: B \triangle ± 0.1 pF (standard for capacitance values ≤ 3.9 pF) C \triangle ± 0.25 pF (standard for capacitance values ≤ 8.2 pF) D \triangle ± 0.5 pF C_R ≥ 10 pF: F \triangle $\pm 1\%$ G \triangle $\pm 2\%$ J \triangle $\pm 5\%$ (standard) K \triangle $\pm 10\%$</p>						
<p>Decimal place for cap. values < 10 pF, otherwise not used</p>						
<p>Packaging 60 \triangle cardboard tape, 180-mm reel 70 \triangle cardboard tape, 330-mm reel</p>						

SMD

Features

- Ultra-low ESR and high Q factor
- Tight capacitance tolerances
- High stability with respect to time, temperature (T_{CC} : 0 ± 60 ppm/°C), frequency and voltage
- Class 1 characteristic with copper inner electrodes
- Excellent attenuation
- High self-resonant frequency
- Lower power dissipation / Less energy absorption
- Based on AEC-Q200 Rev-C



Applications

- High-frequency applications
- Matching circuits
- Cellular communication, Bluetooth, DECT
- Cable TV, satellite TV (LNB), GPS, satellite radio
- Filters, RF amplifiers, VCOs

Termination

- Nickel barrier terminations (Ni) for lead-free soldering

Options

- Alternative capacitance values and tolerances available on request

Delivery mode

- Cardboard tape, 180-mm and 330-mm reel available

Electrical data

Temperature characteristic			C0H	
Climatic category	(IEC 60068-1)		55/125/56	
Standard			EIA	
Dielectric			Class 1	
Rated voltage		V_R	50	VDC
Test voltage		V_{test}	$2.5 \cdot V_R/5$ s	VDC
Capacitance range		C_R	0.3 pF ... 82 pF	
Temperature coefficient			$0 \pm 60 \cdot 10^{-6}/K$	
Dissipation factor	(limit value)	$\tan \delta$	$< 1.0 \cdot 10^{-3}$	
Insulation resistance ¹⁾	(at +25 °C)	R_{ins}	$> 10^5$	MΩ
Insulation resistance ¹⁾	(at +125 °C)	R_{ins}	$> 10^4$	MΩ
Time constant ¹⁾	(at +25 °C)	τ	> 1000	s
Time constant ¹⁾	(at +125 °C)	τ	> 100	s
Operating temperature range		T_{op}	-55 ... +125	°C
Ageing			none	

1) For $C_R > 10$ nF the time constant $\tau = C \cdot R_{ins}$ is given.

HQF

Multilayer ceramic capacitors

HQF


SMD

Capacitance tolerances

C_R	$C_R \leq 3.9 \text{ pF}$		$4.7 \text{ pF} \leq C_R \leq 8.2 \text{ pF}$		
Code letter	B (standard)	C	B	C (standard)	D
Tolerance	$\pm 0.1 \text{ pF}$	$\pm 0.25 \text{ pF}$	$\pm 0.1 \text{ pF}$	$\pm 0.25 \text{ pF}$	$\pm 0.5 \text{ pF}$

C_R	$C_R \geq 10 \text{ pF}$			
Code letter	F	G	J (standard)	K
Tolerance	$\pm 1\%$	$\pm 2\%$	$\pm 5\%$	$\pm 10\%$


Dimensional drawing



Dimensions (mm)

Case size	(inch)	0402	0603
	(mm)	1005	1608
l		1.0 ± 0.10	1.6 ± 0.15
w		0.5 ± 0.05	0.8 ± 0.10
th		0.5 ± 0.05	0.8 ± 0.10
k		$0.1 - 0.40$	$0.1 - 0.40$


Tolerances to CECC 32101-801

SMD
Recommended solder pad

Recommended dimensions (mm) for reflow soldering

Case size	(inch/mm)	Type	A	C	D
	0402/1005	single chip	0.35 ... 0.45	1.0 ... 1.4	0.4 ... 0.6
	0603/1608	single chip	0.6 ... 0.7	1.8 ... 2.2	0.6 ... 0.8

Recommended dimensions (mm) for wave soldering

Case size	(inch/mm)	Type	A	C	D
	0603/1608	single chip	0.8 ... 0.9	2.2 ... 2.8	0.6 ... 0.8

Termination


HQF

Multilayer ceramic capacitors

HQF

SMD

Product range for HQF chip capacitors

Size inch (l x w)	0402	0603
mm (l x w)	1005	1608
Type	B37923	B37933
$C_R \setminus V_R$ (VDC)	50	50
0.3 pF		
0.4 pF		
0.5 pF		
0.6 pF		
0.7 pF		
0.8 pF		
0.9 pF		
1.0 pF		
1.2 pF		
1.5 pF		
1.8 pF		
2.2 pF		
2.7 pF		
3.3 pF		
3.9 pF		
4.7 pF		
5.6 pF		
6.8 pF		
8.2 pF		
10 pF		
12 pF		
15 pF		
18 pF		
22 pF		
27 pF		
82 pF		

SMD
Ordering codes and packing for HQF, 50 VDC, nickel barrier terminations

C _R	Ordering code	Chip thickness mm	Cardboard tape, Ø180-mm reel	Cardboard tape, Ø330-mm reel
			** \triangle 60	** \triangle 70
			pcs./reel	pcs./reel

Case size 0402, 50 VDC

0.3 pF	B37923K5000B3**	0.5 ±0.05	10000	50000
0.4 pF	B37923K5000B4**	0.5 ±0.05	10000	50000
0.5 pF	B37923K5000B5**	0.5 ±0.05	10000	50000
0.6 pF	B37923K5000B6**	0.5 ±0.05	10000	50000
0.7 pF	B37923K5000B7**	0.5 ±0.05	10000	50000
0.8 pF	B37923K5000B8**	0.5 ±0.05	10000	50000
0.9 pF	B37923K5000B9**	0.5 ±0.05	10000	50000
1.0 pF	B37923K5010B0**	0.5 ±0.05	10000	50000
1.2 pF	B37923K5010B2**	0.5 ±0.05	10000	50000
1.5 pF	B37923K5010B5**	0.5 ±0.05	10000	50000
1.8 pF	B37923K5010B8**	0.5 ±0.05	10000	50000
2.2 pF	B37923K5020B2**	0.5 ±0.05	10000	50000
2.7 pF	B37923K5020B7**	0.5 ±0.05	10000	50000
3.3 pF	B37923K5030B3**	0.5 ±0.05	10000	50000
3.9 pF	B37923K5030B9**	0.5 ±0.05	10000	50000
4.7 pF	B37923K5040C7**	0.5 ±0.05	10000	50000
5.6 pF	B37923K5050C6**	0.5 ±0.05	10000	50000
6.8 pF	B37923K5060C8**	0.5 ±0.05	10000	50000
8.2 pF	B37923K5080C2**	0.5 ±0.05	10000	50000
10 pF	B37923K5100J0**	0.5 ±0.05	10000	50000
12 pF	B37923K5120J0**	0.5 ±0.05	10000	50000
15 pF	B37923K5150J0**	0.5 ±0.05	10000	50000
18 pF	B37923K5180J0**	0.5 ±0.05	10000	50000
22 pF	B37923K5220J0**	0.5 ±0.05	10000	50000

HQF

Multilayer ceramic capacitors
HQF
SMD
Ordering codes and packing for HQF, 50 VDC, nickel barrier terminations

C_R	Ordering code	Chip thickness mm	Cardboard tape, Ø180-mm reel	Cardboard tape, Ø330-mm reel
			** \triangle 60	** \triangle 70
			pcs./reel	pcs./reel

Case size 0603, 50 VDC

0.4 pF	B37933K5000B4**	0.8 ±0.1	4000	16000
0.5 pF	B37933K5000B5**	0.8 ±0.1	4000	16000
0.6 pF	B37933K5000B6**	0.8 ±0.1	4000	16000
0.7 pF	B37933K5000B7**	0.8 ±0.1	4000	16000
0.8 pF	B37933K5000B8**	0.8 ±0.1	4000	16000
0.9 pF	B37933K5000B9**	0.8 ±0.1	4000	16000
1.0 pF	B37933K5010B0**	0.8 ±0.1	4000	16000
1.2 pF	B37933K5010B2**	0.8 ±0.1	4000	16000
1.5 pF	B37933K5010B5**	0.8 ±0.1	4000	16000
1.8 pF	B37933K5010B8**	0.8 ±0.1	4000	16000
2.2 pF	B37933K5020B2**	0.8 ±0.1	4000	16000
2.7 pF	B37933K5020B7**	0.8 ±0.1	4000	16000
3.3 pF	B37933K5030B3**	0.8 ±0.1	4000	16000
3.9 pF	B37933K5030B9**	0.8 ±0.1	4000	16000
4.7 pF	B37933K5040C7**	0.8 ±0.1	4000	16000
5.6 pF	B37933K5050C6**	0.8 ±0.1	4000	16000
6.8 pF	B37933K5060C8**	0.8 ±0.1	4000	16000
8.2 pF	B37933K5080C2**	0.8 ±0.1	4000	16000
10 pF	B37933K5100J0**	0.8 ±0.1	4000	16000
12 pF	B37933K5120J0**	0.8 ±0.1	4000	16000
15 pF	B37933K5150J0**	0.8 ±0.1	4000	16000
18 pF	B37933K5180J0**	0.8 ±0.1	4000	16000
22 pF	B37933K5220J0**	0.8 ±0.1	4000	16000
27 pF	B37933K5270J0**	0.8 ±0.1	4000	16000
82 pF	B37933K5820J0**	0.8 ±0.1	4000	16000

SMD
Typical RF performance for HQF capacitors, case size 0402, 50 VDC

Capacitance pF	$f_{res}^{1)}$ MHz	ESR @ 1 GHz ²⁾ mΩ	Q @ 1 GHz ²⁾	ESR @ $f_{res}^{2)}$ mΩ
0.3	23400	560	920	710
0.4	20350	490	805	605
0.5	19700	440	720	535
0.6	17400	405	650	485
0.7	15100	375	600	445
0.8	14450	355	560	415
0.9	12600	335	520	385
1.0	12000	320	490	365
1.2	10600	295	440	330
1.5	8900	265	390	290
1.8	7100	245	350	265
2.2	6400	225	310	235
2.7	6000	205	275	210
3.3	5500	185	245	190
3.9	5350	170	225	175
4.7	4650	155	200	155
5.6	3950	145	175	140
6.8	4100	130	155	125
8.2	3650	120	140	115
10	3350	110	120	105
12	3350	102	104	94
15	2600	92	88	82
18	2300	84	70	74
22	2200	78	56	66

1) Measured with impedance analyser E4991 A, parts not soldered.

2) Measured with network analyser HP 8753D, parts soldered.

HQF
Multilayer ceramic capacitors
HQF
SMD
Typical RF performance for HQF capacitors, case size 0603, 50 VDC

Capacitance pF	$f_{res}^{3)}$ MHz	ESR @ 1 GHz ⁴⁾ mΩ	Q @ 1 GHz ⁴⁾	ESR @ $f_{res}^{4)}$ mΩ
0.4	17800	445	860	595
0.5	17100	400	805	540
0.6	13600	385	755	510
0.7	12200	345	635	440
0.8	11400	325	595	410
0.9	10600	315	560	390
1.0	9600	300	525	365
1.2	8800	275	455	335
1.5	7900	250	395	300
1.8	6900	240	360	285
2.2	5750	215	305	250
2.7	5100	200	270	235
3.3	4700	185	235	210
3.9	4150	175	210	200
4.7	3550	165	185	185
5.6	3130	150	160	170
6.8	2850	140	135	155
8.2	2730	130	115	140
10	2580	120	96	130
12	2400	110	76	118
15	2150	102	62	108
18	2050	96	50	100
22	1870	88	34	90
27	1780	80	26	82

Capacitance pF	$f_{res}^{3)}$ MHz	ESR @ 1 GHz ⁴⁾ mΩ	Q @ 1 GHz ⁴⁾	ESR @ $f_{res}^{4)}$ mΩ
82	930	52	105	52


3) Measured with impedance analyser E4991 A, parts not soldered.

4) Measured with network analyser HP 8753D, parts soldered.


SMD

Typical characteristics for case size 0402¹⁾


ESR versus capacitance C
(for not soldered parts)




ESR versus capacitance C
at self-resonant frequency (for soldered parts)



ESR versus frequency f



Self-resonant frequency f_{res} versus capacitance C




1) For more detailed information on frequency behavior and characteristics see www.epcos.com/mlcc_impedance.


SMD

Typical characteristics for case size 0402¹⁾

Q factor versus capacitance C



Q factor versus frequency f




1) For more detailed information on frequency behavior and characteristics see www.epcos.com/mlcc_impedance.


SMD

Typical characteristics for case size 0603¹⁾


ESR versus capacitance C
(for not soldered parts)




ESR versus capacitance C
at self-resonant frequency (for soldered parts)



ESR versus frequency f



Self-resonant frequency f_{res} versus capacitance C




1) For more detailed information on frequency behavior and characteristics see www.epcos.com/mlcc_impedance.


SMD

Typical characteristics for case size 0603¹⁾

Q factor versus capacitance C



Q factor versus frequency f



1) For more detailed information on frequency behavior and characteristics see www.epcos.com/mlcc_impedance.

SMD

Cautions and warnings

How to select ceramic capacitors

Remember the following when selecting ceramic capacitors:

1. Ceramic capacitors that must fulfill high quality requirements must be qualified based on AEC-Q200 Rev-C.
2. When ceramic capacitors are used at the connection to a battery or power supply (e.g. clamp 15 or 30 in an automobile) or for safety-relevant applications, two single ceramic capacitors should be connected in series. Alternatively a ceramic capacitor with integrated series circuits should be used in order to reduce the possibility of a short circuit caused by a fracture. The MLSC from EPCOS contains such a series circuit in a single component.
3. The use of multilayer varistors (MLVs) is recommended for ESD protection (see chapter "Effects on mechanical, thermal and electrical stress", section 1.4).
4. Additional stress factors such as continuous operating voltage or application-specific derating must be taken into account in the selection of components (refer to chapter "Reliability").

Recommendations for the circuit board design

1. Components with an optimized geometrical design are preferable where permitted by the application.
2. Use at least FR4 circuit board material.
3. Geometrically optimized circuit boards are preferable, especially those that cannot be deformed.
4. Ceramic capacitors should be placed with a sufficient minimum distance from the edge of a circuit board. High bending forces may be exerted there when boards are separated and during further processing of a board (e.g. when incorporating it in a housing).
5. Ceramic capacitors should always be placed parallel to the possible bending axis of a circuit board.
6. Screw connections should not be used to fix a board or connect several boards. Components should not be placed near screw holes. If screw connections are unavoidable, they should be cushioned, for instance using rubber pads.

SMD

Recommendations for processing

1. Ensure correct positioning of a ceramic capacitor on the solder pad.
2. Be careful when using casting, injection-molded and molding compounds and cleaning agents. They can damage a capacitor.
3. Support a circuit board and reduce placement forces.
4. Do not straighten a board (manually) if it is distorted by soldering.
5. Separate boards with a peripheral saw, or preferably with a milling head (no dicing or breaking).
6. Be careful when subsequently placing heavy or leaded components (e.g. transformers or snap-in components) because of the danger of bending and fracture.
7. When testing, transporting, packing or inserting a board, avoid any deformation of it so that components are not damaged.
8. Avoid excessive force when plugging a connector into a device soldered onto a board.
9. Only mount ceramic capacitors using the soldering process (reflow or wave) that is permissible for them (see chapter "Soldering directions").
10. When soldering, select the softest solder profile possible (heating time, peak temperature, cooling time) to avoid thermal stress and damage.
11. Ensure the correct solder meniscus height and solder quantity.
12. Ensure correct dosing of the cement.
13. Ceramic capacitors with external silver-palladium terminations are intended for conductive adhesion - they are not suited for lead-free soldering processes.

This listing does not claim to be complete, but merely reflects the experience of EPCOS AG.

SMD
Symbols and terms

Symbol	English	German
A	Area	Fläche
C	Capacitance	Kapazität
C ₀	Initial (original) capacitance	Anfangskapazität
C ₁	Capacitance value after one hour's use	Kapazitätswert nach einer Stunde
C _R	Rated capacitance	Nennkapazität
C ₂₀	Capacitance at 20 °C	Kapazität bei 20 °C
C ₂₅	Capacitance at 25 °C	Kapazität bei 25 °C
ΔC	Capacitance change	Kapazitätsänderung
D	Bending displacement	Durchbiegung
E _a	Activation energy	Aktivierungsenergie
ESR	Equivalent series resistance	Ersatzserienwiderstand
F	Force	Kraft
f	Frequency	Frequenz
f _{meas}	Measuring frequency	Messfrequenz
f _{res}	Self-resonant frequency	Eigenresonanzfrequenz
I _{test}	Test current	Prüfstrom
k	Ageing constant	Alterungskonstante
L	Inductance	Induktivität
N	Quantity (integer values)	Anzahl (ganzzahliger Wert)
P _{loss}	Power dissipation or loss	Verlustleistung
Q _{el}	Electrical charge	Elektrische Ladung
Q	Quality	Güte
R _{ins}	Insulation resistance	Isolationswiderstand
R _p	Parallel resistance	Parallelwiderstand
R _s	Series resistance (circuit resistance)	Serienwiderstand
S _v	Rate of rise of a voltage pulse	Flankensteilheit eines Spannungsimpulses
T	Temperature	Temperatur
T _{meas}	Measuring temperature	Messtemperatur
T _{op}	Operating temperature	Betriebstemperatur
T _{ref}	Reference temperature	Bezugstemperatur
T _{test}	Test temperature	Prüftemperatur
t	Time	Zeit
t _r	Rise time of a voltage pulse	Anstiegszeit eines Spannungsimpulses
t _{test}	Test duration	Prüfdauer
tan δ	Dissipation factor	Verlustfaktor

SMD

Symbol	English	German
V	Voltage	Spannung
V ₀	Initial (original) voltage (basic voltage level)	Anfangsspannung (Spannungsgrundpegel)
V _{meas}	Measuring voltage	Messspannung
V _R	Rated voltage	Nennspannung
V _S	Amplitude of a voltage pulse	Hub des Spannungsimpulses
V _{RMS}	Measuring (root-mean-square or effective) AC voltage	Effektivspannung
V _{test}	Test voltage	Prüfspannung
Z	Magnitude of impedance (AC resistance)	Betrag der Impedanz (Wechselstromwiderstand)
α	Temperature coefficient	Temperaturkoeffizient
ε ₀	Absolute dielectric constant	Absolute Dielektrizitätskonstante
ε _r	Relative dielectric constant	Relative Dielektrizitätskonstante
λ	Failure rate	Ausfallrate
τ	Time constant	Zeitkonstante

Abbreviations / Notes

Symbol	English	German
$\square e$	Lead spacing (in mm)	Rastermaß (in mm)
<u>SMD</u>	Surface-mounted devices	Oberflächenmontierbares Bauelement
*	To be replaced by a number in ordering codes, type designations etc.	Platzhalter für Zahl im Bestellnummerncode oder für die Typenbezeichnung.
+	To be replaced by a letter.	Platzhalter für einen Buchstaben.
	All dimensions are given in mm.	Alle Maße sind in mm angegeben.
	The commas used in numerical values denote decimal points.	Verwendete Kommas in Zahlenwerten bezeichnen Dezimalpunkte.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Multilayer Ceramic Capacitors MLCC - SMD/SMT](#) category:

Click to view products by [EPCOS](#) manufacturer:

Other Similar products are found below :

[M39014/01-1467](#) [M39014/02-1218V](#) [M39014/02-1225V](#) [M39014/02-1262V](#) [M39014/02-1301](#) [M39014/22-0631](#) [1210J5000102JCT](#)
[1210J2K00102KXT](#) [1210J5000103KXT](#) [1210J5000223KXT](#) [D55342E07B379BR-TR](#) [D55342E07B523DR-T/R](#) [1812J1K00103KXT](#)
[1812J1K00473KXT](#) [1812J2K00680JCT](#) [1812J4K00102MXT](#) [1812J5000102JCT](#) [1812J5000103JCT](#) [1812J5000682JCT](#) [NIN-FB391JTRF](#)
[NIN-FC2R7JTRF](#) [NPIS27H102MTRF](#) [C1206C101J1GAC](#) [C1608C0G1E472JT000N](#) [C2012C0G2A472J](#) [CA050M0047REH-0607](#)
[2220J2K00101JCT](#) [KHC201E225M76N0T00](#) [1812J1K00222JCT](#) [1812J2K00102KXT](#) [1812J2K00222KXT](#) [1812J2K00472KXT](#) [2-1622820-](#)
[7-CUT-TAPE](#) [2220J3K00102KXT](#) [2225J2500824KXT](#) [CCR07CG103KM](#) [CGA2B2C0G1H010C](#) [CGA2B2C0G1H040C](#)
[CGA2B2C0G1H050C](#) [CGA2B2C0G1H060D](#) [CGA2B2C0G1H070D](#) [CGA2B2C0G1H151J](#) [CGA2B2C0G1H1R5C](#) [CGA2B2C0G1H2R2C](#)
[CGA2B2C0G1H3R3C](#) [CGA2B2C0G1H680J](#) [CGA2B2C0G1H6R8D](#) [CGA2B2X8R1H221K](#) [CGA2B2X8R1H472K](#) [CGA3E1X7R1C474K](#)