



Receptacle
(COM Module)



Tape and Reel
for fully automated processing



Plug
(Carrier Board)

Colibri® for COM Express®

ept's **Colibri®** connector is a shielded, 2-row, SMT interconnect system in 0.5 mm pitch.

It is designed to meet the requirements according to specifications not only of PICMG COM Express®, but also of SFF-SIG Core Express®. Furthermore **Colibri®** products are compatible with all common connectors available on the market and extensively tested.

The connector system is available with 8 mm and 5 mm stacking height plus 220 and 440 pins.

Additional versions with flexible pin count as well as multiple stacking heights are available on request.


Key Features


- Meets the requirements of PICMG COM Express® and SFF-SIG CoreExpress®
- Intermatability with available connectors in the market
- Tested up to 5 Gbit/s; applications up to 8 Gbit/s possible
- Robust connector design
- Custom configurations in pin count
- Integrated Pick & Place area
- Packed in Tape & Reel

Applications


- COM Express®
- CoreExpress®
- Mezzanine Add-on Cards

COM  **Express®**







Technical Specifications		Colibri® for COM Express®	
		0.5 mm SMT Board-to-Board Connector System	
BASICS	Specification	PICMG® COM.0	
	No. of contacts	220 / 440	
	Termination technology	SMT	
	Operating temperature range	- 40 °C to + 85 °C	
MATERIAL	Insulator material	LCP, UL 94 V-0	
	Contact material	Copper alloy	
	Plating	Au over Ni	
MECHANICAL	Grid	0.5 mm	
	Mating force per pin	max. 0.9 N	
	Separating force per pin	min. 0.1 N	
	Durability	30 mating cycles	
	Coplanarity	max. 0.1 mm	
ELECTRICAL	Operational current	max. 0.5 A	
	Operating voltage	50 VAC	
	Contact resistance	max. 75 mΩ	
	Insulation resistance	> 100 MΩ	
	Test voltage	200 VAC	
	Data transfer rate	5 Gbit/s (8 Gbit/s)	
PROCESSING	Soldering temperature	260 °C per J-STD-020	
	MSL	1	
	Packaging	Tape and reel	
	Assembly	Pick and place	
APPROVAL	Flammability	UL pending	
	Environment	RoHS compliant	




Drawing shows version with 8 mm stacking height, dimensions in mm

Plug (Base Board)

No. of contacts	Colibri® Plug	
		
	Part number 8 mm stacking height	Part number 5 mm stacking height
220	401-55101-51	401-51101-51
220 with pick & place cap	401-55151-51	401-51151-51
440 with pick & place cap	401-55501-51	401-51501-51

Options – Tray packaging (please add VP1 to the part number!)	On request – Other contact numbers – Other stack heights – Different plating thickness	Note – For detailed information see customer drawing
---	--	---



Dimensions in mm

Receptacle (COM Module)

Colibri® Receptacle	
No. of contacts	Part number
220	402-51101-51
440	402-51501-51

<p>Options</p> <ul style="list-style-type: none"> – Tray packaging (please add VP1 to the part number!) 	<p>On request</p> <ul style="list-style-type: none"> – Other contact numbers – Different plating thickness 	<p>Note</p> <ul style="list-style-type: none"> – For detailed information see customer drawing
--	---	--

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [FFC & FPC Connectors](#) category:

Click to view products by [EPT manufacturer](#):

Other Similar products are found below :

[HFW11R-1STE1H1LF](#) [FH29B-100S-0.2SHW\(99\)](#) [FA5S008HP1](#) [FH29B-120S-0.2SHW\(99\)](#) [FH29B-80S-0.2SHW\(99\)](#) [FHS-16](#) [FPH-2022G](#)
[52610-1075](#) [52610-1275](#) [52610-1934](#) [XF3M\(1\)-1415-1B-R100](#) [501864-3091-TR225](#) [0525594033](#) [086210010340800](#) [086222026001800](#)
[52271-2869-CUT-TAPE](#) [62674-201121DLF](#) [62684-36210E9ALF](#) [52610-1675](#) [52746-1671-TR250](#) [10051922-2810EHLF](#) [6-520415-9](#)
[BD021-09A-A1-0350-0200-0550-LD](#) [SFV6R-1STE9HLF](#) [XF3M-2915-1B-R100](#) [1658549-1](#) [62674-221121ALF](#) [46214008010800](#)
[046298003000883](#) [151660622](#) [842-816-2630-035](#) [AYF530665TA](#) [AYF351525](#) [046296011930846+](#) [AYF352325A](#) [046254020000800+](#)
[FH19C-13S-0.5SH\(99\)](#) [FH39J-51S-0.3SHW\(99\)](#) [AYF355125A](#) [AYF530365TA](#) [FH29B-44S-0.2SHW\(99\)](#) [SFW5R-2STAE9LF](#) [AYF351125A](#)
[AYF350725A](#) [62684-502100AHLF](#) [FH39-61S-0.3SHW\(99\)](#) [AYF414035A](#) [10064555-172520HLF](#) [AYF212335A](#) [504754-2500](#)