


Section C-C



Kabeldaten Physical characteristics of the cable	
Drahtaufbau conductors	AWG 20/7 (0,56mm ²) Litzen verzinkt 20 AWG 7x28 (7x0,32mm ²) tinned stranded copper
Approbationen	UL 1007/1569 TR64
max. Betriebstemperatur max temperature rating	105°C
max. Betriebsspannung max electrical voltage rating	300V
Außendurchmesser +/- 3% Outer diameter	1,9mm
Biegeradius einmalig bending radius static	10mm
Biegeradius wiederholt bending radius in motion	20mm

Part Number	Number of conductors	Dim. L	Dim. A
169127	2	200	11,54
169128		400	
167355		500	
169129		600	
169130		800	
167356		1000	
167357		1500	
167358		2000	
169131	3	200	14,08
169132		400	
167359		500	
169133		600	
169134		800	
167360		1000	
167361		1500	
167362		2000	
169135	5	200	19,16
169136		400	
167363		500	
169137		600	
169138		800	
167364		1000	
167365		1500	
167366		2000	
169139	6	200	21,7
169140		400	
167367		500	
169141		600	
169142		800	
167368		1000	
167369		1500	
167370		2000	
169143	8	200	26,78
169144		400	
167371		500	
169145		600	
169146		800	
167372		1000	
167373		1500	
167374		2000	

Copyright by ERNI GmbH
Proprietary notice pursuant to ISO 16016 to be observed.

Information:		Tolerances		Scale 1.5:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		All Dimensions in mm		
Subject to modification without prior notice. Drawing will not be updated.		Designation MaxiBridge Standard Kabelkonfektionen MaxiBridge Standard Cable Assemblies		
		www.ERNI.com		167356
d	04.10.2010			I
Index	Date			A3
		Class		VERMAXI

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Computer Cables](#) category:

Click to view products by [ERNI](#) manufacturer:

Other Similar products are found below :

[68809-0004](#) [8F36-AAA105-1.00](#) [IB63](#) [CB-716EB-RS](#) [CB-716P8P9-RS](#) [CBK-11-290K-00](#) [ACL-10550](#) [ACL-10568-2](#) [ACL-10568-5](#)
[427522400-3](#) [426091300-3](#) [48000023](#) [10114976-P015002LF](#) [10111838-S444ALF](#) [88761-6101](#) [NT631C-CN321-EU](#) [ACL-10568NF-1](#)
[MIKROE-2092](#) [PCL-101100R-2E](#) [1700009405](#) [PS/2 Cable](#) [NT31C-CN323-EU](#) [PCL-10168H-1E](#) [68801-1905](#) [111068-1015](#) [100436-1107](#)
[68801-0630](#) [68801-3612](#) [68801-3618](#) [205058-1002](#) [PS2NK](#) [SATA cable](#) [96021-0000-00-0](#) [FAK-SMZSMZ 5M](#) [FAK-SMZSMZ-3M](#) [ACC-](#)
[500-200-R](#) [iW-C40-PCIe08-C1](#) [1700001531](#) [96048-0000-00-0](#) [96054-0000-00-0](#) [SATA III cable 30cm, down/straight](#) [cab-Pico-ITX-LVDS](#)
[PCL-101100SB-2E](#) [AXXSTCBLQAT](#) [NT31C-KBA05](#) [A2U4PSWCXCXK1](#) [2 port SATA to 5 pin,L=200mm](#) [P782-006-DH](#) [ACL-10568NF-](#)
[2](#) [PCL-101100R-1E](#)