

Elastische Einpresszone / *compliant pressfit zone*

Isolierwerkstoff / *housing material* : PBT GF30

Bauart 7 / *type 7*

Anforderungsstufe 2 = 400 Steckzyklen / *performance class 2 = 400 mating cycles*

Fehlende Masse und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Schichtaufbau im metallisierten Loch siehe Zeichnung 164062/Nr.6

diameter of drilled hole see drawing 164062/No.6

1) $\phi 1,0 \pm 0,09$ Durchmesser des metallisierten Loches


$\phi 1,0 \pm 0,09$ Diameter of finished plated-through hole

$\phi 1,15 \pm 0,025$ Bohrungsdurchmesser des Loches


$\phi 1,15 \pm 0,025$ Diameter of drilled hole

Bestückungsplan / *contact layout*

■ bestückt / *assemble*



Leiterplatten-Lochbild / *PCB drillhole pattern*



ohne Flansch

without flange

Information: All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.	Tolerances All Dimensions in mm	Scale 2:1
	Subject to modification without prior notice. Drawing will not be updated.	Designation Federleiste CD 128 EE Fem. Connector CD 128 Pressfit
www.ERNI.com	254844	I
Index	Date	N:00060804.SZA STVCD

Consider protection memo from DIN 34

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [ERNI manufacturer](#):

Other Similar products are found below :

[384307](#) [119812](#) [133420](#) [144310](#) [234063](#) [284136](#) [374144](#) [043593](#) [044847](#) [914083](#) [914070](#) [24070](#) [224473](#) [923766](#) [220245](#) [992215](#) [254498](#)
[294649](#) [234067](#) [413-853](#) [044846](#) [014375](#) [234066](#) [063388](#) [914538](#) [220012](#) [323759](#) [284172](#) [104518](#) [103649](#) [354338](#) [54546](#) [104087](#) [64622](#)
[234065](#) [839036](#) [464459](#) [973027](#) [973056](#) [354141](#) [164015](#) [134573](#) [104322](#) [933070](#) [254976](#) [254877](#) [384261](#) [063-349](#) [104086](#) [594211](#)