


Missing informations
and dimensions
see at DIN 41626

M 2:1



Masse nur informativ,
keine Prüfpläne erstellen.

Technical Data:

Insertion/withdrawal force per contact: $\leq 10\text{N} / \leq 1.6\text{N}$
 Mechanical operations: ≥ 500
 Contact resistance: $\leq 1\text{m}\Omega$

Operation Temperature: $-55^\circ\text{C} - +125^\circ\text{C}$

Solder temperature: according JEDEC 020C
 suitable assembly process: leadfree wave / reflow soldering

RoHS compliance: yes (6/6)

Designed for use with: right angle male DIN connector (M-style),
 straight male 2mm HM connector

Packaging: antistatic plastic bag
 Packaging unit: 100 pieces per bag
 Marking of packaging: label or direct printed on bag
 required date see ERNI labeling spec. 254792

Current	Cable cross area	AWG
10 A	1.5 mm ²	16
20 A	4 mm ²	12
40 A	10 mm ²	8

594225	1	40 A	2 - 4 μm NiP+ 0.1 μm Au	4.9-0.4	5.6	5.2
594223	1	20 A		2.8-0.5	3.7	4.0
594221	1	10 A		1.85+0.15 -0.05	2.6	3.0
594224	2	20 A	2 - 3 μm Ni min. 0.8 μm Au sel.	2.8-0.5	3.7	4.0
284821	1	40 A	2 - 3 μm Ni min. 1.3 μm Au sel.	4.9-0.4	5.6	5.2
284820	1	20 A		2.8-0.5	3.7	4.0
284819	1	10 A		1.85+0.15 -0.05	2.6	3.0
Part-No.	Class	Current	Plating	\varnothing A	\varnothing B	C

Information:		Tolerances		Scale	5:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation	
		www.ERNI.com		High Current Male Contact Hand Solder Termination	
		ERNI		053312	
t	18.06.2015			I	
Index	Date			A3	
				Class	STVSKO

Copyright by ERNI GmbH.
Proprietary notice pursuant to ISO 9006 to be observed.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Hard Metric Connectors](#) category:

Click to view products by [ERNI](#) manufacturer:

Other Similar products are found below :

[6345127-1](#) [646916-9](#) [6469658-1](#) [973108](#) [1-2000713-0](#) [1-2000713-2](#) [1-2000713-3](#) [1645343-1](#) [1645456-1](#) [1645594-1](#) [1645595-1](#) [1645601-1](#)
[1934822-1](#) [278071110010833](#) [1645179-1](#) [1645245-1](#) [1645457-1](#) [1645525-1](#) [1645570-1](#) [1645596-1](#) [17041102202](#) [1857470-1](#) [1934275-1](#)
[1934289-1](#) [1934759-1](#) [2000673-1](#) [2170292-2](#) [2-536642-6](#) [3-106015-1](#) [352188-1](#) [352629-1](#) [5120823-1](#) [5120899-1](#) [3-100145-0](#) [3-100147-0](#)
[3-100669-1](#) [3-106081-0](#) [HM2DK2368PLF](#) [5646530-1](#) [3-352049-0](#) [3-352069-0](#) [3-352115-0](#) [3-352638-0](#) [352189-1](#) [3-646357-0](#) [3-646487-0](#)
[3-646513-0](#) [104108](#) [106726-1](#) [114352](#)