

## 60 & 40 W, High Density, Compact Non-Dimmable CV Class 2 / Class II LED Drivers

Nominal Input Voltage	Max. Output Power	Nominal Output Voltage	Max. Output Current	Efficiency	Max. Case Temperature	THD	Power Factor
120 & 277, 220 to 240 Vac	60 W	12, 24, 48 Vdc	5, 2.5, 1.25 A	up to 93% typical	90°C (measured at the hot spot)	< 20%	> 0.9

### Models with Flying Leads, Aluminum Case:

L 130 x W 19.85 x H 19.85 mm  
(L 5.12 x W 0.78 x H 0.78 in)



### Models with "-S" Suffix, Bottom Leads with Studs, Aluminum Case:

L 130 x W 19.85 x H 23.85 mm  
(L 5.12 x W 0.78 x H 0.94 in)



### Models with "-T" Suffix (Terminal Blocks), Aluminum Case:

L 183.2 x W 19.85 x H 19.85 mm  
(L 7.12 x W 0.78 x H 0.78 in)



### FEATURES

- Very high power density of 20 W/in<sup>3</sup>
- Class 2 power supply
- UL Class P
- IP20-rated case with silicone-based potting
- 90° C maximum case hot spot temperature
- Lifetime: 50,000 hours min at 70° C case temperature
- Complies with ENERGY STAR®, DLC (DesignLight Consortium®) and CA Title 24 technical requirements
- Worldwide safety approvals



- Additional safety approvals when using the optional strain reliefs for models with "-T" suffix



ERP Part Number	Nominal Input Voltage (Vac)	Pout Max (W)	Vout Nom (Vdc)	Iout Min (A)	Iout Max (A)	Open Loop Voltage (No Load Vout Max) (Vdc)
<b>120 &amp; 277 VAC NOMINAL INPUT</b>						
<b>VLM40W</b>						
VLM40W-12	120 & 277	40	12	0.1	3.3	12.84
VLM40W-24	120 & 277	40	24	0.05	1.67	25.68
VLM40W-48	120 & 277	40	48	0.025	0.83	51.36
VLM40W-12-S	120 & 277	40	12	0.1	3.3	12.84
VLM40W-24-S	120 & 277	40	24	0.05	1.67	25.68
VLM40W-48-S	120 & 277	40	48	0.025	0.83	51.36
<b>VLM60W</b>						
VLM60W-12	120 & 277	60	12	0.1	5	12.84
VLM60W-24	120 & 277	60	24	0.05	2.5	25.68
VLM60W-48	120 & 277	60	48	0.025	1.25	51.36
VLM60W-12-S	120 & 277	60	12	0.1	5	12.84
VLM60W-24-S	120 & 277	60	24	0.05	2.5	25.68
VLM60W-48-S	120 & 277	60	48	0.025	1.25	51.36
<b>220 to 240 VAC NOMINAL INPUT</b>						
<b>VLM40E</b>						
VLM40E-12	220 to 240	40	12	0.1	3.3	12.84
VLM40E-24	220 to 240	40	24	0.05	1.67	25.68
VLM40E-12-T	220 to 240	40	12	0.1	3.3	12.84
VLM40E-24-T	220 to 240	40	24	0.05	1.67	25.68
VLM40E-48-T	220 to 240	40	48	0.025	0.83	51.36
<b>VLM60E</b>						
VLM60E-12	220 to 240	60	12	0.1	5	12.84
VLM60E-24	220 to 240	60	24	0.05	2.5	25.68
VLM60E-48	220 to 240	60	48	0.025	1.25	51.36
VLM60E-12-T	220 to 240	60	12	0.1	5	12.84
VLM60E-24-T	220 to 240	60	24	0.05	2.5	25.68
VLM60E-48-T	220 to 240	60	48	0.025	1.25	51.36

Suffix for the different mounting options:

- 1) NO suffix: side leads
- 2) "-T": Terminal blocks
- 3) "-S": Bottom lead exit with studs

For additional options of output current and output voltage, contact your sales representative or send an email to: [SaveEnergy@erp-power.com](mailto:SaveEnergy@erp-power.com)

### APPLICATIONS

- Strip lights
- Pendants
- Linears
- Cove Lights



### CHINA Operations

tel: +86-756-6266298  
No. 8 Pingdong Road 2  
Zhuhai, Guangdong, China 519060

[www.erp-power.com](http://www.erp-power.com)

[SaveEnergy@erp-power.com](mailto:SaveEnergy@erp-power.com)

### USA Headquarters

tel: +1-805-517-1300  
893 Patriot Drive, Suite E  
Moorpark, CA 93021, USA

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [LED Power Supplies](#) category:*

*Click to view products by [ERP Power](#) manufacturer:*

Other Similar products are found below :

[ESS015W-1000-12](#) [EUC-075S105DT](#) [PDA-WIFI](#) [PIFC-K250F](#) [PITB-K222A](#) [ALD-514012PJ134](#) [LB240S24KH](#) [LMH020-SPLC-0000-0000001](#) [LMD600-0100-C1A7-7030000](#) [79534](#) [79535](#) [EUG-200S210DT](#) [ESS030W-1050-21](#) [ESS030W-0900-32](#) [BPOXL 4-12-035](#) [SLM160W-3.9-40-ZA](#) [ESS010W-0180-42](#) [ESS010W-0350-24](#) [ESS010W-0200-42](#) [PDA080B-1A0G](#) [ESS010W-0500-12](#) [PDA150B-S1A5G](#) [ZPS-20](#) [SLM140W-1.05-130-ZA](#) [ESS040W-1400-27](#) [ESS015W-0700-18](#) [ESS010E-0250-42](#) [EVM120W-2700-42-ECN2](#) [EDC-100S105SV-0007](#) [79278](#) [EUD-150S350DVA](#) [LWA320-C420-ARK-B](#) [50304](#) [OT FIT 50/220-240/300 D L](#) [OT FIT 35/220-240/350 D CS L](#) [OT FIT 65/220-240/350 D CS L](#) [ELEMENT 30/220-240/700 S](#) [LC 75W 100-400MA 1-10V LP EXC](#) [LCA 35W 150-700MA ONE4ALL LP PRE](#) [LCA 50W 100-400MA ONE4ALL LP PRE](#) [LCA 50W 350-1050MA ONE4ALL LP PRE](#) [LCA 50W 350-1050MA 2XCH LP PRE](#) [LCI 150/325-1050/300 O4A SL PRE](#) [LCA 75W 100-400MA ONE4ALL LP PRE](#) [LCA 45W 500-1400MA ONE4ALL SC PRE](#) [LC 50W 100-400MA FLEXC LP EXC](#) [LCA 75W 350-1050MA ONE4ALL LP PRE](#) [LC 50W 350-1050MA FLEXC LP EXC](#) [LC 75W 350-1050MA FLEXC LP EXC](#) [LCA 75W 900-1800MA ONE4ALL LP PRE](#)